

General Description

3102 is a clear, high gloss, non-yellowing concrete and masonry surface sealer specially formulated of acrylic polymers in a VOC compliant solvent solution. This coating is outstanding in its ability to protect surfaces from staining and discoloration.

Uses

Very effective on exposed aggregate, concrete or concrete pavers to achieve the "wet" look, and to minimize discoloration caused by the rough texture trapping dirt particles. Clearglaze is an excellent all round weather proofing coating. Effective sealer for terazzo, stone, slate and unglazed tiles.

Protective coating for concrete and other substrates against occasional spills of acids, alkalis, food acids, oil, water based paints, and wet concrete.

For Exterior Use Only.

Physical Properties

Appearance	-	Clear liquid
Density (25 ⁰ C)	-	0.94 kg/litre (7.8 lb/U.S. gallon)
Dry Film Appearance	-	Clear
Drying Time (21 ⁰ C)	-	1 to 2 hours
Coverage	-	150 to 250 ft ² per U.S. gal (depending on porosity)
Solids	-	25%

Application Instructions

Make sure surface is free of oil and dirt. This can be achieved by scrubbing with a soap solution of trisodium phosphate or Paveclean solution. After cleaning, rinse the surface thoroughly and let dry.

Apply 3102 by roller or low pressure sprayer. Caution should be used when rolling at temperatures above 20°C. Do not apply in direct sunlight.

Apply in thin coats. Wait a minimum of 2 hours between coats.

Not for use as a Cure and Seal. Please use Clearcoat 3101 for curing. Allow concrete to cure a minimum of 7 days before applying 3102 Clearglaze.

Do not thin. Tools can be cleaned up with xylene or Resolve after use.

Sealed surfaces may be slippery. Addition of 3115 Sure Foot Anti Slip Additive is recommended.

Packaging

Clearglaze is available in 3.78 ltr (1 U.S. gal), 18.93 ltr (5 U.S. gal), and 205 ltr (55 U.S. gal.) drums.