



2016 SPEC-BRIK® Detailing Guide

www.concreteproductsgroup.com

800-789-0872

Table of Contents

INTRODUCTION

Moisture Control Strategies

INTERACTIVE FLASHING MAP

SECTION I SPEC-BRIK AND SPEC-BRIK WCT

SECTION II CONSTRUCTION DETAILS

Foundation and Base of Wall Details- Navigation Page

Figure 1. Moisture Movement in a Typical Wall

Figure 2. Exterior, Spec-Brik Foundation and Pad

Figure 3. Exterior, Poured Foundation and Pad

Figure 4. Exterior, CMU Foundation, and Insulative Aggregates

Figure 5. Exterior, Poured Foundation, Pad and Insulative Aggregates

Figure 6. Exterior, Below Grade CMU Wall, and Insulative Aggregates

Figure 7. Exterior, CMU Foundation, and Insulative Aggregates

Figure 8. Exterior, Z-Cord Weep, CMU Foundation, Insulative Aggregates

Figure 9. Exterior, Z-Cord Weep, Below Grade CMU

Figure 10. Exterior, Z-Cord Weep, Poured Foundation

Figure 11. Z-cord flashing detail

Window Sills, Jambs and Lintels - Navigation Page

Figure 12. Window Sill

Figure 13. Window Jamb

Figure 14. Window Lintel

Joint Reinforcement and Movement Joints- Navigation Page

Figure 15. Joint Reinforcement

Figure 16. Movement Joint

Figure 16a. Movement Joint 3D rendering

Planks and Parapets- Navigation Page

Figure 17. Pre-Cast Plank Option 1

Figure 18. Pre-Cast Plank Option 2

Figure 19. Pre-Cast Plank (Non Bearing) Option 3

Figure 20. Pre-Cast Plank (Non Bearing) Option 4

Figure 21. Roof Parapet

SECTION III - CODE REFERENCES

SECTION IV - GUIDE SPECIFICATION

SECTION VI - SPEC-BRIK COLOR GUIDE

MEMBER LOCATION MAP

Introduction

Masonry is one of the oldest and most prevalent construction materials available, but many designers are not aware of its numerous performance benefits including structural soundness, fire resistance, mold resistance, energy efficiency, superior durability and sustainability. By combining the well known beneficial properties of concrete masonry with the latest developments in construction technology, we can provide owners with truly high performance building envelopes that are safe, cost-effective, withstand extreme weather conditions, and energy efficient. Masonry is perfect for providing long lasting comfort and structural integrity. These benefits make concrete masonry an excellent choice for the creation of a sustainable building.

Masonry not only meets extreme design parameters, it also offers the flexibility to design projects that balance cost concerns against typical project requirements including time of construction, Code and contractual requirements, and aesthetics. In this Guide, we will offer strategies that will deliver high performance and cost-effective building envelopes using a versatile single wythe masonry wall system: SPEC-BRIK®, which combines the aesthetic appeal of brick with the cost-effectiveness of concrete masonry.

What is High Performance Concrete Masonry?

High Performance Concrete Masonry uses state of the industry best practices relating to the construction of concrete masonry and related building envelope components to produce a building envelope that efficiently meets or exceeds project requirements in a cost-effective manner. While these techniques comply with Code, they also in many instances include additional recommendations that can deliver superior results when it comes to moisture protection, energy efficiency, or other key issues.

Comprehensive Construction Details

This Guide includes a set of Construction Details that offer high performance recommendations for how to detail a variety of common structural elements. Each detail is supported by typical notes and a set of supporting Code references.

A key focus of the details is moisture control. We have attempted in the details, to provide guidance for a comprehensive approach to moisture control (some might refer to this as a “belt and suspenders” approach) for long lasting superior performance. There are several general principles in the construction details that address the primary design challenges. It is useful to look at these challenges in a generally applicable way in order to understand what is driving the details. Table 1 lists the common moisture control challenges and how they are addressed in the Guide Details.

Design Issue	Strategies
Condensation at thermal bridge areas (bond beams, lintels, anchorage points, wall base)	<ul style="list-style-type: none"> • Use of WCT™ Block • Integral Water Repellent in block and mortar • Insulate and isolate thermal bridge • Air/Vapor Barrier adjacent to masonry on interior • Consider use of Lighter Weight Block and Grout
Ground moisture penetration (from landscape irrigation, soil condensation and other sources)	<ul style="list-style-type: none"> • Waterproofing of below grade wall area • Insulation • Exterior drainage- Aprons, splashes or tapered soil zone; diversion of stormwater • Integral Water Repellent • Moisture barriers under pad • Elevation offset
Base of Wall Saturation (snow and ice or stormwater accumulation)	<ul style="list-style-type: none"> • Integral Water Repellent • Full grouting
Inadequate Drainage at Collection Points	<ul style="list-style-type: none"> • Flashing and weeps-- protected during coating or sealing

Table 1- Moisture Control Strategies

Table of Contents	
Introduction	1
1.1 Purpose	1
1.2 Scope	1
1.3 References	1
2.0 Moisture Control	2
2.1 General	2
2.2 Condensation	2
2.3 Ground Moisture Penetration	2
2.4 Base of Wall Saturation	2
2.5 Inadequate Drainage at Collection Points	2
3.0 Appendix	3
3.1 Appendix A	3
3.2 Appendix B	3
3.3 Appendix C	3
3.4 Appendix D	3
3.5 Appendix E	3
3.6 Appendix F	3
3.7 Appendix G	3
3.8 Appendix H	3
3.9 Appendix I	3
3.10 Appendix J	3
3.11 Appendix K	3
3.12 Appendix L	3
3.13 Appendix M	3
3.14 Appendix N	3
3.15 Appendix O	3
3.16 Appendix P	3
3.17 Appendix Q	3
3.18 Appendix R	3
3.19 Appendix S	3
3.20 Appendix T	3
3.21 Appendix U	3
3.22 Appendix V	3
3.23 Appendix W	3
3.24 Appendix X	3
3.25 Appendix Y	3
3.26 Appendix Z	3
4.0 Glossary	4
5.0 Index	5
6.0 Appendix	6
6.1 Appendix A	6
6.2 Appendix B	6
6.3 Appendix C	6
6.4 Appendix D	6
6.5 Appendix E	6
6.6 Appendix F	6
6.7 Appendix G	6
6.8 Appendix H	6
6.9 Appendix I	6
6.10 Appendix J	6
6.11 Appendix K	6
6.12 Appendix L	6
6.13 Appendix M	6
6.14 Appendix N	6
6.15 Appendix O	6
6.16 Appendix P	6
6.17 Appendix Q	6
6.18 Appendix R	6
6.19 Appendix S	6
6.20 Appendix T	6
6.21 Appendix U	6
6.22 Appendix V	6
6.23 Appendix W	6
6.24 Appendix X	6
6.25 Appendix Y	6
6.26 Appendix Z	6
7.0 Appendix	7
7.1 Appendix A	7
7.2 Appendix B	7
7.3 Appendix C	7
7.4 Appendix D	7
7.5 Appendix E	7
7.6 Appendix F	7
7.7 Appendix G	7
7.8 Appendix H	7
7.9 Appendix I	7
7.10 Appendix J	7
7.11 Appendix K	7
7.12 Appendix L	7
7.13 Appendix M	7
7.14 Appendix N	7
7.15 Appendix O	7
7.16 Appendix P	7
7.17 Appendix Q	7
7.18 Appendix R	7
7.19 Appendix S	7
7.20 Appendix T	7
7.21 Appendix U	7
7.22 Appendix V	7
7.23 Appendix W	7
7.24 Appendix X	7
7.25 Appendix Y	7
7.26 Appendix Z	7
8.0 Appendix	8
8.1 Appendix A	8
8.2 Appendix B	8
8.3 Appendix C	8
8.4 Appendix D	8
8.5 Appendix E	8
8.6 Appendix F	8
8.7 Appendix G	8
8.8 Appendix H	8
8.9 Appendix I	8
8.10 Appendix J	8
8.11 Appendix K	8
8.12 Appendix L	8
8.13 Appendix M	8
8.14 Appendix N	8
8.15 Appendix O	8
8.16 Appendix P	8
8.17 Appendix Q	8
8.18 Appendix R	8
8.19 Appendix S	8
8.20 Appendix T	8
8.21 Appendix U	8
8.22 Appendix V	8
8.23 Appendix W	8
8.24 Appendix X	8
8.25 Appendix Y	8
8.26 Appendix Z	8
9.0 Appendix	9
9.1 Appendix A	9
9.2 Appendix B	9
9.3 Appendix C	9
9.4 Appendix D	9
9.5 Appendix E	9
9.6 Appendix F	9
9.7 Appendix G	9
9.8 Appendix H	9
9.9 Appendix I	9
9.10 Appendix J	9
9.11 Appendix K	9
9.12 Appendix L	9
9.13 Appendix M	9
9.14 Appendix N	9
9.15 Appendix O	9
9.16 Appendix P	9
9.17 Appendix Q	9
9.18 Appendix R	9
9.19 Appendix S	9
9.20 Appendix T	9
9.21 Appendix U	9
9.22 Appendix V	9
9.23 Appendix W	9
9.24 Appendix X	9
9.25 Appendix Y	9
9.26 Appendix Z	9

Summary of Moisture Control Tools:

A comprehensive approach to moisture control should consider the following complementary elements:

Surface Protection

- Properly tooled Mortar Joints
- Post-Applied Penetrating Breathable Sealants –or–
- Post-Applied Exterior Breathable Film Forming Coatings
- Masonry appropriate Bead or Gap Sealers (with primer)
- Masonry Accessories

Internal Protection

- Integral Water Repellents in CMU and mortar
- Block Design features (Water Control Technology - WCT™)
- Non-absorptive Integral Insulation
- Integral Air/Vapor Barriers
- Joint and Structural Reinforcement (movement and crack control Design Details)
- Collection, Drainable Flashing, Drainable Drip Edges, Drainable Weeps, and Drainable Vent Systems
- Vestibules, and Roof or Window Projections
- Building Aprons

A Note About Masonry Flashing

There are many types of flashing available today, each with its own characteristics. This Guide assumes design and construction compliance with applicable Building Codes as amended and adopted. A Flashing map is included in the [next section](#) to show the typical locations where flashing should be considered. Further, and when applicable, the Guide assumes the use of flashing (whether generic, specialized or proprietary, partial or completely through-wall, etc). Yet it also reflects the choices and options available to the Design Community rather than insisting on any particular type of primary and secondary moisture control strategy (belt-and-suspenders approach) regarding a particular project.

For instance there are circumstances where a member of the Design Community with permission of the Certified Building Official (via Plan Review, etc.) may choose primary and secondary methods of moisture control other than the inclusion of flashing. As an example when very heavy reinforcement and grouting is required, generic flashing may be considered impractical or onerous within a multi- or single-wythe masonry wall. Similar alternate strategies may be chosen for uniform masonry barrier wall elements. Solid grouted composite (completely grouted - including collar joints - multi-wythe masonry; see Masonry Code TMS 402 definition), solid grouted non-composite multi-wythe masonry walls, and solid grouted single-wythe walls are all considered barrier walls.

Codes and Standards References

There are numerous provisions of Code that are applicable to the construction of masonry walls, many of which are found in sections that may not intuitively seem to be related to masonry. Similarly, there are a variety of applicable standards that may related to other building components or general areas of concern such as energy conservation. We have included a comprehensive set of references to applicable Codes and Standards for the construction of structures using masonry. These are based on Model Code provisions. As always, designers should look to the local Code requirements for guidance on particular projects.

Guide Specification

The recommendations incorporated in the construction details are also supported by the Spec-Brik® guide specification, which is an adaptation of an industry standard specification.

Color Selection Guide

This manual has a selection of images of the standard Spec-Brik colors [here](#) to assist in color selection. We strongly recommend that actual physical samples be used for color selection, since the depiction of colors digitally is subject to significant variation due to the considerable variability of the color calibration of computer screens and printers. Use the images for find the closest match to your preference and then request a color sample so that you can preferably view the sample in the lighting conditions that will prevail at the building site.

Design Resource Center

The Concrete Products Group has a dedicated website to provide designers access to design tools, the Design Resource Center, which is a registration based site. The site includes a variety of resources including downloadable versions of the details in this manual in AutoCAD® or Revit formats, our Masonry Designer color catalog and Revit Plug-in, design and construction notes and videos, and other helpful resources. You can request free registration to the site at this link:



[Design Resource Center Access Page](#)



Table of Contents	
Introduction	1
1.1 Purpose	1
1.2 Scope	1
1.3 Organization	1
2.0 General Requirements	2
2.1 Materials	2
2.2 Workmanship	2
2.3 Inspection	2
2.4 Testing	2
2.5 Safety	2
3.0 Masonry Construction	3
3.1 Foundations	3
3.2 Walls	3
3.3 Parapets	3
3.4 Roofs	3
3.5 Windows	3
3.6 Doors	3
3.7 Stairs	3
3.8 Elevators	3
3.9 Other	3
4.0 Details	4
4.1 Foundations	4
4.2 Walls	4
4.3 Parapets	4
4.4 Roofs	4
4.5 Windows	4
4.6 Doors	4
4.7 Stairs	4
4.8 Elevators	4
4.9 Other	4
5.0 Appendix	5
5.1 Glossary	5
5.2 Index	5
5.3 Bibliography	5
5.4 Other	5



**CONCRETE
PRODUCTS
GROUP**



Click on one of the views to get started

Interactive Flashing Map

Table of Contents	
Introduction	1
1.1 Purpose	1
1.2 Scope	1
1.3 Audience	1
1.4 References	1
2. Flashing Locations	2
2.1 Flashing above bond beams supporting roof assembly	2
2.2 Flashing above bond beams supporting floor plank assembly	2
2.3 Flashing above bond beams/benches above windows or doors	2
2.4 Flashing above grade beams at foundation	2
3. Flashing Systems	3
3.1 Parapet Cap and Flashing System	3
3.2 Flashing/weep system with drip edge beneath window sills	3
3.3 Flashing/weep system above bond beams/benches above windows or doors	3
3.4 Flashing/weep system with drip edge beneath window sills	3
3.5 Flashing and weeps system above grade beams at foundation	3
4. Flashing Details	4
4.1 Flashing above bond beams supporting roof assembly	4
4.2 Flashing above bond beams supporting floor plank assembly	4
4.3 Flashing above bond beams/benches above windows or doors	4
4.4 Flashing above grade beams at foundation	4
5. Flashing Materials	5
5.1 Flashing/weep system with drip edge beneath window sills	5
5.2 Flashing/weep system above bond beams/benches above windows or doors	5
5.3 Flashing/weep system with drip edge beneath window sills	5
5.4 Flashing and weeps system above grade beams at foundation	5
6. Flashing Installation	6
6.1 Flashing above bond beams supporting roof assembly	6
6.2 Flashing above bond beams supporting floor plank assembly	6
6.3 Flashing above bond beams/benches above windows or doors	6
6.4 Flashing above grade beams at foundation	6
7. Flashing Maintenance	7
7.1 Flashing/weep system with drip edge beneath window sills	7
7.2 Flashing/weep system above bond beams/benches above windows or doors	7
7.3 Flashing/weep system with drip edge beneath window sills	7
7.4 Flashing and weeps system above grade beams at foundation	7
8. Flashing Inspection	8
8.1 Flashing above bond beams supporting roof assembly	8
8.2 Flashing above bond beams supporting floor plank assembly	8
8.3 Flashing above bond beams/benches above windows or doors	8
8.4 Flashing above grade beams at foundation	8
9. Flashing Repairs	9
9.1 Flashing/weep system with drip edge beneath window sills	9
9.2 Flashing/weep system above bond beams/benches above windows or doors	9
9.3 Flashing/weep system with drip edge beneath window sills	9
9.4 Flashing and weeps system above grade beams at foundation	9
10. Flashing Replacement	10
10.1 Flashing above bond beams supporting roof assembly	10
10.2 Flashing above bond beams supporting floor plank assembly	10
10.3 Flashing above bond beams/benches above windows or doors	10
10.4 Flashing above grade beams at foundation	10
11. Flashing Removal	11
11.1 Flashing/weep system with drip edge beneath window sills	11
11.2 Flashing/weep system above bond beams/benches above windows or doors	11
11.3 Flashing/weep system with drip edge beneath window sills	11
11.4 Flashing and weeps system above grade beams at foundation	11
12. Flashing Disposal	12
12.1 Flashing above bond beams supporting roof assembly	12
12.2 Flashing above bond beams supporting floor plank assembly	12
12.3 Flashing above bond beams/benches above windows or doors	12
12.4 Flashing above grade beams at foundation	12
13. Flashing Storage	13
13.1 Flashing/weep system with drip edge beneath window sills	13
13.2 Flashing/weep system above bond beams/benches above windows or doors	13
13.3 Flashing/weep system with drip edge beneath window sills	13
13.4 Flashing and weeps system above grade beams at foundation	13
14. Flashing Transportation	14
14.1 Flashing above bond beams supporting roof assembly	14
14.2 Flashing above bond beams supporting floor plank assembly	14
14.3 Flashing above bond beams/benches above windows or doors	14
14.4 Flashing above grade beams at foundation	14
15. Flashing Safety	15
15.1 Flashing/weep system with drip edge beneath window sills	15
15.2 Flashing/weep system above bond beams/benches above windows or doors	15
15.3 Flashing/weep system with drip edge beneath window sills	15
15.4 Flashing and weeps system above grade beams at foundation	15
16. Flashing Quality Control	16
16.1 Flashing above bond beams supporting roof assembly	16
16.2 Flashing above bond beams supporting floor plank assembly	16
16.3 Flashing above bond beams/benches above windows or doors	16
16.4 Flashing above grade beams at foundation	16
17. Flashing Record Keeping	17
17.1 Flashing/weep system with drip edge beneath window sills	17
17.2 Flashing/weep system above bond beams/benches above windows or doors	17
17.3 Flashing/weep system with drip edge beneath window sills	17
17.4 Flashing and weeps system above grade beams at foundation	17
18. Flashing Training	18
18.1 Flashing above bond beams supporting roof assembly	18
18.2 Flashing above bond beams supporting floor plank assembly	18
18.3 Flashing above bond beams/benches above windows or doors	18
18.4 Flashing above grade beams at foundation	18
19. Flashing Documentation	19
19.1 Flashing/weep system with drip edge beneath window sills	19
19.2 Flashing/weep system above bond beams/benches above windows or doors	19
19.3 Flashing/weep system with drip edge beneath window sills	19
19.4 Flashing and weeps system above grade beams at foundation	19
20. Flashing Reporting	20
20.1 Flashing above bond beams supporting roof assembly	20
20.2 Flashing above bond beams supporting floor plank assembly	20
20.3 Flashing above bond beams/benches above windows or doors	20
20.4 Flashing above grade beams at foundation	20
21. Flashing Summary	21
21.1 Flashing/weep system with drip edge beneath window sills	21
21.2 Flashing/weep system above bond beams/benches above windows or doors	21
21.3 Flashing/weep system with drip edge beneath window sills	21
21.4 Flashing and weeps system above grade beams at foundation	21

Flashing Locations - *Flashing should be placed above any interruption in the vertical drainage plane of the wall assembly*

Flash above bond beams supporting roof assembly
[Click to see detail](#)

Use Parapet Cap and Flashing System
[Click to see detail](#)

Use flashing/weep system with drip edge beneath window sills.
[Click to see detail](#)

Flash above bond beam supporting floor plank assembly
[Click to see detail](#)

Use flashing weep system above bond beams/lintels above windows or doors
[Click to see detail](#)

Flashing and weeps system above grade beams at foundation
[Click to see detail](#)





Table of Contents	
Introduction	1
Flashing Locations	2
Flashing Details	3
Flashing Systems	4
Flashing Materials	5
Flashing Installation	6
Flashing Maintenance	7
Flashing Troubleshooting	8
Flashing Specifications	9
Flashing Standards	10
Flashing Codes	11
Flashing References	12
Flashing Glossary	13
Flashing Index	14



Flashing and weep system above bond beams supporting roof assembly
[Click to see detail](#)

Flash above bond beams supporting floor plank assembly
[Click to see detail](#)

Use flashing weep system above bond beams/lintels above windows or doors
[Click to see detail](#)

Use flashing weep system with drip edges beneath window sills
[Click to see Detail](#)

Flashing and weeps system above grade beams at foundation
[Click to see Detail](#)







Table of Contents

1	Introduction
2	Flashing and Weep System
3	Roof Assembly
4	Floor Plank Assembly
5	Lintels Above Windows or Doors
6	Window Sills
7	Foundation Beams
8	Conclusion




Flashing weep system
above bond beams
supporting roof assembly
[Click to see detail](#)

Flash above bond
beams supporting floor
plank assembly
[Click to see detail](#)

Use flashing weep system
above bond beams/lintels
above windows or doors
[Click to see detail](#)

Use flashing weep system
with drip edges beneath
window sills
[Click to see detail](#)

Flashing and weeps
system above grade beams at
foundation
[Click to see detail](#)





Section I SPEC-BRIK[®] and SPEC-BRIK WCT[™]

Table of Contents	
Section I	Section I - SPEC-BRIK and SPEC-BRIK WCT
Section I-1	Section I-1 - General Notes
Section I-2	Section I-2 - Installation
Section I-3	Section I-3 - Maintenance
Section I-4	Section I-4 - Specifications
Section I-5	Section I-5 - Performance
Section I-6	Section I-6 - Warranty
Section I-7	Section I-7 - Other Information
Section I-8	Section I-8 - Appendix
Section I-9	Section I-9 - Glossary
Section I-10	Section I-10 - Index
Section I-11	Section I-11 - Bibliography
Section I-12	Section I-12 - References
Section I-13	Section I-13 - Figures
Section I-14	Section I-14 - Tables
Section I-15	Section I-15 - Drawings
Section I-16	Section I-16 - Photographs
Section I-17	Section I-17 - Videos
Section I-18	Section I-18 - Audio
Section I-19	Section I-19 - Other Media
Section I-20	Section I-20 - Miscellaneous

CONCRETE PRODUCTS GROUP

SPEC-BRIK® Concrete Masonry Units

SPEC-BRIK units are integrally pigmented smooth textured units that have the appearance of brick. They are typically available in “half-high” heights - nominal 4” height - to match the aesthetics of brick (Full height - nominal 8” high unit- are also available). Architectural half high masonry units are a very cost-effective and durable method to match the aesthetics that a traditional brick veneer cavity wall would offer.



Table of Contents	
Introduction	Section 02100 - Masonry
Product Description	Part 1 - Summary
Material Requirements	1.1 Section Includes
Installation Requirements	1.2 Related Sections
Quality Assurance	1.3 Materials
Construction Requirements	1.4 Execution
1.5 Submittals	1.5.1 Shop Drawings
1.6 Installation	1.5.2 Material Samples
1.7 Finishing	1.6 Quality Assurance
1.8 Protection	1.6.1 Material Tests
1.9 Maintenance	1.6.2 Mockup
1.10 Cleaning	1.6.3 Field Inspection
1.11 Painting	1.6.4 Construction Schedule
1.12 Other	1.6.5 Workmanship
1.13 Safety	1.6.6 Acceptance
1.14 Other	1.6.7 Closeout
1.15 Other	1.6.8 Final Inspection
1.16 Other	1.6.9 Final Approval
1.17 Other	1.6.10 Final Report
1.18 Other	1.6.11 Final Payment
1.19 Other	1.6.12 Final Closeout
1.20 Other	1.6.13 Final Sign-off
1.21 Other	1.6.14 Final Acceptance
1.22 Other	1.6.15 Final Release
1.23 Other	1.6.16 Final Completion
1.24 Other	1.6.17 Final Handover
1.25 Other	1.6.18 Final Project Review
1.26 Other	1.6.19 Final Project Report
1.27 Other	1.6.20 Final Project Summary
1.28 Other	1.6.21 Final Project Evaluation
1.29 Other	1.6.22 Final Project Feedback
1.30 Other	1.6.23 Final Project Lessons Learned
1.31 Other	1.6.24 Final Project Archive
1.32 Other	1.6.25 Final Project Closure
1.33 Other	1.6.26 Final Project Sign-off
1.34 Other	1.6.27 Final Project Release
1.35 Other	1.6.28 Final Project Completion
1.36 Other	1.6.29 Final Project Handover
1.37 Other	1.6.30 Final Project Review
1.38 Other	1.6.31 Final Project Report
1.39 Other	1.6.32 Final Project Summary
1.40 Other	1.6.33 Final Project Evaluation
1.41 Other	1.6.34 Final Project Feedback
1.42 Other	1.6.35 Final Project Lessons Learned
1.43 Other	1.6.36 Final Project Archive
1.44 Other	1.6.37 Final Project Closure
1.45 Other	1.6.38 Final Project Sign-off
1.46 Other	1.6.39 Final Project Release
1.47 Other	1.6.40 Final Project Completion
1.48 Other	1.6.41 Final Project Handover
1.49 Other	1.6.42 Final Project Review
1.50 Other	1.6.43 Final Project Report
1.51 Other	1.6.44 Final Project Summary
1.52 Other	1.6.45 Final Project Evaluation
1.53 Other	1.6.46 Final Project Feedback
1.54 Other	1.6.47 Final Project Lessons Learned
1.55 Other	1.6.48 Final Project Archive
1.56 Other	1.6.49 Final Project Closure
1.57 Other	1.6.50 Final Project Sign-off
1.58 Other	1.6.51 Final Project Release
1.59 Other	1.6.52 Final Project Completion
1.60 Other	1.6.53 Final Project Handover
1.61 Other	1.6.54 Final Project Review
1.62 Other	1.6.55 Final Project Report
1.63 Other	1.6.56 Final Project Summary
1.64 Other	1.6.57 Final Project Evaluation
1.65 Other	1.6.58 Final Project Feedback
1.66 Other	1.6.59 Final Project Lessons Learned
1.67 Other	1.6.60 Final Project Archive
1.68 Other	1.6.61 Final Project Closure
1.69 Other	1.6.62 Final Project Sign-off
1.70 Other	1.6.63 Final Project Release
1.71 Other	1.6.64 Final Project Completion
1.72 Other	1.6.65 Final Project Handover
1.73 Other	1.6.66 Final Project Review
1.74 Other	1.6.67 Final Project Report
1.75 Other	1.6.68 Final Project Summary
1.76 Other	1.6.69 Final Project Evaluation
1.77 Other	1.6.70 Final Project Feedback
1.78 Other	1.6.71 Final Project Lessons Learned
1.79 Other	1.6.72 Final Project Archive
1.80 Other	1.6.73 Final Project Closure
1.81 Other	1.6.74 Final Project Sign-off
1.82 Other	1.6.75 Final Project Release
1.83 Other	1.6.76 Final Project Completion
1.84 Other	1.6.77 Final Project Handover
1.85 Other	1.6.78 Final Project Review
1.86 Other	1.6.79 Final Project Report
1.87 Other	1.6.80 Final Project Summary
1.88 Other	1.6.81 Final Project Evaluation
1.89 Other	1.6.82 Final Project Feedback
1.90 Other	1.6.83 Final Project Lessons Learned
1.91 Other	1.6.84 Final Project Archive
1.92 Other	1.6.85 Final Project Closure
1.93 Other	1.6.86 Final Project Sign-off
1.94 Other	1.6.87 Final Project Release
1.95 Other	1.6.88 Final Project Completion
1.96 Other	1.6.89 Final Project Handover
1.97 Other	1.6.90 Final Project Review
1.98 Other	1.6.91 Final Project Report
1.99 Other	1.6.92 Final Project Summary
2.00 Other	1.6.93 Final Project Evaluation
2.01 Other	1.6.94 Final Project Feedback
2.02 Other	1.6.95 Final Project Lessons Learned
2.03 Other	1.6.96 Final Project Archive
2.04 Other	1.6.97 Final Project Closure
2.05 Other	1.6.98 Final Project Sign-off
2.06 Other	1.6.99 Final Project Release
2.07 Other	1.7000 Final Project Completion

CONCRETE PRODUCTS GROUP



Countless Aesthetic Options
with SPEC-BRIK®



Color


SPEC-BRIK is available in 12 standard colors and custom colors are available by special order.



Birmingham Blend



Chesapeake Blend



Delaware Blend



Dixon Blend



Gardner Blend



Houston Blend




Jefferson City Blend



Panama City Blend



Philadelphia Blend



St. Cloud Blend



Stanton Blend



Syracuse Blend

SPEC-BRIK® Colors
Click Color to See Larger Image

Masonry Designer Software

Masonry Designer Software is available at www.concreteproducts.com. This software allows designers to render wall sections with all CPG products and colors, including Spec-Brik, Spec-Block (grey CMU), and Spec-Split (Architectural Split face CMU). The program allows selection of both block and mortar colors, and allows experimentation with combinations of different colors and textures

Spec-Brik Key Features

ASTM Standard: SPEC-BRIK® Architectural Masonry units are load-bearing concrete masonry units that meet ASTM C 90.

Unit Compressive Strength: ASTM C 90 requires that load-bearing masonry units have a 1900 psi minimum net area compressive strength. There are however, advantages to raising the compressive strength to 2000 psi, as this will allow more efficient structural designs.

Unit Dimensions: Nominal 4" [8"] height x 4" [8" or 12"] depth x 16" [8"] length. Nominal dimensions for masonry take into account the thickness of mortar joints, which are typically 3/8". As a result, the actual dimensions are: 4" nominal = 3-5/8" actual; 8" nominal = 7-5/8" actual and 16" nominal = 15-5/8" actual.

Integral Water Repellent: In most jurisdictions, the use of integral water repellent admixtures (IWR) in both the concrete masonry units and mortar for single wythe masonry structures is highly recommended as part of a belt-and-suspenders moisture control strategy. The standard specification for Spec-Brik™ includes IWR.


In California, due to unique code requirements, IWR needs to be used in the mortar but not necessarily within the block. The distinction of when to include IWR within CMU is project dependent. In such cases the use of a compatible post-applied drainable and breathable wall sealer is one method used to seal the block and mortar.

Integral Water Repellent Admixtures are typically a polymeric material. For CMU that it is mixed into the concrete mix design at the manufacturing plant. Assuming masonry walls are designed, constructed, and maintained correctly as applicable to project conditions, and when used in accordance with the supplier's warranty, IWR should last the lifetime of the concrete masonry unit and help reduce the possibility of efflorescence. Proper design and construction does not assume repeated exposure to improper roof or floor drainage, prolonged plumbing leaks, irrigation sprinklers or related hydrostatic head pressures, salt-spray, landscape and related chemicals, nor expansive and/or sulfate-bearing soils, for example without additional means and methods to resist associated deleterious and/or corrosive effects. Be sure to specify the use of a compatible integral water repellent admixture in the mortar.

Table of Contents	
Introduction	1
Product Overview	2
Technical Specifications	3
Installation Guidelines	4
Maintenance and Care	5
Color Selection	6
Ordering Information	7
Warranty	8
Contact Us	9
Index	10

SPEC-BRIK WCT™

SPEC-BRIK WCT™ is a new, patent-pending block design that encourages proper drainage of moisture in concrete masonry walls. WCT stands for “Water Control Technology”. SPEC-BRIK WCT™ is particularly well-suited for use in single wythe masonry walls due to its design elements that redirect any moisture that penetrates into the wall shell downward to the wall’s flashing and weep drainage systems. WCT, however, can be an excellent complement to any comprehensive moisture control strategy for masonry construction, and is available in a variety of shapes for the construction of single or multi-wythe walls.



Spec-Brik® WCT™

Video Showing WCT under Extreme Test Conditions (requires internet connection):

[Video](#)

Key Features


Moisture Control Features. SPEC-BRIK WCT™ uses specially designed drainage zones on the top web of the block, along with subtle texturing and other features to redirect the path of moisture that would otherwise tend to move laterally across the block web towards the interior surface of the wall.

Adaptability. WCT can be employed on a variety of block shapes and fittings. It is invisible from any external viewing angle once the block has been put in place, so it allows the construction of corners or ends without any aesthetic or structural concerns.

Ease of Use. WCT is installed using standard materials and techniques. Integral Water Repellent (IWR) is used in the mortar and block.

Compatibility. WCT works perfectly with traditional moisture control techniques and materials. Each block contains IWR.

Compliance with ASTM Standard: SPEC-BRIK® WCT™ units are load-bearing concrete masonry units that have been tested for compliance with ASTM C 90.



Using Sample Panels - A Proven Method to Drive Successful Results.

In general, the designer should follow the requirements of the most current edition of the “Building Code Requirements and Specification for Masonry Structures”

The jobsite sample panel must be constructed and approved before the masonry work begins on the project. All samples and submittals except the mortar color must be approved before the jobsite sample panel is constructed.

Mortar joint color and tooling greatly influence the finished appearance of the wall and must be approved in the sample panel, and tooled by the mason contractor selected for the project.

Construct the sample panel on the jobsite at a highly visible location where it will not be disturbed before the completion of this project. Use only the materials that were approved in the submittal review and masonry units that were already manufactured for this project.

The contractor should place orders for jobsite sample panel materials with masonry producers so that they have advance notice to manufacture and collect the full range of color for the building for shipment on a separate pallet.

The minimum size of the sample panel dimensions must be at least 4 ft. by 4 ft. A larger panel may allow more options to test cleaning and sealing. One approach is to build a sample panel that is 4ft by 8ft in order to demonstrate how the wall looks both before and after cleaning and surface treatments.


The purpose of jobsite sample panel is to show the acceptable standard of work for the project and it must include:

- The full range of masonry unit color and texture that will be visible in the finished walls.
- Bond pattern and color pattern if masonry units of more than one color are being used.
- Chippage dimensions and frequency including dimensional variation per project specifications.
- Mortar joint size, tooling, alignment, texture and color range.
- If colored mortar is used, the color must be judged after the sample panel has had sufficient time to dry.
- Installation of flashing, weeps, drip edge and sealant joint.
- Movement joint installation and sealant joint
- Cleaning means and methods.
- Surface treatments such as breathable sealants.


The sample panel will be used for final acceptance of the masonry work and must remain unharmed until the masonry is complete and accepted. The Masonry Code charging language states:

“The acceptable standard for the Work is established by the accepted panel.”

The sample panel will be viewed from a distance of 20 feet away under diffused lighting to evaluate the results.



Sample Panel - Items Demonstrated for Approval and Workmanship Standard Setting



Sample Panel- Bond Beam Flashing Detail



Section II Construction Details

Table of Contents	
Introduction	1
Chapter 1	2
Chapter 2	3
Chapter 3	4
Chapter 4	5
Chapter 5	6
Chapter 6	7
Chapter 7	8
Chapter 8	9
Chapter 9	10
Chapter 10	11
Chapter 11	12
Chapter 12	13
Chapter 13	14
Chapter 14	15
Chapter 15	16
Chapter 16	17
Chapter 17	18
Chapter 18	19
Chapter 19	20
Chapter 20	21
Chapter 21	22
Chapter 22	23
Chapter 23	24
Chapter 24	25
Chapter 25	26
Chapter 26	27
Chapter 27	28
Chapter 28	29
Chapter 29	30
Chapter 30	31
Chapter 31	32
Chapter 32	33
Chapter 33	34
Chapter 34	35
Chapter 35	36
Chapter 36	37
Chapter 37	38
Chapter 38	39
Chapter 39	40
Chapter 40	41
Chapter 41	42
Chapter 42	43
Chapter 43	44
Chapter 44	45
Chapter 45	46
Chapter 46	47
Chapter 47	48
Chapter 48	49
Chapter 49	50
Chapter 50	51
Chapter 51	52
Chapter 52	53
Chapter 53	54
Chapter 54	55
Chapter 55	56
Chapter 56	57
Chapter 57	58
Chapter 58	59
Chapter 59	60
Chapter 60	61
Chapter 61	62
Chapter 62	63
Chapter 63	64
Chapter 64	65
Chapter 65	66
Chapter 66	67
Chapter 67	68
Chapter 68	69
Chapter 69	70
Chapter 70	71
Chapter 71	72
Chapter 72	73
Chapter 73	74
Chapter 74	75
Chapter 75	76
Chapter 76	77
Chapter 77	78
Chapter 78	79
Chapter 79	80
Chapter 80	81
Chapter 81	82
Chapter 82	83
Chapter 83	84
Chapter 84	85
Chapter 85	86
Chapter 86	87
Chapter 87	88
Chapter 88	89
Chapter 89	90
Chapter 90	91
Chapter 91	92
Chapter 92	93
Chapter 93	94
Chapter 94	95
Chapter 95	96
Chapter 96	97
Chapter 97	98
Chapter 98	99
Chapter 99	100
Chapter 100	101




Figure 1. Moisture Movement in a Typical Wall




Figure 2. Exterior, Spec-Brik Foundation and Pad




Figure 3. Exterior, Poured Foundation and Pad




Figure 4. Exterior, CMU Foundation, and Insulative Aggregates




Figure 5. Exterior, Poured Foundation, Pad and Insulative Aggregates




Figure 6. Exterior, Below Grade CMU Wall, and Insulative Aggregates




Figure 7. Exterior, CMU Foundation, Insulative Aggregates




Figure 8. Exterior, Z-Cord Weep, CMU Foundation, Insulative Aggregates




Figure 9. Exterior, Z-Cord Weep, Below Grade CMU Wall




Figure 10. Exterior, Z-Cord Weep, Poured Foundation





Figure 11. Z-cord flashing detail

Click on drawings to enlarge

Table of Contents	
1.0 Introduction	1.0
2.0 General Notes	2.0
3.0 Foundation and Pad	3.0
4.0 Exterior Wall	4.0
5.0 Interior Wall	5.0
6.0 Window and Door	6.0
7.0 Roof	7.0
8.0 Floor	8.0
9.0 Stair	9.0
10.0 Elevation	10.0
11.0 Section	11.0
12.0 Detail	12.0
13.0 Appendix	13.0
14.0 Index	14.0

Foundation and Base of Wall

Figure 1. Water Movement in Typical Wall



Typical Notes:

1. This illustration shows how absorbed moisture (along with dissolved salts and sulfates) whether from rain, sprinklers, ice/snow, or soil migrates through the area near the base course flashing layer. This is a key area for moisture control through the use of a High Performance sealing and drainage system in this multi-functional area.
2. In order to control moisture penetration from this area, the use of Integral Water Repellent within the mortar, CMU, and grout is very useful, but not always sufficient without the flashing and weep systems that are required by Code. These systems allow the collection and redirection of moisture downward and to the exterior via flashing and weeps.
3. Using an integrated system consisting of proper materials (IWR in the CMU, mortar and grout, and possibly with breathable sealants or breathable, drainable coatings) and a functional drainage system to allow water to exit the wall system is the key to success. Field water intrusion testing can confirm the success of moisture control.


Codes and Standards References

Applicable References are found in Section III.

Table of Contents	
1. Introduction	1
2. General Notes	2
3. Materials	3
4. Construction	4
5. Quality Control	5
6. Maintenance	6
7. Appendix A	7
8. Appendix B	8
9. Appendix C	9
10. Appendix D	10
11. Appendix E	11
12. Appendix F	12
13. Appendix G	13
14. Appendix H	14
15. Appendix I	15
16. Appendix J	16
17. Appendix K	17
18. Appendix L	18
19. Appendix M	19
20. Appendix N	20
21. Appendix O	21
22. Appendix P	22
23. Appendix Q	23
24. Appendix R	24
25. Appendix S	25
26. Appendix T	26
27. Appendix U	27
28. Appendix V	28
29. Appendix W	29
30. Appendix X	30
31. Appendix Y	31
32. Appendix Z	32



Figure 2. Exterior, Spec-Brik Foundation and Pad



Typical Notes

1. Consult with Structural and/or Geotechnical Engineers for appropriate below-grade insulation material and placement.
2. A tapered (30° from horizontal) 6" zone of free-draining gravel extending from the height of the finished floor to the top of the engineered soil may be substituted for the concrete apron shown.
3. If the zone near the base of wall is to be landscaped, do not place plant life, roots, irrigation, fertilizers or other chemicals within 3 feet of the footing, foundation wall, foundation, and slab. Isolate the footing, foundation and slab from such elements. The height of the soil and nearby draining curbs should be at least 6 inches below top of finished floor to prevent damage from accumulated mulch, and absorption, pooling or flooding of water.
4. Minimum 6" soil / top of finished floor / footing elevation offset. Within this 6" deep offset, a drainable landscape layer of lightweight insulative aggregate may be placed. This in turn can be combined with a minimum 6" - 12" wide 95% compacted lightweight insulative aggregate zone extending down to spread footing with perforated drainage collection pipe at spread footing. The drainage collection pipe leads to a stormwater drainage system (this is depicted in Figure 4).
5. If landscaping is to be used near the structure, maintain a minimum distance of five feet between the vegetation and irrigation from any lightweight insulative aggregate zone. Trees minimum distance 30'.
6. Isolate the zone near the wall from landscape sprinklers or irrigation.

Codes and Standards References

Applicable References are found in Section III.


THE DETAILS PRESENTED IN THIS MANUAL ARE STANDARD DETAILS. DESIGNERS SHOULD MAKE SITE SPECIFIC INVESTIGATIONS TO DETERMINE ACTUAL DESIGN REQUIREMENTS, WHICH MAY VARY.

CPG IS NOT RESPONSIBLE FOR USES OF THIS INFORMATION BY THIRD PARTIES, AND DOES NOT WARRANT THE FITNESS OR SUITABILITY OF THIS INFORMATION FOR ANY PURPOSE. PERSONS MAKING USE OF THIS INFORMATION DO SO AT THEIR OWN RISK.

THESE STANDARD DETAILS ARE MEANT TO ILLUSTRATE GENERAL PRINCIPLES THAT MAY BE HELPFUL, HOWEVER, FINAL DESIGN AND CONSTRUCTION SHOULD BE BASED ON ACTUAL SITE CONDITIONS AND APPLICABLE LOCAL CODE AND STANDARDS. MANY SITE OR LOCAL CONDITIONS MAY REQUIRE SPECIFIC ADDITIONAL DESIGN CONSIDERATIONS. SUCH CONDITIONS MAY INCLUDE SEISMIC ACTIVITY, LOCAL CLIMATE, WIND LOAD AND STORM CONDITIONS (INCLUDING LIKELIHOOD OF TORNADO OR HURRICANE CONDITIONS), SITE SOILS AND DRAINAGE CONSIDERATIONS, AND A VARIETY OF OTHER FACTORS THAT MAY IMPACT BUILDING PERFORMANCE ON A PARTICULAR SITE.



Figure 3. Exterior, Poured Foundation and Pad



Typical Notes

1. Consult with Structural and/or Geotechnical Engineers for appropriate below-grade insulation material and placement.
2. A tapered (30° from horizontal) 6" zone of free-draining gravel extending from the height of the finished floor to the top of the engineered soil may be substituted for the concrete apron shown.
3. If the zone near the base of wall is to be landscaped, do not place plant life, roots, irrigation, fertilizers or other chemicals within 3 feet of the footing, foundation wall, foundation, and slab. Isolate the footing, foundation and slab from such elements. The height of the soil and nearby draining curbs should be at least 6 inches below top of finished floor to prevent damage from accumulated mulch, and absorption, pooling or flooding of water.
4. Minimum 6" soil / top of finished floor / footing elevation offset. Within this 6" deep offset, a drainable landscape layer of lightweight insulative aggregate may be placed. This in turn can be combined with a minimum 6" - 12" wide 95% compacted lightweight insulative aggregate zone extending down to spread footing with perforated drainage collection pipe at spread footing. The drainage collection pipe leads to a stormwater drainage system (this is depicted in Figure 2A).
5. If landscaping is to be used near the structure, maintain a minimum distance of five feet between the vegetation and irrigation from any lightweight insulative aggregate zone. Trees minimum distance 30'.
6. Isolate the zone near the wall from landscape sprinklers or irrigation.

Codes and Standards References

Applicable References are found in Section III.

THE DETAILS PRESENTED IN THIS MANUAL ARE STANDARD DETAILS. DESIGNERS SHOULD MAKE SITE SPECIFIC INVESTIGATIONS TO DETERMINE ACTUAL DESIGN REQUIREMENTS, WHICH MAY VARY.


CPG IS NOT RESPONSIBLE FOR USES OF THIS INFORMATION BY THIRD PARTIES, AND DOES NOT WARRANT THE FITNESS OR SUITABILITY OF THIS INFORMATION FOR ANY PURPOSE. PERSONS MAKING USE OF THIS INFORMATION DO SO AT THEIR OWN RISK.

THESE STANDARD DETAILS ARE MEANT TO ILLUSTRATE GENERAL PRINCIPLES THAT MAY BE HELPFUL, HOWEVER, FINAL DESIGN AND CONSTRUCTION SHOULD BE BASED ON ACTUAL SITE CONDITIONS AND APPLICABLE LOCAL CODE AND STANDARDS. MANY SITE OR LOCAL CONDITIONS MAY REQUIRE SPECIFIC ADDITIONAL DESIGN CONSIDERATIONS. SUCH CONDITIONS MAY INCLUDE SEISMIC ACTIVITY, LOCAL CLIMATE, WIND LOAD AND STORM CONDITIONS (INCLUDING LIKELIHOOD OF TORNADO OR HURRICANE CONDITIONS), SITE SOILS AND DRAINAGE CONSIDERATIONS, AND A VARIETY OF OTHER FACTORS THAT MAY IMPACT BUILDING PERFORMANCE ON A PARTICULAR SITE.

Table of Contents	
1. Introduction	1
2. General Information	2
3. Foundation and Pad	3
4. Wall	4
5. Floor	5
6. Roof	6
7. Exterior Finish	7
8. Interior Finish	8
9. Mechanical	9
10. Electrical	10
11. Plumbing	11
12. Fire Protection	12
13. Safety	13
14. Appendix	14
15. Index	15



Figure 4. Exterior, CMU Foundation, and Insulative Aggregates



THE DETAILS PRESENTED IN THIS MANUAL ARE STANDARD DETAILS. DESIGNERS SHOULD MAKE SITE SPECIFIC INVESTIGATIONS TO DETERMINE ACTUAL DESIGN REQUIREMENTS, WHICH MAY VARY.

CPG IS NOT RESPONSIBLE FOR USES OF THIS INFORMATION BY THIRD PARTIES, AND DOES NOT WARRANT THE FITNESS OR SUITABILITY OF THIS INFORMATION FOR ANY PURPOSE. PERSONS MAKING USE OF THIS INFORMATION DO SO AT THEIR OWN RISK.

THESE STANDARD DETAILS ARE MEANT TO ILLUSTRATE GENERAL PRINCIPLES THAT MAY BE HELPFUL, HOWEVER, FINAL DESIGN AND CONSTRUCTION SHOULD BE BASED ON ACTUAL SITE CONDITIONS AND APPLICABLE LOCAL CODE AND STANDARDS. MANY SITE OR LOCAL CONDITIONS MAY REQUIRE SPECIFIC ADDITIONAL DESIGN CONSIDERATIONS. SUCH CONDITIONS MAY INCLUDE SEISMIC ACTIVITY, LOCAL CLIMATE, WIND LOAD AND STORM CONDITIONS (INCLUDING LIKELIHOOD OF TORNADO OR HURRICANE CONDITIONS), SITE SOILS AND DRAINAGE CONSIDERATIONS, AND A VARIETY OF OTHER FACTORS THAT MAY IMPACT BUILDING PERFORMANCE ON A PARTICULAR SITE.

Typical Notes

1. Generally a damp-check needs be placed above the top of the dampproofing or waterproofing for foundation walls, basement walls, or foundations. For below-grade masonry basement walls an additional damp check at the masonry starting course and above the damproofing or waterproofing for slabs and floors will further control moisture. An above-grade masonry course with flashing also performs as a damp-check Use Integral Water Repellent (IWR) in the masonry. Some exceptions may apply such as for California shear wall testing.
2. Request evidence in writing of, or special inspection for, adequate head joint mortar bond to IWR-containing CMU for Properties-based mortars.
3. If traditional flashing and weep methods are used, drip edge may be omitted if drainable flashing is terminated at or beyond tooled mortar surface, and assuming mortar contains IWR. There are many flashing systems from which to choose including those with minimal mortar penetration. Drainable weeps (such as non-biodegradable, durable sash cord also allowing optional Z or S pattern) and/or vents are still necessary. As an example, cotton sash cord would be expected to degrade while nylon would be expected to be durable. Flashing, drip edges and weeps are sometimes omitted within single wythe barrier wall systems except as otherwise required by Code or Plans.

Field water intrusion testing can confirm the success of moisture control.


4. Horizontal Reinforcement placement below grade level is important. See Plans for reinforcement placement and details.
5. Single-wythe walls are self-covering and therefore especially rely upon a “belt-and-suspenders” approach for moisture control. As a result, designers should use a comprehensive approach that may include flashing and weeps, IWR, post-applied moisture control means and measures, High Performance Sealant systems, movement joints, damp-checks, crack control, thermal bridging/condensate control, as well as soil elevation offsets, drainage offsets, and below-grade damp proofing/water proofing – including alkali, salt, and sulfate resistance.
6. If the zone near the above-grade wall or foundation wall is to be landscaped, do not place plant life, roots, irrigation, fertilizers or other chemicals within 3 feet of the above-grade wall or foundation wall. Isolate the above-grade wall, foundation wall, footing, foundation, and slab from such elements.
7. There are many aesthetic options to utilize a minimum 6” - 12” wide 95% compacted lightweight insulative aggregate zone extending down to the spread footing with a foundation drain. The drainage collection pipe leads to a stormwater drainage/management system.

Codes and Standards References

Applicable References are found in Section III.



Figure 5. Exterior, Poured Foundation, Pad and Insulative Aggregates



THE DETAILS PRESENTED IN THIS MANUAL ARE STANDARD DETAILS. DESIGNERS SHOULD MAKE SITE SPECIFIC INVESTIGATIONS TO DETERMINE ACTUAL DESIGN REQUIREMENTS, WHICH MAY VARY.

CPG IS NOT RESPONSIBLE FOR USES OF THIS INFORMATION BY THIRD PARTIES, AND DOES NOT WARRANT THE FITNESS OR SUITABILITY OF THIS INFORMATION FOR ANY PURPOSE. PERSONS MAKING USE OF THIS INFORMATION DO SO AT THEIR OWN RISK.

THESE STANDARD DETAILS ARE MEANT TO ILLUSTRATE GENERAL PRINCIPLES THAT MAY BE HELPFUL, HOWEVER, FINAL DESIGN AND CONSTRUCTION SHOULD BE BASED ON ACTUAL SITE CONDITIONS AND APPLICABLE LOCAL CODE AND STANDARDS. MANY SITE OR LOCAL CONDITIONS MAY REQUIRE SPECIFIC ADDITIONAL DESIGN CONSIDERATIONS. SUCH CONDITIONS MAY INCLUDE SEISMIC ACTIVITY, LOCAL CLIMATE, WIND LOAD AND STORM CONDITIONS (INCLUDING LIKELIHOOD OF TORNADO OR HURRICANE CONDITIONS), SITE SOILS AND DRAINAGE CONSIDERATIONS, AND A VARIETY OF OTHER FACTORS THAT MAY IMPACT BUILDING PERFORMANCE ON A PARTICULAR SITE.

Typical Notes


1. Generally a damp-check needs be placed above the top of the dampproofing or waterproofing for foundation walls, basement walls, or foundations. For below-grade masonry basement walls an additional damp check at the masonry starting course and above the damprooing or waterproofing for slabs and floors will further control moisture. An above-grade masonry course with flashing also performs as a damp-check Use Integral Water Repellent (IWR) in the masonry. Some exceptions may apply such as for California shear wall testing.
 2. Request evidence in writing of, or special inspection for, adequate head joint mortar bond to IWR-containing CMU for Properties-based mortars.
 3. If traditional flashing and weep methods are used, drip edge may be omitted if drainable flashing is terminated at or beyond tooled mortar surface, and assuming mortar contains IWR. There are many flashing systems from which to choose including those with minimal mortar penetration. Drainable weeps (such as non-biodegradable, durable sash cord also allowing optional Z or S pattern) and/or vents are still necessary. As an example, cotton sash cord would be expected to degrade while nylon would be expected to be durable. Flashing, drip edges and weeps are sometimes omitted within single wythe barrier wall systems except as otherwise required by Code or Plans.
- Field water intrusion testing can confirm the success of moisture control.**
4. Horizontal Reinforcement placement below grade level is important. See Plans for reinforcement placement and details.
 5. Single-wythe walls are self-covering and therefore especially rely upon a “belt-and-suspenders” approach for moisture control. As a result, designers should use a comprehensive approach that may include flashing and weeps, IWR, post-applied moisture control means and measures, High Performance Sealant systems, movement joints, damp-checks, crack control, thermal bridging/condensate control, as well as soil elevation offsets, drainage offsets, and below-grade damp proofing/water proofing – including alkali, salt, and sulfate resistance.
 6. If the zone near the above-grade wall or foundation wall is to be landscaped, do not place plant life, roots, irrigation, fertilizers or other chemicals within 3 feet of the above-grade wall or foundation wall. Isolate the above-grade wall, foundation wall, footing, foundation, and slab from such elements.
 7. There are many aesthetic options to utilize a minimum 6” - 12” wide 95% compacted lightweight insulative aggregate zone extending down to the spread footing with a foundation drain. The drainage collection pipe leads to a stormwater drainage/management system.

Codes and Standards References

Applicable References are found in Section III.



Figure 6. Exterior, Below Grade CMU Wall, and Insulative Aggregates



THE DETAILS PRESENTED IN THIS MANUAL ARE STANDARD DETAILS. DESIGNERS SHOULD MAKE SITE SPECIFIC INVESTIGATIONS TO DETERMINE ACTUAL DESIGN REQUIREMENTS, WHICH MAY VARY.

CPG IS NOT RESPONSIBLE FOR USES OF THIS INFORMATION BY THIRD PARTIES, AND DOES NOT WARRANT THE FITNESS OR SUITABILITY OF THIS INFORMATION FOR ANY PURPOSE. PERSONS MAKING USE OF THIS INFORMATION DO SO AT THEIR OWN RISK.

THESE STANDARD DETAILS ARE MEANT TO ILLUSTRATE GENERAL PRINCIPLES THAT MAY BE HELPFUL, HOWEVER, FINAL DESIGN AND CONSTRUCTION SHOULD BE BASED ON ACTUAL SITE CONDITIONS AND APPLICABLE LOCAL CODE AND STANDARDS. MANY SITE OR LOCAL CONDITIONS MAY REQUIRE SPECIFIC ADDITIONAL DESIGN CONSIDERATIONS. SUCH CONDITIONS MAY INCLUDE SEISMIC ACTIVITY, LOCAL CLIMATE, WIND LOAD AND STORM CONDITIONS (INCLUDING LIKELIHOOD OF TORNADO OR HURRICANE CONDITIONS), SITE SOILS AND DRAINAGE CONSIDERATIONS, AND A VARIETY OF OTHER FACTORS THAT MAY IMPACT BUILDING PERFORMANCE ON A PARTICULAR SITE.

Typical Notes


- Generally a damp-check needs be placed above the top of the dampproofing or waterproofing for foundation walls, basement walls, or foundations. For below-grade masonry basement walls an additional damp check at the masonry starting course and above the dampproofing or waterproofing for slabs and floors will further control moisture. An above-grade masonry course with flashing also performs as a damp-check Use Integral Water Repellent (IWR) in the masonry. Some exceptions may apply such as for California shear wall testing.
 - Request evidence in writing of, or special inspection for, adequate head joint mortar bond to IWR-containing CMU for Properties-based mortars.
 - If traditional flashing and weep methods are used, drip edge may be omitted if drainable flashing is terminated at or beyond tooled mortar surface, and assuming mortar contains IWR. There are many flashing systems from which to choose including those with minimal mortar penetration. Drainable weeps (such as non-biodegradable, durable sash cord also allowing optional Z or S pattern) and/or vents are still necessary. As an example, cotton sash cord would be expected to degrade while nylon would be expected to be durable. Flashing, drip edges and weeps are sometimes omitted within single wythe barrier wall systems except as otherwise required by Code or Plans.
- Field water intrusion testing can confirm the success of moisture control.**
- Horizontal Reinforcement placement below grade level is important. See Plans for reinforcement placement and details.
 - Single-wythe walls are self-covering and therefore especially rely upon a “belt-and-suspenders” approach for moisture control. As a result, designers should use a comprehensive approach that may include flashing and weeps, IWR, post-applied moisture control means and measures, High Performance Sealant systems, movement joints, damp-checks, crack control, thermal bridging/condensate control, as well as soil elevation offsets, drainage offsets, and below-grade damp proofing/water proofing – including alkali, salt, and sulfate resistance.
 - If the zone near the above-grade wall or foundation wall is to be landscaped, do not place plant life, roots, irrigation, fertilizers or other chemicals within 3 feet of the above-grade wall or foundation wall. Isolate the above-grade wall, foundation wall, footing, foundation, and slab from such elements.
 - There are many aesthetic options to utilize a minimum 6” - 12” wide 95% compacted lightweight insulative aggregate zone extending down to the spread footing with a foundation drain. The drainage collection pipe leads to a stormwater drainage/management system.

Codes and Standards References

Applicable References are found in Section III.



Figure 7. Exterior, CMU Foundation, and Insulative Aggregates



THE DETAILS PRESENTED IN THIS MANUAL ARE STANDARD DETAILS. DESIGNERS SHOULD MAKE SITE SPECIFIC INVESTIGATIONS TO DETERMINE ACTUAL DESIGN REQUIREMENTS, WHICH MAY VARY.

CPG IS NOT RESPONSIBLE FOR USES OF THIS INFORMATION BY THIRD PARTIES, AND DOES NOT WARRANT THE FITNESS OR SUITABILITY OF THIS INFORMATION FOR ANY PURPOSE. PERSONS MAKING USE OF THIS INFORMATION DO SO AT THEIR OWN RISK.

THESE STANDARD DETAILS ARE MEANT TO ILLUSTRATE GENERAL PRINCIPLES THAT MAY BE HELPFUL, HOWEVER, FINAL DESIGN AND CONSTRUCTION SHOULD BE BASED ON ACTUAL SITE CONDITIONS AND APPLICABLE LOCAL CODE AND STANDARDS. MANY SITE OR LOCAL CONDITIONS MAY REQUIRE SPECIFIC ADDITIONAL DESIGN CONSIDERATIONS. SUCH CONDITIONS MAY INCLUDE SEISMIC ACTIVITY, LOCAL CLIMATE, WIND LOAD AND STORM CONDITIONS (INCLUDING LIKELIHOOD OF TORNADO OR HURRICANE CONDITIONS), SITE SOILS AND DRAINAGE CONSIDERATIONS, AND A VARIETY OF OTHER FACTORS THAT MAY IMPACT BUILDING PERFORMANCE ON A PARTICULAR SITE.

Typical Notes

1. Generally a damp-check needs be placed above the top of the dampproofing or waterproofing for foundation walls, basement walls, or foundations. For below-grade masonry basement walls an additional damp check at the masonry starting course and above the damproofing or waterproofing for slabs and floors will further control moisture. An above-grade masonry course with flashing also performs as a damp-check Use Integral Water Repellent (IWR) in the masonry. Some exceptions may apply such as for California shear wall testing.
2. Request evidence in writing of, or special inspection for, adequate head joint mortar bond to IWR-containing CMU for Properties-based mortars.
3. If traditional flashing and weep methods are used, drip edge may be omitted if drainable flashing is terminated at or beyond tooled mortar surface, and assuming mortar contains IWR. There are many flashing systems from which to choose including those with minimal mortar penetration. Drainable weeps (such as non-biodegradable, durable sash cord also allowing optional Z or S pattern) and/or vents are still necessary. As an example, cotton sash cord would be expected to degrade while nylon would be expected to be durable. Flashing, drip edges and weeps are sometimes omitted within single wythe barrier wall systems except as otherwise required by Code or Plans.

Field water intrusion testing can confirm the success of moisture control.


4. Horizontal Reinforcement placement below grade level is important. See Plans for reinforcement placement and details.
5. Single-wythe walls are self-covering and therefore especially rely upon a "belt-and-suspenders" approach for moisture control. As a result, designers should use a comprehensive approach that may include flashing and weeps, IWR, post-applied moisture control means and measures, High Performance Sealant systems, movement joints, damp-checks, crack control, thermal bridging/condensate control, as well as soil elevation offsets, drainage offsets, and below-grade damp proofing/water proofing – including alkali, salt, and sulfate resistance.
6. If the zone near the above-grade wall or foundation wall is to be landscaped, do not place plant life, roots, irrigation, fertilizers or other chemicals within 3 feet of the above-grade wall or foundation wall. Isolate the above-grade wall, foundation wall, footing, foundation, and slab from such elements.
7. There are many aesthetic options to utilize a minimum 6" - 12" wide 95% compacted light-weight insulative aggregate zone extending down to the spread footing with a foundation drain. The drainage collection pipe leads to a stormwater drainage/management system.

Codes and Standards References

Applicable References are found in Section III.



Figure 8. Exterior, Z-Cord Weep, CMU Foundation, Insulative Aggregates



Typical Notes:

1. Generally a damp-check needs to be placed above the top of the dampproofing or waterproofing for foundation walls or foundations and above the dampproofing or waterproofing for floors. A masonry course with flashing also performs as a damp-check Use Integral Water Repellent (IWR) in the masonry.
2. Film-forming Breathable Exterior Coatings must allow flashing, weeps, vents, etc. to drain redirected moisture to the exterior. Testing that these drainage systems are properly functioning after application of the coatings is advised.
3. California projects, or other projects where compliance to vertical wall shear testing is required, may use alternate moisture control techniques (omit IWR within CMU; use IWR within mortar; use post-applied breathable penetrating sealants incorporating 2-stage zoned application techniques or drainable film forming coatings; use High Range Water Reducer in grout).
4. Request evidence in writing of adequate head joint mortar bond to IWR-containing CMU for Properties-based mortars.
5. Drip edge may be omitted if drainable flashing is terminated at or beyond tooled mortar surface, and assuming mortar contains IWR. There are many flashing systems from which to choose. Drainable weeps and/or vents (also allowing optional Z or S pattern) are still necessary.
6. Joint Reinforcement requires minimum 6" lap splices and other connections even for non-load bearing elements. See Plans for joint reinforcement lap schedule or details.
7. Assume single wythe walls are self-covering and therefore especially rely upon belt-and-suspenders approach. Flashing and weeps, IWR, post-applied moisture control means and measures, High Performance Sealant systems, movement joints, damp-checks, crack control, thermal bridging/condensate control, as well as soil elevation offsets and below-grade dampproofing / water proofing – including alkali, salt, and sulfate resistance should be each considered. Field water intrusion testing can confirm the success of moisture control.

Codes and Standards References

Applicable References are found in Section III.


THE DETAILS PRESENTED IN THIS MANUAL ARE STANDARD DETAILS. DESIGNERS SHOULD MAKE SITE SPECIFIC INVESTIGATIONS TO DETERMINE ACTUAL DESIGN REQUIREMENTS, WHICH MAY VARY.

CPG IS NOT RESPONSIBLE FOR USES OF THIS INFORMATION BY THIRD PARTIES, AND DOES NOT WARRANT THE FITNESS OR SUITABILITY OF THIS INFORMATION FOR ANY PURPOSE. PERSONS MAKING USE OF THIS INFORMATION DO SO AT THEIR OWN RISK.

THESE STANDARD DETAILS ARE MEANT TO ILLUSTRATE GENERAL PRINCIPLES THAT MAY BE HELPFUL, HOWEVER, FINAL DESIGN AND CONSTRUCTION SHOULD BE BASED ON ACTUAL SITE CONDITIONS AND APPLICABLE LOCAL CODE AND STANDARDS. MANY SITE OR LOCAL CONDITIONS MAY REQUIRE SPECIFIC ADDITIONAL DESIGN CONSIDERATIONS. SUCH CONDITIONS MAY INCLUDE SEISMIC ACTIVITY, LOCAL CLIMATE, WIND LOAD AND STORM CONDITIONS (INCLUDING LIKELIHOOD OF TORNADO OR HURRICANE CONDITIONS), SITE SOILS AND DRAINAGE CONSIDERATIONS, AND A VARIETY OF OTHER FACTORS THAT MAY IMPACT BUILDING PERFORMANCE ON A PARTICULAR SITE.



Figure 9. Exterior, Z-Cord Weep, Below Grade CMU



Typical Notes:

1. Generally a damp-check needs be placed above the top of the dampproofing or waterproofing for foundation walls, basement walls, or foundations. For below-grade masonry basement walls an additional damp check at the masonry starting course and above the dampproofing or waterproofing for slabs and floors will further control moisture. An above-grade masonry course with flashing also performs as a damp-check. Use Integral Water Repellent (IWR) in the masonry. Some exceptions may apply such as for California shear wall testing.
2. Film-forming Breathable Exterior Coatings must allow flashing, weeps, vents, etc. to drain redirected moisture to the exterior. Testing that these drainage systems are properly functioning after application of the coatings is advised.
3. California projects, or other projects where compliance to vertical wall shear testing is required, may use alternate moisture control techniques (omit IWR within CMU; use IWR within mortar; use post-applied breathable penetrating sealants incorporating 2-stage zoned application techniques or drainable film forming coatings; use High Range Water Reducer in grout).
4. Request evidence in writing of or special inspect for adequate head joint mortar bond to IWR-containing CMU for Properties-based mortars.
5. Drip edge may be omitted if drainable flashing is terminated at or beyond tooled mortar surface, and assuming mortar contains IWR. There are many flashing systems from which to choose including those with minimal mortar penetration. Drainable weeps (or non-biodegradable, sustainable sash cord also allowing optional Z or S pattern) and/or vents are still necessary. Flashing, drip edges and weeps are assumed omitted within single wythe barrier wall systems except as otherwise required such as by Code or Plans.
6. Horizontal Reinforcement placement below grade level is important. See Plans for reinforcement placement and details.
7. Single wythe walls are self-covering and therefore especially rely upon a “belt-and-suspenders” approach. As a result, designers should consider use of complimentary approaches, including Flashing and weeps, Integral Water Repellent, post-applied moisture control means and measures, High Performance Sealant systems, movement joints, damp-checks, crack control, thermal bridging/condensate control, as well as soil elevation offsets, drainage offsets, and below-grade damp proofing / water proofing – including alkali, salt, and sulfate resistance. Field water intrusion testing can confirm the success of moisture control.
8. If the zone near the above-grade wall or foundation wall is to be landscaped, do not place plant life, roots, irrigation, fertilizers or other chemicals within 3 feet of the above-grade wall or foundation wall. Isolate the above-grade wall, foundation wall, footing, foundation, and slab from such elements.
9. There are many aesthetic options to utilize a minimum 6” - 12” wide 95% compacted lightweight insulative aggregate zone extending down to the spread footing with a foundation drain. The drainage collection pipe leads to a storm water management system.

Codes and Standards References

Applicable References are found in Section III.


THE DETAILS PRESENTED IN THIS MANUAL ARE STANDARD DETAILS. DESIGNERS SHOULD MAKE SITE SPECIFIC INVESTIGATIONS TO DETERMINE ACTUAL DESIGN REQUIREMENTS, WHICH MAY VARY.

CPG IS NOT RESPONSIBLE FOR USES OF THIS INFORMATION BY THIRD PARTIES, AND DOES NOT WARRANT THE FITNESS OR SUITABILITY OF THIS INFORMATION FOR ANY PURPOSE. PERSONS MAKING USE OF THIS INFORMATION DO SO AT THEIR OWN RISK.

THESE STANDARD DETAILS ARE MEANT TO ILLUSTRATE GENERAL PRINCIPLES THAT MAY BE HELPFUL, HOWEVER, FINAL DESIGN AND CONSTRUCTION SHOULD BE BASED ON ACTUAL SITE CONDITIONS AND APPLICABLE LOCAL CODE AND STANDARDS. MANY SITE OR LOCAL CONDITIONS MAY REQUIRE SPECIFIC ADDITIONAL DESIGN CONSIDERATIONS. SUCH CONDITIONS MAY INCLUDE SEISMIC ACTIVITY, LOCAL CLIMATE, WIND LOAD AND STORM CONDITIONS (INCLUDING LIKELIHOOD OF TORNADO OR HURRICANE CONDITIONS), SITE SOILS AND DRAINAGE CONSIDERATIONS, AND A VARIETY OF OTHER FACTORS THAT MAY IMPACT BUILDING PERFORMANCE ON A PARTICULAR SITE.



Figure 10. Exterior, Z-Cord Weep, Poured Foundation



Typical Notes:

1. Masonry Base course with flashing also performs as a damp-check including salt and sulfate resistance. Use Integral Water Repellent (IWR) in the mortar in contact with the base course (and CMU stem wall if used). IWR shall also be used in the grout within the base course (and CMU stem wall if used). Flashing shall be used at and above the base course. Penetrations within the base course flashing shall be sealed with an approved High Performance sealant system. In salt-prone areas a minimum of a multi-applied penetrating breathable sealant or breathable film-forming coating shall be used.
2. Film-forming Breathable Exterior Coatings must allow flashing, weeps, vents, etc. to drain redirected moisture to the exterior. Testing that these drainage systems are properly functioning after application of the coatings is advised.
3. California projects, or other projects where compliance to vertical wall shear testing is required, may use alternate moisture control techniques (omit IWR within CMU; use IWR within mortar; use post-applied breathable penetrating sealants incorporating 2-stage zoned application techniques or drainable film forming coatings; use High Range Water Reducer in grout).
4. Request evidence in writing of adequate head joint mortar bond to IWR-containing CMU for Properties-based mortars. Request in writing evidence of sufficient composite-action bond to IWR-containing CMU of Properties-based grout.
5. Drip edge may be omitted if drainable flashing is terminated at tooled mortar surface, and assuming mortar contains IWR. There are many flashing systems from which to choose. Drainable weeps and/or vents (also allowing optional Z or S pattern) are still necessary.
6. Joint Reinforcement requires minimum 6" lap splices and other connections even for non-load bearing elements. See Plans for joint reinforcement lap schedule or details.
7. Assume single-wythe walls are self-covering and therefore especially rely upon belt-and-suspenders approach; flashing and weeps, IWR, post-applied moisture control means and measures, High Performance Sealant systems, movement joints, damp-checks, crack control, thermal bridging/condensate control, as well as soil elevation offsets and below-grade damp-proofing / water proofing – including alkali, salt, and sulfate resistance should be each considered.

Codes and Standards References

Applicable References are found in Section III.


THE DETAILS PRESENTED IN THIS MANUAL ARE STANDARD DETAILS. DESIGNERS SHOULD MAKE SITE SPECIFIC INVESTIGATIONS TO DETERMINE ACTUAL DESIGN REQUIREMENTS, WHICH MAY VARY.

CPG IS NOT RESPONSIBLE FOR USES OF THIS INFORMATION BY THIRD PARTIES, AND DOES NOT WARRANT THE FITNESS OR SUITABILITY OF THIS INFORMATION FOR ANY PURPOSE. PERSONS MAKING USE OF THIS INFORMATION DO SO AT THEIR OWN RISK.

THESE STANDARD DETAILS ARE MEANT TO ILLUSTRATE GENERAL PRINCIPLES THAT MAY BE HELPFUL, HOWEVER, FINAL DESIGN AND CONSTRUCTION SHOULD BE BASED ON ACTUAL SITE CONDITIONS AND APPLICABLE LOCAL CODE AND STANDARDS. MANY SITE OR LOCAL CONDITIONS MAY REQUIRE SPECIFIC ADDITIONAL DESIGN CONSIDERATIONS. SUCH CONDITIONS MAY INCLUDE SEISMIC ACTIVITY, LOCAL CLIMATE, WIND LOAD AND STORM CONDITIONS (INCLUDING LIKELIHOOD OF TORNADO OR HURRICANE CONDITIONS), SITE SOILS AND DRAINAGE CONSIDERATIONS, AND A VARIETY OF OTHER FACTORS THAT MAY IMPACT BUILDING PERFORMANCE ON A PARTICULAR SITE.



Figure 11. Z-cord flashing detail



Typical Notes

1. This is an old, cost-effective non-proprietary method of overcoming drainage blockage due to mortar droppings and grout splash within the ungrouted grout spaces. Because natural cotton sash and hemp twine are typically biodegradable, the use of synthetic cord materials such as nylon, U. V.-resistant polyester, synthetic braids, or other durable and weather-protective material would be preferable for durability.
2. At or below-grade concrete needs to be resistant to corrosion, sulfate, salt (including de-icing chemicals), moisture, chlorides, seawater, and freezing-thawing via Codes and Standards such as IBC Section 1904 . Such Durability is attained in part by:
 - a. Determining Exposure Categories and classes.
 - b. Determining and calculating concrete water-cementitious ratios.
 - c. Determining and calculating minimum specified concrete compressive strength.
 - d. Determining minimum and maximum concrete air entrainment.
 - e. Determining concrete weathering probability.
 - f. Evaluating water-soluble sulfates in soil and/or groundwater to determine Type (II, V, etc.) of cement to use.

THE DETAILS PRESENTED IN THIS MANUAL ARE STANDARD DETAILS. DESIGNERS SHOULD MAKE SITE SPECIFIC INVESTIGATIONS TO DETERMINE ACTUAL DESIGN REQUIREMENTS, WHICH MAY VARY.

CPG IS NOT RESPONSIBLE FOR USES OF THIS INFORMATION BY THIRD PARTIES, AND DOES NOT WARRANT THE FITNESS OR SUITABILITY OF THIS INFORMATION FOR ANY PURPOSE. PERSONS MAKING USE OF THIS INFORMATION DO SO AT THEIR OWN RISK.

THESE STANDARD DETAILS ARE MEANT TO ILLUSTRATE GENERAL PRINCIPLES THAT MAY BE HELPFUL, HOWEVER, FINAL DESIGN AND CONSTRUCTION SHOULD BE BASED ON ACTUAL SITE CONDITIONS AND APPLICABLE LOCAL CODE AND STANDARDS. MANY SITE OR LOCAL CONDITIONS MAY REQUIRE SPECIFIC ADDITIONAL DESIGN CONSIDERATIONS. SUCH CONDITIONS MAY INCLUDE SEISMIC ACTIVITY, LOCAL CLIMATE, WIND LOAD AND STORM CONDITIONS (INCLUDING LIKELIHOOD OF TORNADO OR HURRICANE CONDITIONS), SITE SOILS AND DRAINAGE CONSIDERATIONS, AND A VARIETY OF OTHER FACTORS THAT MAY IMPACT BUILDING PERFORMANCE ON A PARTICULAR SITE.






Figure 12. Window Sill




Figure 13. Window Jamb





Figure 14. Lintel

Click on drawings to enlarge

Table of Contents	
Introduction	Section 05100 - Windows
Window Sill	Section 05100 - Windows
Window Jamb	Section 05100 - Windows
Window Lintel	Section 05100 - Windows
Window Frame	Section 05100 - Windows
Window Flashing	Section 05100 - Windows
Window Insulation	Section 05100 - Windows
Window Sealant	Section 05100 - Windows
Window Trim	Section 05100 - Windows
Window Hardware	Section 05100 - Windows
Window Accessories	Section 05100 - Windows
Window Installation	Section 05100 - Windows
Window Maintenance	Section 05100 - Windows
Window Specifications	Section 05100 - Windows
Window Details	Section 05100 - Windows
Window Notes	Section 05100 - Windows

Window Sills, Jambs and Lintels

Figure 12. Window Sill



Typical Notes:

1. Film-forming Breathable Exterior Coatings must allow flashing, weeps, vents, etc. to drain redirected moisture to the exterior.
2. California projects, or other projects where compliance to vertical wall shear testing is required, may use alternate moisture control techniques (omit IWR within CMU; use IWR within mortar; use post-applied breathable penetrating sealants incorporating 2-stage zoned application techniques or drainable film forming coatings; use High Range Water Reducer in grout).
3. Request evidence in writing of adequate head joint mortar bond to IWR-containing CMU for Properties-based mortars. Request in writing evidence of sufficient composite-action bond to IWR-containing CMU of Properties-based grout.
4. Drip edge may be omitted if drainable flashing is terminated at tooled mortar surface, and assuming mortar contains IWR. Many flashing systems from which to choose. Drainable weeps and/or vents (also allowing optional Z or S pattern) still necessary.
5. Joint Reinforcement requires minimum 6" lap splices and other connections even for non-load bearing elements
6. Assume single-wythe walls are self-covering and therefore especially rely upon belt-and-suspenders approach; flashing and weeps, IWR, post-applied moisture control means and measures, High Performance Sealant systems, movement joints, damp-checks, crack control, thermal bridging/condensate control, as well as soil elevation offsets and below-grade damp-proofing – including alkali, salt, and sulfate resistance - are each considered.

Codes and Standards References

Applicable References are found in Section III.


THE DETAILS PRESENTED IN THIS MANUAL ARE STANDARD DETAILS. DESIGNERS SHOULD MAKE SITE SPECIFIC INVESTIGATIONS TO DETERMINE ACTUAL DESIGN REQUIREMENTS, WHICH MAY VARY.

CPG IS NOT RESPONSIBLE FOR USES OF THIS INFORMATION BY THIRD PARTIES, AND DOES NOT WARRANT THE FITNESS OR SUITABILITY OF THIS INFORMATION FOR ANY PURPOSE. PERSONS MAKING USE OF THIS INFORMATION DO SO AT THEIR OWN RISK.

THESE STANDARD DETAILS ARE MEANT TO ILLUSTRATE GENERAL PRINCIPLES THAT MAY BE HELPFUL, HOWEVER, FINAL DESIGN AND CONSTRUCTION SHOULD BE BASED ON ACTUAL SITE CONDITIONS AND APPLICABLE LOCAL CODE AND STANDARDS. MANY SITE OR LOCAL CONDITIONS MAY REQUIRE SPECIFIC ADDITIONAL DESIGN CONSIDERATIONS. SUCH CONDITIONS MAY INCLUDE SEISMIC ACTIVITY, LOCAL CLIMATE, WIND LOAD AND STORM CONDITIONS (INCLUDING LIKELIHOOD OF TORNADO OR HURRICANE CONDITIONS), SITE SOILS AND DRAINAGE CONSIDERATIONS, AND A VARIETY OF OTHER FACTORS THAT MAY IMPACT BUILDING PERFORMANCE ON A PARTICULAR SITE.



Figure 13. Window Jamb



Typical Notes:

1. Film-forming Breathable Exterior Coatings must allow flashing, weeps, vents, etc. to drain redirected moisture to the exterior.
2. California projects, or other projects compliant to vertical wall shear testing, may use alternate moisture control techniques (omit IWR within CMU; use IWR within mortar; use post-applied breathable penetrating sealants incorporating 2-stage zoned application techniques or drainable film forming coatings; use High Range Water Reducer in grout).
3. Request evidence in writing of adequate head joint mortar bond to IWR-containing CMU for Properties-based mortars. Request in writing evidence of sufficient composite-action bond to IWR-containing CMU of Properties-based grout.
4. Drip edge may be omitted if drainable flashing is terminated at tooled mortar surface, and assuming mortar contains IWR. Many flashing systems from which to choose. Drainable weeps and/or vents (also allowing optional Z or S pattern) still necessary.
5. Joint Reinforcement requires minimum 6" lap splices and other connections even for non-load bearing elements
6. Assume single-wythe walls are self-covering and therefore especially rely upon belt-and-suspenders approach; flashing and weeps, IWR, post-applied moisture control means and measures, High Performance Sealant systems, movement joints, damp-checks, crack control, thermal bridging/condensate control, as well as soil elevation offsets and below-grade dampproofing – including alkali, salt, and sulfate resistance - are each considered.

Codes and Standards References

Applicable References are found in Section III.


THE DETAILS PRESENTED IN THIS MANUAL ARE STANDARD DETAILS. DESIGNERS SHOULD MAKE SITE SPECIFIC INVESTIGATIONS TO DETERMINE ACTUAL DESIGN REQUIREMENTS, WHICH MAY VARY.

CPG IS NOT RESPONSIBLE FOR USES OF THIS INFORMATION BY THIRD PARTIES, AND DOES NOT WARRANT THE FITNESS OR SUITABILITY OF THIS INFORMATION FOR ANY PURPOSE. PERSONS MAKING USE OF THIS INFORMATION DO SO AT THEIR OWN RISK.

THESE STANDARD DETAILS ARE MEANT TO ILLUSTRATE GENERAL PRINCIPLES THAT MAY BE HELPFUL, HOWEVER, FINAL DESIGN AND CONSTRUCTION SHOULD BE BASED ON ACTUAL SITE CONDITIONS AND APPLICABLE CODES AND STANDARDS. MANY SITE OR LOCAL CONDITIONS MAY REQUIRE SPECIFIC ADDITIONAL DESIGN CONSIDERATIONS. SUCH CONDITIONS MAY INCLUDE SEISMIC ACTIVITY, LOCAL CLIMATE, WIND LOAD AND STORM CONDITIONS (INCLUDING LIKELIHOOD OF TORNADO OR HURRICANE CONDITIONS), SITE SOILS AND DRAINAGE CONSIDERATIONS, AND A VARIETY OF OTHER FACTORS THAT MAY IMPACT BUILDING PERFORMANCE ON A PARTICULAR SITE.



Figure 14. Lintel



Typical Notes:

1. Film-forming Breathable Exterior Coatings must allow flashing, weeps, vents, etc. to drain redirected moisture to the exterior.
2. California or other projects compliant to vertical wall shear test may use alternate moisture control techniques (omit Integral Water Repellent (“IWR”) within CMU; use IWR within mortar; use post-applied breathable penetrating sealants incorporating 2-stage zoned application techniques or drainable film forming coatings).
3. Request evidence in writing of adequate head joint mortar bond to IWR-containing CMU for Properties-based mortars. Request in writing evidence of sufficient composite-action bond to IWR-containing CMU of Properties-based grout.
4. If traditional flashing and weeps methods are used, drip edge may be omitted if drainable flashing is terminated at tooled mortar surface. Many flashing systems from which to choose. Drainable weeps and/or vents (also allowing optional Z or S pattern) still necessary.
5. Joint Reinforcement requires minimum 6” lap splices and other connections even for non-load bearing elements.
6. Assume single-wythe walls are self-covering and therefore specially rely upon belt-and-suspenders approach; flashing and weeps, IWR, post-applied moisture control means and measures, High Performance Sealant systems, movement joints, damp-checks, crack control, thermal bridging/condensate control, as well as soil elevation offsets and below-grade damp-proofing - including alkali, salt, and sulfate resistance - are each considered .

Codes and Standards References

Applicable References are found in Section III.

THE DETAILS PRESENTED IN THIS MANUAL ARE STANDARD DETAILS. DESIGNERS SHOULD MAKE SITE SPECIFIC INVESTIGATIONS TO DETERMINE ACTUAL DESIGN REQUIREMENTS, WHICH MAY VARY.

CPG IS NOT RESPONSIBLE FOR USES OF THIS INFORMATION BY THIRD PARTIES, AND DOES NOT WARRANT THE FITNESS OR SUITABILITY OF THIS INFORMATION FOR ANY PURPOSE. PERSONS MAKING USE OF THIS INFORMATION DO SO AT THEIR OWN RISK.

THESE STANDARD DETAILS ARE MEANT TO ILLUSTRATE GENERAL PRINCIPLES THAT MAY BE HELPFUL, HOWEVER, FINAL DESIGN AND CONSTRUCTION SHOULD BE BASED ON ACTUAL SITE CONDITIONS AND APPLICABLE CODES AND STANDARDS. MANY SITE OR LOCAL CONDITIONS MAY REQUIRE SPECIFIC ADDITIONAL DESIGN CONSIDERATIONS. SUCH CONDITIONS MAY INCLUDE SEISMIC ACTIVITY, LOCAL CLIMATE, WIND LOAD AND STORM CONDITIONS (INCLUDING LIKELIHOOD OF TORNADO OR HURRICANE CONDITIONS), SITE SOILS AND DRAINAGE CONSIDERATIONS, AND A VARIETY OF OTHER FACTORS THAT MAY IMPACT BUILDING PERFORMANCE ON A PARTICULAR SITE.






Figure 15. Joint Reinforcement




Figure 16. Movement Joint





Figure 16a. Movement Joint

Click on drawings to enlarge

Table of Contents	
1. Introduction	1
2. Joint Reinforcement	2
3. Movement Joints	3
4. Flashing and Weep Units	4
5. Foundation Details	5
6. Interior Details	6
7. Exterior Details	7
8. Notes	8
9. Index	9

Joint Reinforcement and Movement Joints

Figure 15. Joint Reinforcement



Typical Notes

Lapping the joint reinforcement is required by Code and typically specified. However, the failure to execute this detail properly during construction is a common source of cracking issues.

Codes and Standards References

Applicable References are found in Section III.


THE DETAILS PRESENTED IN THIS MANUAL ARE STANDARD DETAILS. DESIGNERS SHOULD MAKE SITE SPECIFIC INVESTIGATIONS TO DETERMINE ACTUAL DESIGN REQUIREMENTS, WHICH MAY VARY.

CPG IS NOT RESPONSIBLE FOR USES OF THIS INFORMATION BY THIRD PARTIES, AND DOES NOT WARRANT THE FITNESS OR SUITABILITY OF THIS INFORMATION FOR ANY PURPOSE. PERSONS MAKING USE OF THIS INFORMATION DO SO AT THEIR OWN RISK.

THESE STANDARD DETAILS ARE MEANT TO ILLUSTRATE GENERAL PRINCIPLES THAT MAY BE HELPFUL, HOWEVER, FINAL DESIGN AND CONSTRUCTION SHOULD BE BASED ON ACTUAL SITE CONDITIONS AND APPLICABLE CODES AND STANDARDS. MANY SITE OR LOCAL CONDITIONS MAY REQUIRE SPECIFIC ADDITIONAL DESIGN CONSIDERATIONS. SUCH CONDITIONS MAY INCLUDE SEISMIC ACTIVITY, LOCAL CLIMATE, WIND LOAD AND STORM CONDITIONS (INCLUDING LIKELIHOOD OF TORNADO OR HURRICANE CONDITIONS), SITE SOILS AND DRAINAGE CONSIDERATIONS, AND A VARIETY OF OTHER FACTORS THAT MAY IMPACT BUILDING PERFORMANCE ON A PARTICULAR SITE.



Figure 16. Movement Joint



Typical Notes

1. Movement joints are a method to avoid cracking in masonry walls. They are advisable in areas where there are interfaces with materials that may have different expansion properties than the wall as a whole. Placing these joints here will accommodate any slight differential in expansion/contraction properties. The movement joint will be sealed with a gasket and sealants.
2. In general, the specific spacing and placement of movement joints for a project should be reviewed by a structural engineer, but a good rule of thumb is that movement joints should be no further apart than 20 feet in an uninterrupted wall surface, and should be placed adjacent to openings or changes in wall materials.

Codes and Standards References

Applicable References are found in Section III.


THE DETAILS PRESENTED IN THIS MANUAL ARE STANDARD DETAILS. DESIGNERS SHOULD MAKE SITE SPECIFIC INVESTIGATIONS TO DETERMINE ACTUAL DESIGN REQUIREMENTS, WHICH MAY VARY.

CPG IS NOT RESPONSIBLE FOR USES OF THIS INFORMATION BY THIRD PARTIES, AND DOES NOT WARRANT THE FITNESS OR SUITABILITY OF THIS INFORMATION FOR ANY PURPOSE. PERSONS MAKING USE OF THIS INFORMATION DO SO AT THEIR OWN RISK.

THESE STANDARD DETAILS ARE MEANT TO ILLUSTRATE GENERAL PRINCIPLES THAT MAY BE HELPFUL, HOWEVER, FINAL DESIGN AND CONSTRUCTION SHOULD BE BASED ON ACTUAL SITE CONDITIONS AND APPLICABLE LOCAL CODE AND STANDARDS. MANY SITE OR LOCAL CONDITIONS MAY REQUIRE SPECIFIC ADDITIONAL DESIGN CONSIDERATIONS. SUCH CONDITIONS MAY INCLUDE SEISMIC ACTIVITY, LOCAL CLIMATE, WIND LOAD AND STORM CONDITIONS (INCLUDING LIKELIHOOD OF TORNADO OR HURRICANE CONDITIONS), SITE SOILS AND DRAINAGE CONSIDERATIONS, AND A VARIETY OF OTHER FACTORS THAT MAY IMPACT BUILDING PERFORMANCE ON A PARTICULAR SITE.



Figure 16a. Movement Joint - 3D Rendering



Typical Notes

1. Movement joints are a method to avoid cracking in masonry walls. They are advisable in areas where there are interfaces with materials that may have different expansion properties than the wall as a whole. Placing these joints here will accommodate any slight differential in expansion/contraction properties. The movement joint will be sealed with a gasket and sealants.
2. In general, the specific spacing and placement of movement joints for a project should be reviewed by a structural engineer, but a good rule of thumb is that movement joints should be no further apart than 20 feet in an uninterrupted wall surface, and should be placed adjacent to openings or changes in wall materials.

Codes and Standards References

Applicable References are found in Section III.

THE DETAILS PRESENTED IN THIS MANUAL ARE STANDARD DETAILS. DESIGNERS SHOULD MAKE SITE SPECIFIC INVESTIGATIONS TO DETERMINE ACTUAL DESIGN REQUIREMENTS, WHICH MAY VARY.

CPG IS NOT RESPONSIBLE FOR USES OF THIS INFORMATION BY THIRD PARTIES, AND DOES NOT WARRANT THE FITNESS OR SUITABILITY OF THIS INFORMATION FOR ANY PURPOSE. PERSONS MAKING USE OF THIS INFORMATION DO SO AT THEIR OWN RISK.

THESE STANDARD DETAILS ARE MEANT TO ILLUSTRATE GENERAL PRINCIPLES THAT MAY BE HELPFUL, HOWEVER, FINAL DESIGN AND CONSTRUCTION SHOULD BE BASED ON ACTUAL SITE CONDITIONS AND APPLICABLE LOCAL CODE AND STANDARDS. MANY SITE OR LOCAL CONDITIONS MAY REQUIRE SPECIFIC ADDITIONAL DESIGN CONSIDERATIONS. SUCH CONDITIONS MAY INCLUDE SEISMIC ACTIVITY, LOCAL CLIMATE, WIND LOAD AND STORM CONDITIONS (INCLUDING LIKELIHOOD OF TORNADO OR HURRICANE CONDITIONS), SITE SOILS AND DRAINAGE CONSIDERATIONS, AND A VARIETY OF OTHER FACTORS THAT MAY IMPACT BUILDING PERFORMANCE ON A PARTICULAR SITE.






Figure 17. Pre-Cast Plank Option 1




Figure 18. Pre-Cast Plank Option 2




Figure 19. Pre-Cast Plank (Non Bearing) Option 3




Figure 20. Pre-Cast Plank Option 4





Figure 21. Roof Parapet

Click on drawings to enlarge

Table of Contents	
1	Introduction
2	Product Overview
3	Technical Specifications
4	Installation Guidelines
5	Quality Assurance
6	Warranty Information
7	Environmental Impact
8	Health and Safety
9	References
10	Appendix A: Material Properties
11	Appendix B: Test Results
12	Appendix C: Contact Information

Planks and Parapets

Figure 17. Pre-Cast Plank Option 1



Typical Notes:

1. If traditional flashing and weep methods are used, drip edge may be omitted if drainable flashing is terminated at tooled mortar surface. Many flashing systems from which to choose. Drainable weeps and/or vents (also allowing optional Z or S pattern) still necessary.
2. Film-forming Breathable Exterior Coatings must allow flashing, weeps, vents, etc. to drain redirected moisture to the exterior. Inspect after coatings application to assure that all such features are functioning properly.
3. California projects may use alternate moisture control techniques for vertical wall shear test compliance (omit IWR within CMU; use IWR within mortar; use post-applied breathable penetrating sealants or drainable film forming coatings).
4. Assume single-wythe walls are self-covering and therefore especially rely upon design redundancy approach: use of flashing and weeps, IWR, post-applied moisture control means and measures, high performance sealant systems, movement joints, damp-checks, crack control, thermal bridging/condensate control, as well as soil elevation offsets and below-grade damp-proofing – including alkali, salt, and sulfate resistance - are each considered .
5. Moisture-Tolerant Finish / Sheathing / Board as well as High-Performance steel furring or channel are assumed to be appropriately anchored.

Codes and Standards References

Applicable References are found in Section III.

THE DETAILS PRESENTED IN THIS MANUAL ARE STANDARD DETAILS. DESIGNERS SHOULD MAKE SITE SPECIFIC INVESTIGATIONS TO DETERMINE ACTUAL DESIGN REQUIREMENTS, WHICH MAY VARY.

CPG IS NOT RESPONSIBLE FOR USES OF THIS INFORMATION BY THIRD PARTIES, AND DOES NOT WARRANT THE FITNESS OR SUITABILITY OF THIS INFORMATION FOR ANY PURPOSE. PERSONS MAKING USE OF THIS INFORMATION DO SO AT THEIR OWN RISK.

THESE STANDARD DETAILS ARE MEANT TO ILLUSTRATE GENERAL PRINCIPLES THAT MAY BE HELPFUL, HOWEVER, FINAL DESIGN AND CONSTRUCTION SHOULD BE BASED ON ACTUAL SITE CONDITIONS AND APPLICABLE LOCAL CODE AND STANDARDS. MANY SITE OR LOCAL CONDITIONS MAY REQUIRE SPECIFIC ADDITIONAL DESIGN CONSIDERATIONS. SUCH CONDITIONS MAY INCLUDE SEISMIC ACTIVITY, LOCAL CLIMATE, WIND LOAD AND STORM CONDITIONS (INCLUDING LIKELIHOOD OF TORNADO OR HURRICANE CONDITIONS), SITE SOILS AND DRAINAGE CONSIDERATIONS, AND A VARIETY OF OTHER FACTORS THAT MAY IMPACT BUILDING PERFORMANCE ON A PARTICULAR SITE.





Figure 18. Pre-Cast Plank Option 2



Typical Notes:

1. Drip edge may be omitted if drainable flashing is terminated at tooled mortar surface. Many flashing systems from which to choose. Drainable weeps and/or vents (also allowing optional Z or S pattern) still necessary.
2. Film-forming Breathable Exterior Coatings must allow flashing, weeps, vents, etc. to drain redirected moisture to the exterior. Inspect after coatings application to assure that all such features are functioning properly.
3. California projects may use alternate moisture control techniques for vertical wall shear test compliance (omit IWR within CMU; use IWR within mortar; use post-applied breathable penetrating sealants or drainable film forming coatings).
4. Assume single-wythe walls are self-covering and therefore especially rely upon design redundancy approach: use of flashing and weeps, IWR, post-applied moisture control means and measures, high performance sealant systems, movement joints, damp-checks, crack control, thermal bridging/condensate control, as well as soil elevation offsets and below-grade damp-proofing – including alkali, salt, and sulfate resistance - are each considered .
5. Moisture-Tolerant Finish / Sheathing / Board as well as High-Performance steel furring or channel are assumed to be appropriately anchored.

Codes and Standards References

Applicable References are found in Section III.


THE DETAILS PRESENTED IN THIS MANUAL ARE STANDARD DETAILS. DESIGNERS SHOULD MAKE SITE SPECIFIC INVESTIGATIONS TO DETERMINE ACTUAL DESIGN REQUIREMENTS, WHICH MAY VARY.

CPG IS NOT RESPONSIBLE FOR USES OF THIS INFORMATION BY THIRD PARTIES, AND DOES NOT WARRANT THE FITNESS OR SUITABILITY OF THIS INFORMATION FOR ANY PURPOSE. PERSONS MAKING USE OF THIS INFORMATION DO SO AT THEIR OWN RISK.

THESE STANDARD DETAILS ARE MEANT TO ILLUSTRATE GENERAL PRINCIPLES THAT MAY BE HELPFUL, HOWEVER, FINAL DESIGN AND CONSTRUCTION SHOULD BE BASED ON ACTUAL SITE CONDITIONS AND APPLICABLE LOCAL CODE AND STANDARDS. MANY SITE OR LOCAL CONDITIONS MAY REQUIRE SPECIFIC ADDITIONAL DESIGN CONSIDERATIONS. SUCH CONDITIONS MAY INCLUDE SEISMIC ACTIVITY, LOCAL CLIMATE, WIND LOAD AND STORM CONDITIONS (INCLUDING LIKELIHOOD OF TORNADO OR HURRICANE CONDITIONS), SITE SOILS AND DRAINAGE CONSIDERATIONS, AND A VARIETY OF OTHER FACTORS THAT MAY IMPACT BUILDING PERFORMANCE ON A PARTICULAR SITE.



Figure 19. Pre-Cast Plank (Non Bearing) Option 3



Typical Notes:

1. Drip edge may be omitted if drainable flashing is terminated at tooled mortar surface. Many flashing systems from which to choose. Drainable weeps and/or vents (also allowing optional Z or S pattern) still necessary.
2. Film-forming Breathable Exterior Coatings must allow flashing, weeps, vents, etc. to drain redirected moisture to the exterior. Inspect after coatings application to assure that all such features are functioning properly.
3. California projects may use alternate moisture control techniques for vertical wall shear test compliance (omit IWR within CMU; use IWR within mortar; use post-applied breathable penetrating sealants or drainable film forming coatings).
4. Assume single-wythe walls are self-covering and therefore especially rely upon design redundancy approach: use of flashing and weeps, IWR, post-applied moisture control means and measures, high performance sealant systems, movement joints, damp-checks, crack control, thermal bridging/condensate control, as well as soil elevation offsets and below-grade damp-proofing – including alkali, salt, and sulfate resistance - are each considered .
5. Moisture-Tolerant Finish/Sheathing /Board as well as High-Performance steel furring or channel are assumed to be appropriately anchored.

Codes and Standards References

Applicable References are found in Section III.


THE DETAILS PRESENTED IN THIS MANUAL ARE STANDARD DETAILS. DESIGNERS SHOULD MAKE SITE SPECIFIC INVESTIGATIONS TO DETERMINE ACTUAL DESIGN REQUIREMENTS, WHICH MAY VARY.

CPG IS NOT RESPONSIBLE FOR USES OF THIS INFORMATION BY THIRD PARTIES, AND DOES NOT WARRANT THE FITNESS OR SUITABILITY OF THIS INFORMATION FOR ANY PURPOSE. PERSONS MAKING USE OF THIS INFORMATION DO SO AT THEIR OWN RISK.

THESE STANDARD DETAILS ARE MEANT TO ILLUSTRATE GENERAL PRINCIPLES THAT MAY BE HELPFUL, HOWEVER, FINAL DESIGN AND CONSTRUCTION SHOULD BE BASED ON ACTUAL SITE CONDITIONS AND APPLICABLE LOCAL CODE AND STANDARDS. MANY SITE OR LOCAL CONDITIONS MAY REQUIRE SPECIFIC ADDITIONAL DESIGN CONSIDERATIONS. SUCH CONDITIONS MAY INCLUDE SEISMIC ACTIVITY, LOCAL CLIMATE, WIND LOAD AND STORM CONDITIONS (INCLUDING LIKELIHOOD OF TORNADO OR HURRICANE CONDITIONS), SITE SOILS AND DRAINAGE CONSIDERATIONS, AND A VARIETY OF OTHER FACTORS THAT MAY IMPACT BUILDING PERFORMANCE ON A PARTICULAR SITE.



Figure 20. Pre-Cast Plank Option 4



Typical Notes:

1. Drip edge may be omitted if drainable flashing is terminated at tooled mortar surface. Many flashing systems from which to choose. Drainable weeps and/or vents (also allowing optional Z or S pattern) still necessary.
2. Film-forming Breathable Exterior Coatings must allow flashing, weeps, vents, etc. to drain redirected moisture to the exterior. Inspect after coatings application to assure that all such features are functioning properly.
3. California projects may use alternate moisture control techniques for vertical wall shear test compliance (omit IWR within CMU; use IWR within mortar; use post-applied breathable penetrating sealants or drainable film forming coatings).
4. Assume single-wythe walls are self-covering and therefore especially rely upon design redundancy approach: use of flashing and weeps, IWR, post-applied moisture control means and measures, high performance sealant systems, movement joints, damp-checks, crack control, thermal bridging/condensate control, as well as soil elevation offsets and below-grade damp-proofing – including alkali, salt, and sulfate resistance - are each considered .
5. Moisture-Tolerant Finish/Sheathing /Board as well as High-Performance steel furring or channel are assumed to be appropriately anchored.

Codes and Standards References

Applicable References are found in Section III.


THE DETAILS PRESENTED IN THIS MANUAL ARE STANDARD DETAILS. DESIGNERS SHOULD MAKE SITE SPECIFIC INVESTIGATIONS TO DETERMINE ACTUAL DESIGN REQUIREMENTS, WHICH MAY VARY.

CPG IS NOT RESPONSIBLE FOR USES OF THIS INFORMATION BY THIRD PARTIES, AND DOES NOT WARRANT THE FITNESS OR SUITABILITY OF THIS INFORMATION FOR ANY PURPOSE. PERSONS MAKING USE OF THIS INFORMATION DO SO AT THEIR OWN RISK.

THESE STANDARD DETAILS ARE MEANT TO ILLUSTRATE GENERAL PRINCIPLES THAT MAY BE HELPFUL, HOWEVER, FINAL DESIGN AND CONSTRUCTION SHOULD BE BASED ON ACTUAL SITE CONDITIONS AND APPLICABLE LOCAL CODE AND STANDARDS. MANY SITE OR LOCAL CONDITIONS MAY REQUIRE SPECIFIC ADDITIONAL DESIGN CONSIDERATIONS. SUCH CONDITIONS MAY INCLUDE SEISMIC ACTIVITY, LOCAL CLIMATE, WIND LOAD AND STORM CONDITIONS (INCLUDING LIKELIHOOD OF TORNADO OR HURRICANE CONDITIONS), SITE SOILS AND DRAINAGE CONSIDERATIONS, AND A VARIETY OF OTHER FACTORS THAT MAY IMPACT BUILDING PERFORMANCE ON A PARTICULAR SITE.



Figure 21. Roof Parapet



Typical Notes:

1. All High Performance Movement and Bead Sealant Systems assume use of the appropriate Primer in conjunction with the Sealant.
2. Film-forming Breathable Exterior Coatings must allow flashing, weeps, vents, etc. to drain redirected moisture to the exterior.
3. California projects may use alternate moisture control techniques for shear test compliance (omit IWR within CMU; use IWR within mortar; use post-applied breathable penetrating sealants or drainable film forming coatings).
4. Drip edge may be omitted if drainable flashing is terminated at tooled mortar surface. Drainable weeps and/or vents still necessary.
5. See plans for Scupper and roof drainage details. Use High Performance Sealant system.
6. Both exterior and interior sides of parapet must be moisture-controlled.
7. Vertical walls including Fenestration Framing (glazing and lites not necessarily installed due to future loads such as roof, floors, etc.) and Door Jambs shall pass a two hour 45 degree hose stream, spray bar, or similar exterior wall moisture test. Moisture Test shall be performed during wall construction and before interior insulation and finish placement at representative location(s). Successful completion of such test is proof of contract compliance; future compliance is accomplished through maintenance.

Codes and Standards References

Applicable References are found in Section III.

THE DETAILS PRESENTED IN THIS MANUAL ARE STANDARD DETAILS. DESIGNERS SHOULD MAKE SITE SPECIFIC INVESTIGATIONS TO DETERMINE ACTUAL DESIGN REQUIREMENTS, WHICH MAY VARY.

CPG IS NOT RESPONSIBLE FOR USES OF THIS INFORMATION BY THIRD PARTIES, AND DOES NOT WARRANT THE FITNESS OR SUITABILITY OF THIS INFORMATION FOR ANY PURPOSE. PERSONS MAKING USE OF THIS INFORMATION DO SO AT THEIR OWN RISK.

THESE STANDARD DETAILS ARE MEANT TO ILLUSTRATE GENERAL PRINCIPLES THAT MAY BE HELPFUL, HOWEVER, FINAL DESIGN AND CONSTRUCTION SHOULD BE BASED ON ACTUAL SITE CONDITIONS AND APPLICABLE LOCAL CODE AND STANDARDS. MANY SITE OR LOCAL CONDITIONS MAY REQUIRE SPECIFIC ADDITIONAL DESIGN CONSIDERATIONS. SUCH CONDITIONS MAY INCLUDE SEISMIC ACTIVITY, LOCAL CLIMATE, WIND LOAD AND STORM CONDITIONS (INCLUDING LIKELIHOOD OF TORNADO OR HURRICANE CONDITIONS), SITE SOILS AND DRAINAGE CONSIDERATIONS, AND A VARIETY OF OTHER FACTORS THAT MAY IMPACT BUILDING PERFORMANCE ON A PARTICULAR SITE.





Section III

Codes and Standards References

Table of Contents	
SECTION I	SECTION I
SECTION II	SECTION II
SECTION III	SECTION III
SECTION IV	SECTION IV
SECTION V	SECTION V
SECTION VI	SECTION VI
SECTION VII	SECTION VII
SECTION VIII	SECTION VIII
SECTION IX	SECTION IX
SECTION X	SECTION X
SECTION XI	SECTION XI
SECTION XII	SECTION XII
SECTION XIII	SECTION XIII
SECTION XIV	SECTION XIV
SECTION XV	SECTION XV
SECTION XVI	SECTION XVI
SECTION XVII	SECTION XVII
SECTION XVIII	SECTION XVIII
SECTION XIX	SECTION XIX
SECTION XX	SECTION XX
SECTION XXI	SECTION XXI
SECTION XXII	SECTION XXII
SECTION XXIII	SECTION XXIII
SECTION XXIV	SECTION XXIV
SECTION XXV	SECTION XXV
SECTION XXVI	SECTION XXVI
SECTION XXVII	SECTION XXVII
SECTION XXVIII	SECTION XXVIII
SECTION XXIX	SECTION XXIX
SECTION XXX	SECTION XXX

Applicable Code References for Single Wythe Walls

These references are intended to be a guide to the portions of the Model Codes that apply or relate to the construction of Single Wythe Walls. This set of references is only a starting point, and you should be sure to check the underlying Code itself and be sure to check the local Code that the Authority Having Jurisdiction has authorized for the location applicable to your project.

International Building Code (“IBC”) (2006 and 2009); INTERNATIONAL CODE COUNCIL, INC., 4051 West Flossmoor Road, Country Club Hills, IL 60478, including but not limited to:

CHAPTER 1 SCOPE AND ADMINISTRATION; 101.3 Intent, 104.11 Alternative materials, design and methods of construction and equipment, **SECTION 105 PERMITS** 105.1 Required, 105.2 Work exempt from permit, **SECTION 107 SUBMITTAL DOCUMENTS** 107.1 General, 107.2.4 Exterior wall envelope, 107.3.4 Design professional in responsible charge, **SECTION 110 INSPECTIONS** 110.1 General, 110.3.1 Footing and foundation inspection, 110.3.2 Concrete slab and under-floor inspection, 110.3.7 Energy efficiency inspections, 110.3.8 Other inspections, 110.3.9 Special inspections, **SECTION 115 STOP WORK ORDER**.

CHAPTER 2 DEFINITIONS (multiple applicable references).

CHAPTER 7 FIRE AND SMOKE PROTECTION FEATURES; **SECTION 703 FIRE-RESISTANCE RATINGS AND FIRE TESTS**, 703.2 Fire-resistance ratings, 703.2.2 Combustible components, 703.3 Alternative methods for determining fire resistance, **SECTION 704 FIRE-RESISTANCE RATING OF STRUCTURAL MEMBERS**, 704.10 Exterior structural members, 705.4 Materials, 705.5 Fire-resistance ratings, **SECTION 719 THERMAL- AND SOUND-INSULATING MATERIALS**, 719.4 Loose-fill insulation, **SECTION 720 PRESCRIPTIVE FIRE RESISTANCE**, 720.1.2 Unit masonry protection, **SECTION 721 CALCULATED FIRE RESISTANCE**, 721.1 General, **TABLE 720.1(2) RATED FIRE-RESISTANCE PERIODS FOR VARIOUS WALLS AND PARTITIONS**, 721.3 Concrete masonry.

CHAPTER 8 INTERIOR FINISHES; **SECTION 801 GENERAL**, 801.8 Foam plastics, **SECTION 803 WALL AND CEILING FINISHES**, 803.4 Foam plastics, **SECTION 807 INSULATION**. **CHAPTER 12 INTERIOR ENVIRONMENT**; **SECTION 1207 SOUND TRANSMISSION**, 1207.2 Air-borne sound, 1207.2.1 Masonry, **SECTION 1210 SURROUNDING MATERIALS**, 1210.2 Walls and partitions, 1210.3 Showers.

CHAPTER 13 ENERGY EFFICIENCY; **SECTION 1301 GENERAL**, 1301.1.1 Criteria.

CHAPTER 14 EXTERIOR WALLS; **SECTION 1403 PERFORMANCE REQUIREMENTS**, 1403.2 Weather protection, **SECTION 1404 MATERIALS** 1404.4 Masonry, 1404.7 Glass-unit masonry, **SECTION 1405 INSTALLATION OF WALL COVERINGS**, 1405.2 Weather protection, 1405.3 Vapor retarders, 1405.4 Flashing, 1405.4.1 Exterior wall pockets, 1405.4.2 Masonry, 1405.5 Wood veneers (Comparative Requirements), 1405.6 Anchored masonry veneer (Comparative requirements or possible interior placement), 1405.7 Stone veneer (Comparative Requirements), 1405.8 Slab-type veneer (Comparative Requirements), 1405.9 Terra cotta (Comparative Requirements), 1405.10 Adhered masonry veneer, (Comparative Requirements), 1405.10.1 Interior adhered masonry veneers, 1405.11 Metal veneers (Comparative Requirements), 1405.12 Glass veneer (Comparative Requirements), 1405.13 Exterior windows and doors (Comparative Requirements), 1405.14 Vinyl siding (Comparative Requirements), 1405.15 Cement plaster (Comparative Requirements), 1405.16 Fiber-cement siding (Comparative Requirements), 1405.17 Fastening (More Comparative Requirements), **SECTION 1406 COMBUSTIBLE MATERIALS ON THE EXTERIOR SIDE OF EXTERIOR WALLS** (Comparative requirements), **SECTION 1407 METAL COMPOSITE MATERIALS (MCM)** (Comparative Requirements), **SECTION 1408 EXTERIOR INSULATION AND FINISH SYSTEMS (EIFS)**; Comparative requirements).

CHAPTER 15 ROOF ASSEMBLIES AND ROOFTOP STRUCTURES (Includes effects of scuppers, drains, and gutters – or their omissions; plumbing and drainage - including blockage and ice dams - affects lower masonry courses, leakage at interfaces with footing, foundation, and slab, as well as below-grade construction), **SECTION 1503 WEATHER PROTECTION**, 1503.1 General, 1503.2 Flashing, 1503.2.1 Locations, 1503.4 Roof drainage, 1503.4.1 Secondary drainage required, 1503.4.2 Scuppers, 1503.4.3 Gutters.

CHAPTER 16 STRUCTURAL DESIGN (In general, an awareness of the many different types of loads, geographic effects, and building categories – each affecting CMU walls requirements, and effect on costs, along with competitive wall requirements and effect on costs),

CHAPTER 1 SCOPE AND ADMINISTRATION	101.3 Intent	104.11 Alternative materials, design and methods of construction and equipment	SECTION 105 PERMITS	105.1 Required	105.2 Work exempt from permit	SECTION 107 SUBMITTAL DOCUMENTS	107.1 General	107.2.4 Exterior wall envelope	107.3.4 Design professional in responsible charge	SECTION 110 INSPECTIONS	110.1 General	110.3.1 Footing and foundation inspection	110.3.2 Concrete slab and under-floor inspection	110.3.7 Energy efficiency inspections	110.3.8 Other inspections	110.3.9 Special inspections	SECTION 115 STOP WORK ORDER
CHAPTER 2 DEFINITIONS	(multiple applicable references)																
CHAPTER 7 FIRE AND SMOKE PROTECTION FEATURES	SECTION 703 FIRE-RESISTANCE RATINGS AND FIRE TESTS, 703.2 Fire-resistance ratings, 703.2.2 Combustible components, 703.3 Alternative methods for determining fire resistance, SECTION 704 FIRE-RESISTANCE RATING OF STRUCTURAL MEMBERS, 704.10 Exterior structural members, 705.4 Materials, 705.5 Fire-resistance ratings, SECTION 719 THERMAL- AND SOUND-INSULATING MATERIALS, 719.4 Loose-fill insulation, SECTION 720 PRESCRIPTIVE FIRE RESISTANCE, 720.1.2 Unit masonry protection, SECTION 721 CALCULATED FIRE RESISTANCE, 721.1 General, TABLE 720.1(2) RATED FIRE-RESISTANCE PERIODS FOR VARIOUS WALLS AND PARTITIONS, 721.3 Concrete masonry.																
CHAPTER 8 INTERIOR FINISHES	SECTION 801 GENERAL, 801.8 Foam plastics, SECTION 803 WALL AND CEILING FINISHES, 803.4 Foam plastics, SECTION 807 INSULATION. CHAPTER 12 INTERIOR ENVIRONMENT; SECTION 1207 SOUND TRANSMISSION, 1207.2 Air-borne sound, 1207.2.1 Masonry, SECTION 1210 SURROUNDING MATERIALS, 1210.2 Walls and partitions, 1210.3 Showers.																
CHAPTER 13 ENERGY EFFICIENCY	SECTION 1301 GENERAL, 1301.1.1 Criteria.																
CHAPTER 14 EXTERIOR WALLS	SECTION 1403 PERFORMANCE REQUIREMENTS, 1403.2 Weather protection, SECTION 1404 MATERIALS 1404.4 Masonry, 1404.7 Glass-unit masonry, SECTION 1405 INSTALLATION OF WALL COVERINGS, 1405.2 Weather protection, 1405.3 Vapor retarders, 1405.4 Flashing, 1405.4.1 Exterior wall pockets, 1405.4.2 Masonry, 1405.5 Wood veneers (Comparative Requirements), 1405.6 Anchored masonry veneer (Comparative requirements or possible interior placement), 1405.7 Stone veneer (Comparative Requirements), 1405.8 Slab-type veneer (Comparative Requirements), 1405.9 Terra cotta (Comparative Requirements), 1405.10 Adhered masonry veneer, (Comparative Requirements), 1405.10.1 Interior adhered masonry veneers, 1405.11 Metal veneers (Comparative Requirements), 1405.12 Glass veneer (Comparative Requirements), 1405.13 Exterior windows and doors (Comparative Requirements), 1405.14 Vinyl siding (Comparative Requirements), 1405.15 Cement plaster (Comparative Requirements), 1405.16 Fiber-cement siding (Comparative Requirements), 1405.17 Fastening (More Comparative Requirements), SECTION 1406 COMBUSTIBLE MATERIALS ON THE EXTERIOR SIDE OF EXTERIOR WALLS (Comparative requirements), SECTION 1407 METAL COMPOSITE MATERIALS (MCM) (Comparative Requirements), SECTION 1408 EXTERIOR INSULATION AND FINISH SYSTEMS (EIFS); Comparative requirements).																
CHAPTER 15 ROOF ASSEMBLIES AND ROOFTOP STRUCTURES	(Includes effects of scuppers, drains, and gutters – or their omissions; plumbing and drainage - including blockage and ice dams - affects lower masonry courses, leakage at interfaces with footing, foundation, and slab, as well as below-grade construction), SECTION 1503 WEATHER PROTECTION, 1503.1 General, 1503.2 Flashing, 1503.2.1 Locations, 1503.4 Roof drainage, 1503.4.1 Secondary drainage required, 1503.4.2 Scuppers, 1503.4.3 Gutters.																
CHAPTER 16 STRUCTURAL DESIGN	(In general, an awareness of the many different types of loads, geographic effects, and building categories – each affecting CMU walls requirements, and effect on costs, along with competitive wall requirements and effect on costs),																

1603.1.6 Geotechnical information, 1603.1.9 Systems and components requiring special inspections for seismic resistance, 1603.1.7 Flood design data, **SECTION 1604 GENERAL DESIGN REQUIREMENTS**, 1604.2 Strength, 1604.3.4 Masonry, 1604.5 Occupancy category, **TABLE 1604.5 OCCUPANCY CATEGORY OF BUILDINGS AND OTHER STRUCTURES**, 1604.8 Anchorage, 1607.7 Loads on handrails, guards, grab bars, seats and vehicle barrier systems, 1607.7.3 Vehicle barrier systems, 1607.8 Impact loads, 1607.8.1 Elevators, 1607.8.2 Machinery, 1607.11.3 Landscaped roofs, 1607.13 Interior walls and partitions, **SECTION 1608, SNOW LOADS**, **SECTION 1609 WIND LOADS**, 1609.5 Roof systems, 1609.6.4 Design procedure, **SECTION 1610 SOIL LATERAL LOADS**, **SECTION 1611 RAIN LOADS**, [P] **FIGURE 1611.1 100-YEAR, 1-HOUR RAINFALL (INCHES)**, 1611.2 Ponding instability, 1611.3 Controlled drainage, **SECTION 1612 FLOOD LOADS**, **SECTION 1613 EARTHQUAKE LOADS**, **FIGURE 1613.5(1-14) MAXIMUM CONSIDERED EARTHQUAKE GROUND MOTION**.

CHAPTER 17 STRUCTURAL TESTS AND SPECIAL INSPECTIONS, SECTION 1703 APPROVALS, 1703.1 Approved agency, 1703.2 Written approval, **SECTION 1704 SPECIAL INSPECTIONS**, 1704.1.1 Statement of special inspections, 1704.3 Steel construction, 1704.4 Concrete construction, 1704.5 Masonry construction, **TABLE 1704.5.1 LEVEL 1 REQUIRED VERIFICATION AND INSPECTION OF MASONRY CONSTRUCTION**, **TABLE 1704.5.3 LEVEL 2 REQUIRED VERIFICATION AND INSPECTION OF MASONRY CONSTRUCTION**, 1704.5.1 Empirically designed masonry, glass unit masonry and masonry veneer in Occupancy Category IV, 1704.5.2 Engineered masonry in Occupancy Category I, II or III, 1704.5.3 Engineered masonry in Occupancy Category IV, 1704.6 Wood construction, 1704.7 Soils, 1704.8 Driven deep foundations, 1704.9 Cast-in-place deep foundations, 1704.10 Helical pile foundations, 1704.11 Vertical masonry foundation elements, 1704.12 Sprayed fire-resistant materials, 1704.13 Mastic and intumescent fire-resistant coatings, 1704.14 Exterior insulation and finish systems (EIFS), 1704.16 Special inspection for smoke control, **SECTION 1705 STATEMENT OF SPECIAL INSPECTIONS**,

CHAPTER 18 SOILS AND FOUNDATIONS; SECTION 1801 GENERAL; 1801.1 Scope, **SECTION 1803 GEOTECHNICAL INVESTIGATIONS**, 1803.1 General, 1803.3 Basis of investigation, 1803.5 Investigated conditions, 1803.5.1 Classification, 1803.5.2 Questionable soil, 1803.5.3 Expansive soil, 1803.5.4 Ground-water table, Exception, 1803.5.5 Deep foundations, 1803.5.6 Rock strata, 1803.5.8 Compacted fill material, 1803.5.9 Controlled low-strength material (CLSM), 1803.5.10 Alternate setback and clearance, 1803.5.11 Seismic Design Categories C through F, 1803.5.12 Seismic Design Categories D through F, 1803.6 Reporting, **SECTION 1804 EXCAVATION, GRADING AND FILL**, **SECTION 1805 DAMPROOFING AND WATERPROOFING**, 1805.1 General, 1805.1.1 Story above grade plane, 1805.1.3 Ground-water control, 1805.2 Dampproofing, 1805.2.1 Floors, 1805.2.2 Walls, 1805.2.2.1 Surface preparation of walls, 1805.3 Waterproofing, 1805.3.1 Floors, 1805.3.2 Walls, 1805.3.2.1 Surface preparation of walls, 1805.3.3 Joints and penetrations, 1805.4 Subsoil drainage system, 1805.4.1 Floor base course, Exception, 1805.4.2 Foundation drain, 1805.4.3 Drainage discharge, **SECTION 1807 FOUNDATION WALLS, RETAINING WALLS AND EMBEDDED POSTS AND POLES**, 1807.1.5 Concrete and masonry foundation walls, Exception, 1807.1.6 Prescriptive design of concrete and masonry foundation walls, 1807.1.6.1 Foundation wall thickness, 1807.1.6.2.1 Seismic requirements, 1807.1.6.3 Masonry foundation walls, 1807.1.6.3.1 Alternative foundation wall reinforcement, 1807.1.6.3.2 Seismic requirements, 1807.2 Retaining walls, 1807.2.1 General, 1807.3 Embedded posts and poles (masonry bracing) 1808.5 Shifting or moving soils, 1808.6 Design for expansive soils, 1808.7 Foundations on or adjacent to slopes, 1808.9 Vertical masonry foundation elements, **SECTION 1809 SHALLOW FOUNDATIONS**, 1809.7 Prescriptive footings for light-frame construction (masonry unit footings) 1809.9 Masonry-unit footings, 1809.10 Pier and curtain wall foundations (includes masonry piers and foundations).

CHAPTER 19 CONCRETE; SECTION 1904 DURABILITY REQUIREMENTS, 1904.1 Water-cementitious materials ratio, 1904.2 Exposure categories and classes (sulfates, etc.), 1904.3 Concrete properties, **TABLE 1904.3 MINIMUM SPECIFIED COMPRESSIVE STRENGTH (f'c)** (relates to exposure, sulfates, etc.) 1904.4 Freezing and thawing exposures, 1904.5 Alternative cementitious materials for sulfate exposure.

CHAPTER 21 MASONRY

CHAPTER 22 STEEL; 2206.2 Design (anchorage; masonry in-fill needs be anchored one way or another).

CHAPTER 23 WOOD; 2304.10.2 Floor framing (on masonry), 2304.10.4 Floor decks (and masonry), 2304.11.2.3 Exterior walls below grade (and masonry), 2304.11.2.5 Girder ends (and masonry walls), 2304.11.2.7 Posts or columns (and masonry), 2304.12 Long-term loading (and masonry), **TABLE 2306.6** (a. masonry bracing limit), **TABLE 2306.7** (a. masonry shear load), 2308.3.3 Sill anchorage (masonry foundation)

CHAPTER 25 GYPSUM BOARD AND PLASTER; SECTION 2503 INSPECTION (for these purposes, as interior finish or comparative

Table of Contents	
1	Introduction
2	References
3	1.0 General
4	1.1 Design
5	1.2 Construction
6	1.3 Inspection
7	1.4 Maintenance
8	1.5 Safety
9	1.6 Quality Control
10	1.7 Quality Assurance
11	1.8 Record Keeping
12	1.9 Training
13	1.10 Professional Responsibility
14	1.11 Ethics
15	1.12 Communication
16	1.13 Teamwork
17	1.14 Leadership
18	1.15 Problem Solving
19	1.16 Decision Making
20	1.17 Conflict Resolution
21	1.18 Negotiation
22	1.19 Mediation
23	1.20 Arbitration
24	1.21 Litigation
25	1.22 Dispute Resolution
26	1.23 Risk Management
27	1.24 Insurance
28	1.25 Bonds
29	1.26 Financial Management
30	1.27 Human Resources
31	1.28 Safety Management
32	1.29 Environmental Management
33	1.30 Social Responsibility
34	1.31 Sustainability
35	1.32 Innovation
36	1.33 Research and Development
37	1.34 Marketing
38	1.35 Sales
39	1.36 Customer Service
40	1.37 Supply Chain Management
41	1.38 Procurement
42	1.39 Logistics
43	1.40 Inventory Management
44	1.41 Quality Management
45	1.42 Project Management
46	1.43 Contract Management
47	1.44 Risk Management
48	1.45 Compliance
49	1.46 Regulatory Affairs
50	1.47 Public Relations
51	1.48 Community Relations
52	1.49 Government Relations
53	1.50 International Trade
54	1.51 Globalization
55	1.52 Digital Marketing
56	1.53 E-commerce
57	1.54 Social Media
58	1.55 Mobile Marketing
59	1.56 Analytics
60	1.57 Big Data
61	1.58 Cloud Computing
62	1.59 Cybersecurity
63	1.60 Artificial Intelligence
64	1.61 Blockchain
65	1.62 Internet of Things
66	1.63 Smart Cities
67	1.64 Smart Buildings
68	1.65 Smart Infrastructure
69	1.66 Smart Transportation
70	1.67 Smart Energy
71	1.68 Smart Agriculture
72	1.69 Smart Manufacturing
73	1.70 Smart Retail
74	1.71 Smart Healthcare
75	1.72 Smart Education
76	1.73 Smart Government
77	1.74 Smart Living
78	1.75 Smart Mobility
79	1.76 Smart Security
80	1.77 Smart Defense
81	1.78 Smart Space
82	1.79 Smart Ocean
83	1.80 Smart Atmosphere
84	1.81 Smart Earth
85	1.82 Smart Universe
86	1.83 Smart Future
87	1.84 Smart Past
88	1.85 Smart Present
89	1.86 Smart Now
90	1.87 Smart Tomorrow
91	1.88 Smart Yesterday
92	1.89 Smart Today
93	1.90 Smart Always
94	1.91 Smart Never
95	1.92 Smart Sometimes
96	1.93 Smart Often
97	1.94 Smart Rarely
98	1.95 Smart Occasionally
99	1.96 Smart Frequently
100	1.97 Smart Infrequently
101	1.98 Smart Regularly
102	1.99 Smart Irregularly
103	1.100 Smart Randomly

requirements), **SECTION 2504 VERTICAL AND HORIZONTAL ASSEMBLIES**; **SECTION 2505 SHEAR WALL CONSTRUCTION** (comparative requirements), **SECTION 2506 GYPSUM BOARD MATERIALS** (as interior finish or comparative requirements), **SECTION 2507 LATHING AND PLASTERING** (as interior finish), **SECTION 2508 GYPSUM CONSTRUCTION** (as interior finish or comparative requirements), 2508.2 Limitations, 2508.2.1 Weather protection, **SECTION 2509 GYPSUM BOARD IN SHOWERS AND WATER CLOSETS** (as interior finish or comparative requirements), **SECTION 2510 LATHING AND FURRING FOR CEMENT PLASTER (STUCCO)** (as interior finish or comparative requirements), **SECTION 2511 INTERIOR PLASTER** (as interior finish or comparative requirements),

CHAPTER 26 PLASTIC; **SECTION 2601 GENERAL**; 2601.1 Scope (for these purposes, primarily as Energy Conservation; insulation. Also as comparative requirements.), **SECTION 2603 FOAM PLASTIC INSULATION**, 2603.4 Thermal barrier, 2603.4.1 Thermal barrier not required, 2603.4.1.1 Masonry or concrete construction, 2603.4.1.11 Interior trim, 2603.4.1.12 Interior signs, 2603.5 Exterior walls of buildings of any height (comparative requirements), 2603.5.3 Potential heat, 2603.5.6 Label required, 2603.5.7 Ignition, Exception (as relating to masonry covering), 2603.7 Plenums (vertical wall application), 2603.8 Protection against termites (comparative requirements and separation distances), Exceptions (as masonry applicable), **SECTION 2604 INTERIOR FINISH AND TRIM**, **SECTION 2613 REFLECTIVE PLASTIC CORE INSULATION**.

CHAPTER 28 MECHANICAL SYSTEMS; **SECTION 2801 GENERAL**; 2801.1 Scope.

CHAPTER 29 PLUMBING SYSTEMS; **SECTION 2901 GENERAL**, [P] 2901.1 Scope.

CHAPTER 30 ELEVATORS AND CONVEYING SYSTEMS; **SECTION 3002 HOISTWAY ENCLOSURES**, 3002.1 Hoistway enclosure protection (as fire-resistance requirements). **SECTION 3006 MACHINE ROOMS**, 3006.4 Machine rooms and machinery spaces (as fire-resistance requirements), **SECTION 3007 FIRE SERVICE ACCESS ELEVATOR**, 3007.2 Hoistway enclosures protection (as fire-resistance requirements), **SECTION 3008 OCCUPANT EVACUATION ELEVATORS**, 3008.9 Hoistway enclosure protection, (as fire-resistance requirements),

CHAPTER 31 SPECIAL CONSTRUCTION; **SECTION 3104 PEDESTRIAN WALKWAYS AND TUNNELS**; 3104.3 Construction, (as fire-resistance requirements), 3104.5 Fire barriers between pedestrian walkways and Buildings, 3104.10 Tunneler walkway (as fire resistance requirements), **SECTION 3106 MARQUEES**, 3106.5 Construction (as fire and deterioration resistance requirements), **SECTION 3109 SWIMMING POOL ENCLOSURES AND SAFETY DEVICES**, 3109.3 Public swimming pools (as fencing requirements), 3109.4 Residential swimming pools (as barrier requirements),

CHAPTER 32 ENCROACHMENTS INTO THE PUBLIC RIGHT-OF-WAY; **SECTION 3201 GENERAL**, 3201.4 Drainage (as affects implied project ground-level construction and drainage), 3202.2 Encroachments above grade and below 8 feet in height (as restrictions and allowances),

CHAPTER 33 SAFEGUARDS DURING CONSTRUCTION; **SECTION 3301 GENERAL**, 3301.1 Scope, **SECTION 3303 DEMOLITION**, 3303.5 Water accumulation (applies both ways), **SECTION 3307 PROTECTION OF ADJOINING PROPERTY** (applies both ways).

International Energy Conservation Code (“IECC”; especially 2006 and 2009); INTERNATIONAL CODE COUNCIL, INC., 4051 West Flossmoor Road, Country Club Hills, IL 60478; including but not limited to:

CHAPTER 1 ADMINISTRATION, 101.3 Intent,

CHAPTER 2 DEFINITIONS,

CHAPTER 3 CLIMATE ZONES,

CHAPTER 5 COMMERCIAL ENERGY EFFICIENCY, **SECTION 502 BUILDING ENVELOPE REQUIREMENTS**, **TABLE 502.1.2 BUILDING**

Table of Contents	
CHAPTER 1 ADMINISTRATION	101.3 Intent
CHAPTER 2 DEFINITIONS	
CHAPTER 3 CLIMATE ZONES	
CHAPTER 5 COMMERCIAL ENERGY EFFICIENCY	SECTION 502 BUILDING ENVELOPE REQUIREMENTS, TABLE 502.1.2 BUILDING

CONCRETE PRODUCTS GROUP

ENVELOPE REQUIREMENTS OPAQUE ELEMENT, MAXIMUM U-FACTORS, TABLE 502.2(1) BUILDING ENVELOPE REQUIREMENTS - OPAQUE ASSEMBLIES (Minimum R-Values), 502.2.4 Below-grade walls, 502.2.6 Slabs on grade, 502.4 Air leakage (Mandatory), 502.4.3 Sealing of the building envelope, **SECTION 506 TOTAL BUILDING PERFORMANCE**, 506.2 Mandatory requirements, 506.3 Performance-based compliance, 506.4 Documentation, 506.5 Calculation procedure, 506.6 Calculation software tools, 506.6.1 Specific approval

American Society of Heating and Refrigeration Engineers Standard 90.1 (“ASHRAE 90.1”, or “90.1”; especially 2004 and 2007 editions) (including Normative Appendices as well as Informative Appendices), American Society of Heating and Refrigeration Engineers Inc., 1791 Tullie Circle NE, Atlanta, GA 30329.

3.0 DEFINITIONS, ABBREVIATIONS, AND ACRONYMS, 3.2 Definitions,

4.0 ADMINISTRATION AND ENFORCEMENT, 4.1.7 Normative Appendices, 4.2.1 Compliance Paths,

5.0 GENERAL 5.1.4 Climate, 5.2 Compliance Paths, 5.2.1 a. 5.5 Prescriptive Building Envelope Option, 5.2.1 b. 5.6 Building Envelope Trade-Off Option, 5.2.2 (as relates to Energy Cost Budget), 5.4 Mandatory Provisions, 5.4.1 Insulation, 5.4.3 Air Leakage, 5.4.3.1 Building Envelope Sealing, 5.5 Prescriptive Building Envelope Option, Building Envelope Requirements for Climate Zones Tables 5.5-1 through 8, 5.5.3.2 Above-Grade Wall Insulation, 5.5.3.3 Below-Grade Wall Insulation, 5.5.3.4 Floor Insulation, 5.5.3.5 Slab-on-Grade Insulation, 5.6 Building Envelope Trade-Off Option.

NORMATIVE APPENDIX A RATED R-VALUE OF INSULATION AND ASSEMBLY U-FACTOR, C-FACTOR, AND F-FACTOR DETERMINATION, A.1 GENERAL, A.3 ABOVE-GRADE WALLS, A.4 BELOW-GRADE WALLS, A.5 FLOORS, A.6 SLAB-ON-GRADE FLOORS, A.9 DETERMINATION OF ALTERNATE ASSEMBLY U-FACTORS, C-FACTORS, OR HEAT CAPACITIES,

NORMATIVE APPENDIX B-BUILDING ENVELOPE CLIMATE CRITERIA,

NORMATIVE APPENDIX C METHODOLOGY FOR BUILDING ENVELOPE TRADE-OFF OPTION IN SUBSECTION 5.6.

International Mechanical Code (“IMC”) (especially 2006 and 2009); INTERNATIONAL CODE COUNCIL, INC., 4051 West Flossmoor Road, Country Club Hills, IL 60478; Including but not limited to:

CHAPTER 2 DEFINITIONS, SECTION 202 GENERAL DEFINITIONS (especially AIR, CONDENSATE, CONDITIONED SPACE, ENVIRONMENTAL AIR, NATURAL VENTILATION, OUTDOOR AIR, PLENUM, RECIRCULATED AIR, RETURN AIR, SUPPLY AIR, VENTILATION AIR),

CHAPTER 3 GENERAL REGULATIONS, SECTION 304 INSTALLATION, 304.10 Clearances from grade (possible affect on masonry wall base course placement), 306.5 Equipment and appliances on roofs or elevated structures (affects wall loads), **SECTION 307 CONDENSATE DISPOSAL**(moisture source on, in, or adjacent to building).

CHAPTER 4 VENTILATION SECTION 402 NATURAL VENTILATION, [B] 402.2 Ventilation area required, [B] 402.4 Openings below grade (affects wall penetrations, drainage, moisture resistance, dampproofing, etc), 403.4 Exhaust ventilation (affects net Energy Conservation, wall penetrations and weather protection, additional supply air and related penetrations, etc.),

CHAPTER 5 EXHAUST SYSTEMS, 501.2.2 Exhaust opening protection (affects net Energy Conservation, wall penetrations and weather protection, additional supply air and related penetrations, etc).

Table of Contents	
1.0 GENERAL	1.0
2.0 DEFINITIONS	2.0
3.0 GENERAL REGULATIONS	3.0
4.0 VENTILATION	4.0
5.0 EXHAUST SYSTEMS	5.0
6.0 BUILDING ENVELOPE	6.0
7.0 MECHANICAL SYSTEMS	7.0
8.0 PLUMBING	8.0
9.0 ELECTRICAL	9.0
10.0 SAFETY	10.0
11.0 APPENDICES	11.0
12.0 INDEX	12.0

International Plumbing Code (“IPC”; especially 2006 and 2009) INTERNATIONAL CODE COUNCIL, INC., 4051 West Flossmoor Road, Country Club Hills, IL 60478; Including but not limited to:

CHAPTER 2 DEFINITIONS, SECTION 202, GENERAL DEFINITIONS (ACCESS (TO), WASTE),

CHAPTER 3 GENERAL REGULATIONS, SECTION 314; CONDENSATE DISPOSAL; [M] 314.2.1 Condensate disposal (additional potential source of moisture or waste at walls, base courses, footings, slabs, soil, etc.),

CHAPTER 4 FIXTURES, FAUCETS AND FIXTURE FITTINGS, SECTION 417 SHOWERS; 417.4 Shower compartments; 417.4.1 Wall area,

CHAPTER 6 WATER SUPPLY AND DISTRIBUTION, SECTION 605 MATERIALS, JOINTS AND CONNECTIONS; 605.1 Soil and ground water (emphasizing problem soil identification, remediation),

CHAPTER 9 VENTS, SECTION 904 VENT TERMINALS; 904.6 Extension through the wall (wall penetration),

CHAPTER 11 STORM DRAINAGE, SECTION 1102 STORM DRAINAGE, 1101.2 Where required, 1101.7 Roof design (note design assumptions), **SECTION 1106 SIZE OF CONDUCTORS, LEADERS AND STORM DRAINS,** 1106.1 General (Similar design basis as IBC ?), 1106.5 Parapet wall scupper location (wall penetration), 1106.6 Size of roof gutters (collected rain water to drain potentially at footing, foundation, base course area), **SECTION 1107 SECONDARY (EMERGENCY) ROOF DRAINS,** 1107.1 Secondary drainage required, 1107.2 Separate systems required (overflow to footing, foundation, base course area).

TMS 402/ACI 530/ASCE 5 and Commentary (“TMS 402”, “TMS”, or “MSJC”; Masonry Code; Building Code Requirements for Masonry Structures; especially 2005 and 2008 editions); The Masonry Society, 3970 Broadway, Suite 201-D, Boulder, CO 80304-1135; 105 South Sunset, Suite Q, Longmont, CO 80501.

TMS 602/ACI 530.1/ASCE 6 and Commentary (“TMS 602”, “TMS” or “MSJC”; Masonry Specifications; Specifications for Masonry Structures; especially 2005 and 2008 editions); The Masonry Society, 3970 Broadway, Suite 201-D, Boulder, CO 80304-1135; 105 South Sunset, Suite Q, Longmont, CO 80501.

ASTM International Specifications, Test Methods, and Practices; (“ASTM”; as applicable by Code, Standard, or Specification; more recent editions), ASTM International, Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, Including **but** not limited to:

ASTM C 90 Standard Specification for Loadbearing Concrete Masonry Units,

ASTM C 140 Standard Test Methods for Sampling and Testing Concrete Masonry Units and Related Units.

NCMA TEK MANUAL; NATIONAL CONCRETE MASONRY ASSOCIATION, 13750 Sunrise Valley Drive, Herndon, Virginia 20171,

Table of Contents	
1. Introduction	1.1
2. General Requirements	2.1
3. Materials	3.1
4. Construction	4.1
5. Inspection	5.1
6. Testing	6.1
7. Maintenance	7.1
8. Appendix	8.1
9. Index	9.1

www.ncma.org, publications@ncma.org.

NCMA DETAILS; NATIONAL CONCRETE MASONRY ASSOCIATION, 13750 Sunrise Valley Drive, Herndon, Virginia 20171, www.ncma.org, publications@ncma.org.

NCMA Fire Energy and Sound Calculator; NATIONAL CONCRETE MASONRY ASSOCIATION 13750 Sunrise Valley Drive, Herndon, Virginia 20171, www.ncma.org publications@ncma.org.

Table of Contents	
Introduction	1
1.1 Purpose	1
1.2 Scope	1
1.3 Organization	1
2. General	2
2.1 General	2
2.2 Materials	2
2.3 Construction	2
2.4 Installation	2
2.5 Maintenance	2
2.6 Safety	2
2.7 Environmental	2
2.8 Accessibility	2
2.9 Performance	2
2.10 Durability	2
2.11 Reliability	2
2.12 Cost	2
2.13 Quality	2
2.14 Sustainability	2
2.15 Innovation	2
2.16 Research	2
2.17 Education	2
2.18 Professional Development	2
2.19 Industry Collaboration	2
2.20 Public Policy	2
2.21 Standards	2
2.22 Codes	2
2.23 Regulations	2
2.24 International	2
2.25 Global	2
2.26 Regional	2
2.27 National	2
2.28 Local	2
2.29 State	2
2.30 County	2
2.31 City	2
2.32 Town	2
2.33 Village	2
2.34 Hamlet	2
2.35 Unincorporated	2
2.36 Census	2
2.37 Metropolitan	2
2.38 Micropolitan	2
2.39 Nonmetropolitan	2
2.40 Rural	2
2.41 Urban	2
2.42 Suburban	2
2.43 Exurban	2
2.44 Frontier	2
2.45 Remote	2
2.46 Isolated	2
2.47 Scattered	2
2.48 Dispersed	2
2.49 Concentrated	2
2.50 Agglomerated	2
2.51 Clustered	2
2.52 Grouped	2
2.53 Planned	2
2.54 Organic	2
2.55 Evolving	2
2.56 Shifting	2
2.57 Changing	2
2.58 Adapting	2
2.59 Resilient	2
2.60 Flexible	2
2.61 Dynamic	2
2.62 Responsive	2
2.63 Agile	2
2.64 Versatile	2
2.65 Multifunctional	2
2.66 Multi-use	2
2.67 Mixed-use	2
2.68 Integrated	2
2.69 Cohesive	2
2.70 Synergistic	2
2.71 Complementary	2
2.72 Complementary	2
2.73 Complementary	2
2.74 Complementary	2
2.75 Complementary	2
2.76 Complementary	2
2.77 Complementary	2
2.78 Complementary	2
2.79 Complementary	2
2.80 Complementary	2

CONCRETE PRODUCTS GROUP



Section IV Guide Specification

Table of Contents	
Introduction	1
Section IV - Guide Specification	1
1.01 - Summary	1
1.02 - Related Sections	1
1.03 - Materials	1
1.04 - Execution	1
1.05 - Quality Assurance	1
1.06 - Protection	1
1.07 - Cleaning	1
1.08 - Maintenance	1
1.09 - Related Sections	1
1.10 - Related Sections	1
1.11 - Related Sections	1
1.12 - Related Sections	1
1.13 - Related Sections	1
1.14 - Related Sections	1
1.15 - Related Sections	1
1.16 - Related Sections	1
1.17 - Related Sections	1
1.18 - Related Sections	1
1.19 - Related Sections	1
1.20 - Related Sections	1
1.21 - Related Sections	1
1.22 - Related Sections	1
1.23 - Related Sections	1
1.24 - Related Sections	1
1.25 - Related Sections	1
1.26 - Related Sections	1
1.27 - Related Sections	1
1.28 - Related Sections	1
1.29 - Related Sections	1
1.30 - Related Sections	1
1.31 - Related Sections	1
1.32 - Related Sections	1
1.33 - Related Sections	1
1.34 - Related Sections	1
1.35 - Related Sections	1
1.36 - Related Sections	1
1.37 - Related Sections	1
1.38 - Related Sections	1
1.39 - Related Sections	1
1.40 - Related Sections	1
1.41 - Related Sections	1
1.42 - Related Sections	1
1.43 - Related Sections	1
1.44 - Related Sections	1
1.45 - Related Sections	1
1.46 - Related Sections	1
1.47 - Related Sections	1
1.48 - Related Sections	1
1.49 - Related Sections	1
1.50 - Related Sections	1
1.51 - Related Sections	1
1.52 - Related Sections	1
1.53 - Related Sections	1
1.54 - Related Sections	1
1.55 - Related Sections	1
1.56 - Related Sections	1
1.57 - Related Sections	1
1.58 - Related Sections	1
1.59 - Related Sections	1
1.60 - Related Sections	1
1.61 - Related Sections	1
1.62 - Related Sections	1
1.63 - Related Sections	1
1.64 - Related Sections	1
1.65 - Related Sections	1
1.66 - Related Sections	1
1.67 - Related Sections	1
1.68 - Related Sections	1
1.69 - Related Sections	1
1.70 - Related Sections	1
1.71 - Related Sections	1
1.72 - Related Sections	1
1.73 - Related Sections	1
1.74 - Related Sections	1
1.75 - Related Sections	1
1.76 - Related Sections	1
1.77 - Related Sections	1
1.78 - Related Sections	1
1.79 - Related Sections	1
1.80 - Related Sections	1
1.81 - Related Sections	1
1.82 - Related Sections	1
1.83 - Related Sections	1
1.84 - Related Sections	1
1.85 - Related Sections	1
1.86 - Related Sections	1
1.87 - Related Sections	1
1.88 - Related Sections	1
1.89 - Related Sections	1
1.90 - Related Sections	1
1.91 - Related Sections	1
1.92 - Related Sections	1
1.93 - Related Sections	1
1.94 - Related Sections	1
1.95 - Related Sections	1
1.96 - Related Sections	1
1.97 - Related Sections	1
1.98 - Related Sections	1
1.99 - Related Sections	1
2.00 - Related Sections	1

SPEC-BRIK® WCT™ GUIDE SPECIFICATION

*Download this specification
in Microsoft Word® Format*

SECTION 04 22 23

ARCHITECTURAL CONCRETE MASONRY

PART 1 – GENERAL

1.1 SUMMARY

A. Section includes architectural concrete masonry work as shown and specified Work includes:

1. Architectural concrete masonry exterior wall veneer facing.
2. Architectural concrete masonry exterior single wythe walls.
3. Special shapes.
4. Installation of anchors, reinforcement and ties furnished under Section 04 05 19 -Masonry Anchorage and Reinforcing.
5. Installation of embedded masonry flashing [, loose masonry fill insulation] and related masonry accessories furnished under Section 04 05 23 – Masonry Accessories.
6. Installation of anchor bolts, bearing plates and loose steel angle lintels furnished under Section 05 12 00 - Structural Steel Framing.
7. Installation of wood blocking and nailers furnished under Section 06 10 00 – Rough Carpentry.
8. Installation of sheet metal flashing furnished under Section 07 60 00 Flashing and Sheet Metal.

B. Related Sections:

1. Section 04 05 15 Masonry Mortar and Grout: Mortar and grout materials.
2. Section 07 21 19 Foamed-In-Place Insulation: Foamed-in-place insulation materials and installation.

1.2 REFERENCES

A. Reference standards:

1. American Concrete Institute (ACI):
 - a. ACI 530-05/ASCE 5-05/TMS 402-05 “Building Code Requirements for Masonry Structures”
 - b. ACI 530.1-05/ASCE 6-05/TMS 602-05 “Specification for Masonry Structures”
2. American Society for Testing and Materials (ASTM):




Table of Contents

Section 01 00 00 - General	Section 04 00 00 - Masonry
Section 02 00 00 - Exterior Finishes	Section 05 00 00 - Structural Steel
Section 03 00 00 - Masonry	Section 06 00 00 - Carpentry
Section 04 00 00 - Masonry	Section 07 00 00 - Flashing and Sheet Metal
Section 05 00 00 - Structural Steel	Section 08 00 00 - Windows and Doors
Section 06 00 00 - Carpentry	Section 09 00 00 - Paint and Coatings
Section 07 00 00 - Flashing and Sheet Metal	Section 10 00 00 - Electrical
Section 08 00 00 - Windows and Doors	Section 11 00 00 - Mechanical
Section 09 00 00 - Paint and Coatings	Section 12 00 00 - Specialties
Section 10 00 00 - Electrical	
Section 11 00 00 - Mechanical	
Section 12 00 00 - Specialties	

CONCRETE PRODUCTS GROUP

- a. ASTM C 33 Specification for Concrete Aggregates .
 - b. ASTM C 330 Specification for Lightweight Aggregates for Structural Concrete
 - c. ASTM C 331 Specification for Lightweight Aggregates for Concrete Masonry Units
 - d. ASTM C 90-06b Load bearing Concrete Masonry Units.
 - e. ASTM C 150-04 Portland Cement.
 - f. ASTM C 595 Specification for Blended Hydraulic Cements
 - g. ASTM C 618 Specification for Coal Fly Ash and Raw or Calcined Natural Pozzolan for Use in Concrete
 - h. ASTM C 989 Specification for Ground Granulated Blast-Furnace Slag for Use in Concrete and Mortars
 - i. ASTM C 1157 Performance Specification for Hydraulic Cement
 - j. ASTM C 1209 Terminology of Concrete Masonry Units and Related Units
 - k. ASTM C 1232 Terminology of Masonry
 - l. ASTM C 1314 Test Method for Compressive Strength of Masonry Prisms
3. Masonry Industry All-Weather Council (IMIAWC).
 - a. “Recommended Practices & Guide Specifications for Cold Weather Masonry Construction – 1993.
 4. National Concrete Masonry Association (NCMA).
 - a. TEK Manual for Concrete Masonry Design and Construction, TEK Bulletins.
 5. Sheet Metal and Air Conditioning Contractors National Association, Inc. (SMACNA):
 - a. SMACNA “Architect and Sheet Metal Manual - 2003.”

1.3 SUBMITTALS

- A. Product Data: Submit manufacturer’s product data for masonry units [water repellent admixture and masonry insulation.]
- B. Samples: Submit three full size units of each type/color of exposed architectural concrete masonry unit for review of color and texture. Provide the maximum color and texture variation range expected in the finished work.
- C. Certificates: Submit manufacturer’s certification that architectural concrete masonry units comply with specified requirements, including type, grade, curing, moisture content and performance requirements.
- D. Qualification Data: Submit qualification data demonstrating masonry installer’s capabilities and experience. Include list of completed projects with project names, addresses, telephone numbers, names of Architects and Owners, and other information as requested.

Table of Contents	
1.0 GENERAL	1.0
1.1 SUMMARY	1.1
1.2 REFERENCES	1.2
1.3 SUBMITTALS	1.3
1.4 INSTALLATION	1.4
1.5 MAINTENANCE	1.5
2.0 MATERIALS	2.0
2.1 MASONRY UNITS	2.1
2.2 MORTAR	2.2
2.3 WATER REPELLENT ADMIXTURE	2.3
2.4 MASONRY INSULATION	2.4
3.0 EXECUTION	3.0
3.1 PREPARATION	3.1
3.2 INSTALLATION	3.2
3.3 FINISHES	3.3
3.4 PROTECTION	3.4
3.5 MAINTENANCE	3.5
4.0 RELATED SECTIONS	4.0
4.1 CONCRETE	4.1
4.2 METALS	4.2
4.3 PAINTS AND COATINGS	4.3
4.4 GLASS	4.4
4.5 ROOFING	4.5
4.6 MECHANICAL	4.6
4.7 ELECTRICAL	4.7
4.8 PLUMBING	4.8
4.9 HEATING, VENTILATION AND AIR CONDITIONING	4.9
4.10 FINISHES	4.10
4.11 SPECIALTIES	4.11
5.0 APPENDICES	5.0
5.1 QUALIFICATION DATA	5.1
5.2 SAMPLES	5.2
5.3 PRODUCT DATA	5.3
5.4 CERTIFICATES	5.4
5.5 MAINTENANCE	5.5
5.6 RELATED SECTIONS	5.6
6.0 NOTES	6.0
6.1 GENERAL NOTES	6.1
6.2 MATERIALS	6.2
6.3 EXECUTION	6.3
6.4 RELATED SECTIONS	6.4
6.5 APPENDICES	6.5
6.6 NOTES	6.6
6.7 RELATED SECTIONS	6.7
6.8 APPENDICES	6.8
6.9 NOTES	6.9
6.10 RELATED SECTIONS	6.10
6.11 APPENDICES	6.11
6.12 NOTES	6.12
6.13 RELATED SECTIONS	6.13
6.14 APPENDICES	6.14
6.15 NOTES	6.15
6.16 RELATED SECTIONS	6.16
6.17 APPENDICES	6.17
6.18 NOTES	6.18
6.19 RELATED SECTIONS	6.19
6.20 APPENDICES	6.20
6.21 NOTES	6.21
6.22 RELATED SECTIONS	6.22
6.23 APPENDICES	6.23
6.24 NOTES	6.24
6.25 RELATED SECTIONS	6.25
6.26 APPENDICES	6.26
6.27 NOTES	6.27
6.28 RELATED SECTIONS	6.28
6.29 APPENDICES	6.29
6.30 NOTES	6.30
6.31 RELATED SECTIONS	6.31
6.32 APPENDICES	6.32
6.33 NOTES	6.33
6.34 RELATED SECTIONS	6.34
6.35 APPENDICES	6.35
6.36 NOTES	6.36
6.37 RELATED SECTIONS	6.37
6.38 APPENDICES	6.38
6.39 NOTES	6.39
6.40 RELATED SECTIONS	6.40
6.41 APPENDICES	6.41
6.42 NOTES	6.42
6.43 RELATED SECTIONS	6.43
6.44 APPENDICES	6.44
6.45 NOTES	6.45
6.46 RELATED SECTIONS	6.46
6.47 APPENDICES	6.47
6.48 NOTES	6.48
6.49 RELATED SECTIONS	6.49
6.50 APPENDICES	6.50
6.51 NOTES	6.51
6.52 RELATED SECTIONS	6.52
6.53 APPENDICES	6.53
6.54 NOTES	6.54
6.55 RELATED SECTIONS	6.55
6.56 APPENDICES	6.56
6.57 NOTES	6.57
6.58 RELATED SECTIONS	6.58
6.59 APPENDICES	6.59
6.60 NOTES	6.60
6.61 RELATED SECTIONS	6.61
6.62 APPENDICES	6.62
6.63 NOTES	6.63
6.64 RELATED SECTIONS	6.64
6.65 APPENDICES	6.65
6.66 NOTES	6.66
6.67 RELATED SECTIONS	6.67
6.68 APPENDICES	6.68
6.69 NOTES	6.69
6.70 RELATED SECTIONS	6.70
6.71 APPENDICES	6.71
6.72 NOTES	6.72
6.73 RELATED SECTIONS	6.73
6.74 APPENDICES	6.74
6.75 NOTES	6.75
6.76 RELATED SECTIONS	6.76
6.77 APPENDICES	6.77
6.78 NOTES	6.78
6.79 RELATED SECTIONS	6.79
6.80 APPENDICES	6.80
6.81 NOTES	6.81
6.82 RELATED SECTIONS	6.82
6.83 APPENDICES	6.83
6.84 NOTES	6.84
6.85 RELATED SECTIONS	6.85
6.86 APPENDICES	6.86
6.87 NOTES	6.87
6.88 RELATED SECTIONS	6.88
6.89 APPENDICES	6.89
6.90 NOTES	6.90
6.91 RELATED SECTIONS	6.91
6.92 APPENDICES	6.92
6.93 NOTES	6.93
6.94 RELATED SECTIONS	6.94
6.95 APPENDICES	6.95
6.96 NOTES	6.96
6.97 RELATED SECTIONS	6.97
6.98 APPENDICES	6.98
6.99 NOTES	6.99
6.100 RELATED SECTIONS	6.100

- E. Submit written plan for cold and hot weather construction and masonry cleaning procedures.

1.4 QUALITY ASSURANCE

- A. Unit masonry standards: Maintain one copy of the referenced masonry standards in project field office during construction.
 - 1. Building Code: ACI 530-05/ASCE 5-05/TMS 402-05 “Building Code Requirements for Masonry Structures”
 - 2. Specifications: ACI 530.1-05/ASCE 6-05/TMS 602-05 “Specification for Masonry Structures”
- B. Unit Masonry Producer Qualifications: A member in good standing of the National Concrete Masonry Association (NCMA).
- C. Integral Water Repellent Concrete Masonry Producer Qualifications: A firm certified in writing by water repellent manufacturer as a licensed or approved applicator.
- D. General: Appoint at least one experienced and skilled supervisory mason who shall be present at all times and direct work performed under this Section. Supervisor shall be thoroughly familiar with design requirements, type of materials being installed, referenced masonry standards, and other requirements.
 - 1. Use skilled masons for cutting and placing of architectural concrete unit masonry.
 - 2. Comply with applicable codes, regulations, and standards.
- E. Consult other trades and make provisions to permit installation of their work in a manner to avoid cutting and patching. Build in work specified under other Sections, as necessary, and as work progresses.
- F. Pre-Construction Conference: Before commencing masonry construction and associated work, meet at project site, or other mutually agreed location, with Installer, installers of related work, and other entities concerned with masonry performance, including (where applicable) Architect and Owner’s representative. Record discussions and agreements and furnish copy to each participant. Provide at least 72 hours’ advance notice to participants prior to convening pre-construction conference.
- G. Concrete unit masonry construction: Comply with National Concrete Masonry Association (NCMA) “TEK Bulletins,” and as specified.
 - 1. NCMA TEK Bulletin 3-1C “All Weather Concrete Masonry Construction.”
 - 2. NCMA TEK Bulletin 3-2A “Grouting for Concrete Masonry Walls.”
 - 3. NCMA TEK Bulletin 3-3A “Reinforced Concrete Masonry Construction.”
 - 4. NCMA TEK Bulletin 8-2A “Removal of Stains from Concrete Masonry Walls.”
 - 5. NCMA TEK Bulletin 10-1A “Crack Control in Concrete Masonry Walls.”
 - 6. NCMA TEK Bulletin 10-2B “Control Joints for Concrete Masonry Walls.”

1. Introduction	2. Project Information
3. General Notes	4. Materials
5. Construction Methods	6. Quality Assurance
7. Safety	8. Environmental Protection
9. Closeout	10. Appendix
11. Index	12. Revision History

CONCRETE PRODUCTS GROUP

7. NCMA TEK Bulletin 14-4A "Strength Design of Concrete Masonry."
8. NCMA TEK Bulletin 19-4A "Flashing Strategies for Concrete Masonry Walls."
9. NCMA TEK Bulletin 19-5A "Flashing Details for Concrete Masonry Walls."

H. Sample panels: Before starting masonry work build sample wall panel(s) for Architect's inspection and acceptance. Build panel(s) on a firm foundation, in location acceptable to the Architect. Panel(s) shall be L-shaped, with long side a minimum of 5'-4" long x 4'-0" high and with one corner return at least 2'-0" long. Construct sample panel(s) full thickness, installing wall reinforcement, anchors, ties and other requested accessories. Provide special features as directed for control joints. Panel(s) shall show color range and texture of masonry units, bond, mortar joints and workmanship.

1. Build sample panels for [each type of exposed unit masonry construction] [typical exterior wall] [typical interior wall] [typical exterior and interior walls]
2. Clean one-half of each sample panel using approved masonry cleaning materials and methods to represent final cleaning. Remaining one-half to remain without final cleaning for comparison purposes.
3. Retain sample panels during construction as a standard for judging completed masonry work. Do not alter, move, or destroy sample panels until work is completed or removal is authorized.

I. Provide each type of masonry unit from a single manufacturing source to ensure uniform texture and color for continuous and visually related items.

1.5 DELIVERY, STORAGE AND HANDLING

A. Deliver architectural concrete masonry units to the job site on wood pallets, [shrink wrapped with hard plastic cover on top of pallet] with manufacturer's recommended unit protective covers.

1. Inspect architectural concrete masonry units upon delivery to ensure color match with required materials and accepted sample mock-up panel.
2. Stack masonry units in a dry place off the ground on pallets or a prepared plank platform. Method of stacking shall be acceptable to the Architect. Protect with non-staining waterproof tarpaulin coverings arranged to allow air circulation around and above masonry units.

B. Exercise particular care in the storage, handling and installation of masonry units. Exposed architectural concrete unit masonry is utilized as a "finish material." Do not build soiled or damaged masonry units into the work.

1.6 PROJECT CONDITIONS

A. Do not use metal reinforcements or ties coated with loose rust or other coatings, including ice, which will reduce or destroy bond.

B. Protect partially completed architectural concrete masonry against weather damage and moisture at end

Table of Contents	
1.0 GENERAL NOTES	1.0
1.1 MATERIALS	1.1
1.2 CONSTRUCTION	1.2
1.3 FINISHES	1.3
1.4 PROTECTION	1.4
1.5 DELIVERY, STORAGE AND HANDLING	1.5
1.6 PROJECT CONDITIONS	1.6
2.0 SCHEDULE	2.0
3.0 QUALITY CONTROL	3.0
4.0 TESTING	4.0
5.0 MAINTENANCE	5.0
6.0 WARRANTY	6.0
7.0 SIGNATURES	7.0
8.0 APPENDICES	8.0
9.0 REFERENCES	9.0
10.0 INDEX	10.0

of each day or shutdown and when work is not in progress.

1. Cover tops of walls with a strong, waterproof, non-staining membrane. Extended membrane at least 2'-0" down both sides of walls and hold securely in place.
 2. Cover tops of walls with a prefabricated rigid PVC plastic channel shaped cap.
 3. Rotate and flip scaffolding boards each day to prevent mortar staining.
- C. Brace unsupported and newly-laid masonry walls. Maintain bracing in place until building structure provides permanent bracing.
- D. Cold Weather and Hot Weather Construction: Comply with ACI 530 and IMIAWC recommended practices and guide specifications for cold weather and hot weather masonry construction.
- E. Construction Tolerances: Comply with masonry construction tolerances as required by ACI 530.1.
- F. Load application after building masonry columns, piers or walls:
1. Apply uniform design floor or roof loading as per ACI 530.1-05/ASCE 6-05/TMS 602-05, 1.8 — Project conditions.
 2. Do not apply concentrated loads for at least three days.
- G. Stain Prevention: Prevent grout, mortar, and soil from staining the face of masonry to be left exposed or painted. Remove immediately any grout, mortar, and soil that comes in contact with such masonry.
1. Protect base of walls from rain-splashed mud and mortar splatter by means of coverings spread on ground and over wall surface.
 2. Protect sills, ledges, and projection from mortar splatter and dropping.
 3. Protect surfaces of windows and door frames; as well as similar products with painted and integral finishes from mortar splatter and dropping.
- H. Split masonry coursing at heads and sills of openings and cut concrete masonry coursing less than 4" in height not permitted.

PART 2 – PRODUCTS

2.1 ARCHITECTURAL CONCRETE MASONRY MATERIALS

- A. Aggregate: ASTM C33 normal weight aggregate.
1. Washed [_____] coarse aggregate and washed [_____] sand.

Table of Contents	
1.0 GENERAL	1.01 SUMMARY
1.02 REFERENCES	1.03 RELATED SECTIONS
2.0 MATERIALS	2.01 CONCRETE
2.02 MASONRY	2.03 MORTAR
2.04 GROUT	2.05 FINISHES
3.0 EXECUTION	3.01 PREPARATION
3.02 INSTALLATION	3.03 PROTECTION
3.04 MAINTENANCE	

CONCRETE PRODUCTS GROUP

- B. Cement: ASTM C 150, Type required.
 - 1. Color: White/Grey
- C. Water Repellent Admixture: Integral polymeric water repellent admixture for concrete masonry units used in masonry exposed to the exterior.
 - 1. Performance requirements:
 - a. Water resistance: ASTM E 514.
 - b. Flexural Bond Strength: Pass for full wall; ASTM E 72 or C 1072.
 - c. Fully dispersible in water.
- D. Color Pigments: Lightfast, alkali-resistant, weather-resistant natural or synthetic iron oxides manufactured specifically for use in concrete masonry units.
- E. Masonry Cleaning Materials: Standard-strength proprietary masonry cleaner designed for removing mortar/grout stains, efflorescence, and other new construction stains from new concrete masonry without discoloring or damaging masonry surfaces. Provide cleaning product expressly approved for intended use by cleaner manufacturer and manufacturer of concrete masonry units being cleaned.
 - 1. Single Wythe Masonry Sealing Materials: Provide cleaning material manufacturer's compatible masonry sealer coating for all single wythe concrete masonry exterior walls.

2.2 ARCHITECTURAL CONCRETE MASONRY UNITS

A. Architectural Concrete Masonry Units: "Spec-Brik™ WCT™" manufactured by a member of the Concrete Products Group, tel: (800) 789-0872, internet www.concreteproductsgroup.com. [manufactured by Midwest Products Group, Bridgeton, MO, www.kirchnerblock.com; Midwest Products Group, Kansas City, MO, www.midwestblock.com; Block USA, Birmingham, AL, www.blockusa.com; Block USA, Lawrenceville, GA, www.blockusa.com; Block USA – Golf Coast Division, Theodore, AL, www.blockusa.com; Oberfield's Inc., Delaware, OH, www.oberfields.com; Oberfield's LLC, Lima, OH, www.oberfields.com; Basalite Concrete Products, LLC, Dixon, CA, www.basalite.com; Basalite Concrete Products, LLC, Denver, CO, www.basalite.com; Amcon Block, St. Cloud, MN, www.amconblock.com; A. Jandris & Sons, Inc., Gardner, MA, www.ajandris.com; Orco Block Co., Inc., Stanton, CA, www.orco.com; Headwaters Construction Materials, Houston, TX, www.headwaters.com; Fizzano Bros. Concrete Products, Inc., Crum Lynne, PA, www.fizzano.com; Barnes & Cone, Syracuse, NY, www.barnesandcone.com; Allied Concrete Products. LLC, Chesapeake, VA, www.alliedconcreteusa.com.

- B. Spec-Brik® WCT™ Units
 - 1. Smooth exposed face normal weight architectural concrete masonry units with Water Control Technol-

Table of Contents	
SECTION 04 22 23	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 24	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 25	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 26	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 27	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 28	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 29	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 30	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 31	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 32	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 33	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 34	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 35	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 36	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 37	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 38	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 39	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 40	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 41	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 42	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 43	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 44	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 45	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 46	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 47	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 48	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 49	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 50	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 51	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 52	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 53	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 54	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 55	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 56	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 57	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 58	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 59	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 60	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 61	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 62	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 63	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 64	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 65	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 66	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 67	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 68	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 69	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 70	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 71	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 72	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 73	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 74	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 75	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 76	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 77	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 78	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 79	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 80	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 81	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 82	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 83	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 84	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 85	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 86	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 87	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 88	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 89	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 90	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 91	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 92	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 93	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 94	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 95	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 96	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 97	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 98	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 99	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 100	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK

ogy drainage zones meeting all ASTM C-90 testing requirements and containing integral mixed color pigments.

2. Size: Nominal 4" [8", 10", or 12"] width x 4" [8"] height x 16" [8"] length
3. Linear shrinkage: Not to exceed 0.065 percent, ASTM C426.
4. Color(s): Selected by Architect from manufacturer's standard colors/ Custom color(s) matching Architect's sample color.

C. Special shapes:

1. Provide closures, jamb units, headers, lintels, bond beams and other special shapes as indicated.
2. Provide standard manufactured sizes or cut full size units for fractional course height and lengths.
3. Provide two-core type masonry units where required to receive vertical reinforcing and grout/ masonry insulation.

D. Integral Water Repellent Concrete Masonry Units: Provide all exterior wall architectural concrete masonry units, including single wythe walls and facing units, manufactured by a qualified producer using normal weight aggregates that comply with ASTM C 33 and meet requirements of ASTM C 90, and contain the manufacturer's recommended amount of an integral polymeric water repellent admixture.

1. No other admixtures or additives shall be used with the integral water repellent masonry units, except with the written approval of the manufacturer and Architect.

E. Pre-Insulated Masonry Units: manufactured and distributed by Concrete Products Group.

1. Provide Korfill Hi R concrete masonry units factory insulated with individual molded expanded polystyrene inserts that comply with ASTM C 578, Standard Type 1, have a minimum density of 1.0 PCF and a maximum water vapor transmission rate of 1.4 perms.

2.3 MASONRY MORTAR AND ACCESSORIES

A. Mortar and grout: Comply with Section 04 05 15 requirements.

1. Water Repellent Mortar Admixture: Krete Industries "Admix-Krete Gard Mortar Mix"; Grace Construction Products "Admix-Dry Block"; ACM Chemistries "Admix-Rainbloc"; BASF Admixtures, Inc. "Admix-Rheopel"

a. Comply with manufacturer's instructions for mixing and mortar preparation.

B. Anchors, reinforcing and ties: Comply with Section 04 05 19 - Masonry Anchorage and Reinforcing requirements.

C. Flashing [, loose masonry fill insulation] and accessories: Comply with Section 04 05 23 requirements.

SECTION 04 05 15 MASONRY MORTAR AND ACCESSORIES	15
SECTION 04 05 19 MASONRY ANCHORAGE AND REINFORCING	19
SECTION 04 05 23 FLASHING AND ACCESSORIES	23
SECTION 04 05 24 MASONRY UNITS	24
SECTION 04 05 25 MASONRY JOINTS	25
SECTION 04 05 26 MASONRY FINISHES	26
SECTION 04 05 27 MASONRY COATINGS	27
SECTION 04 05 28 MASONRY CLEANING	28
SECTION 04 05 29 MASONRY PROTECTIVE COATINGS	29
SECTION 04 05 30 MASONRY REPAIRS	30
SECTION 04 05 31 MASONRY REPAIRS AND PATCHES	31
SECTION 04 05 32 MASONRY REPAIRS AND PATCHES	32
SECTION 04 05 33 MASONRY REPAIRS AND PATCHES	33
SECTION 04 05 34 MASONRY REPAIRS AND PATCHES	34
SECTION 04 05 35 MASONRY REPAIRS AND PATCHES	35
SECTION 04 05 36 MASONRY REPAIRS AND PATCHES	36
SECTION 04 05 37 MASONRY REPAIRS AND PATCHES	37
SECTION 04 05 38 MASONRY REPAIRS AND PATCHES	38
SECTION 04 05 39 MASONRY REPAIRS AND PATCHES	39
SECTION 04 05 40 MASONRY REPAIRS AND PATCHES	40
SECTION 04 05 41 MASONRY REPAIRS AND PATCHES	41
SECTION 04 05 42 MASONRY REPAIRS AND PATCHES	42
SECTION 04 05 43 MASONRY REPAIRS AND PATCHES	43
SECTION 04 05 44 MASONRY REPAIRS AND PATCHES	44
SECTION 04 05 45 MASONRY REPAIRS AND PATCHES	45
SECTION 04 05 46 MASONRY REPAIRS AND PATCHES	46
SECTION 04 05 47 MASONRY REPAIRS AND PATCHES	47
SECTION 04 05 48 MASONRY REPAIRS AND PATCHES	48
SECTION 04 05 49 MASONRY REPAIRS AND PATCHES	49
SECTION 04 05 50 MASONRY REPAIRS AND PATCHES	50
SECTION 04 05 51 MASONRY REPAIRS AND PATCHES	51
SECTION 04 05 52 MASONRY REPAIRS AND PATCHES	52
SECTION 04 05 53 MASONRY REPAIRS AND PATCHES	53
SECTION 04 05 54 MASONRY REPAIRS AND PATCHES	54
SECTION 04 05 55 MASONRY REPAIRS AND PATCHES	55
SECTION 04 05 56 MASONRY REPAIRS AND PATCHES	56
SECTION 04 05 57 MASONRY REPAIRS AND PATCHES	57
SECTION 04 05 58 MASONRY REPAIRS AND PATCHES	58
SECTION 04 05 59 MASONRY REPAIRS AND PATCHES	59
SECTION 04 05 60 MASONRY REPAIRS AND PATCHES	60
SECTION 04 05 61 MASONRY REPAIRS AND PATCHES	61
SECTION 04 05 62 MASONRY REPAIRS AND PATCHES	62
SECTION 04 05 63 MASONRY REPAIRS AND PATCHES	63
SECTION 04 05 64 MASONRY REPAIRS AND PATCHES	64
SECTION 04 05 65 MASONRY REPAIRS AND PATCHES	65
SECTION 04 05 66 MASONRY REPAIRS AND PATCHES	66
SECTION 04 05 67 MASONRY REPAIRS AND PATCHES	67
SECTION 04 05 68 MASONRY REPAIRS AND PATCHES	68
SECTION 04 05 69 MASONRY REPAIRS AND PATCHES	69
SECTION 04 05 70 MASONRY REPAIRS AND PATCHES	70
SECTION 04 05 71 MASONRY REPAIRS AND PATCHES	71
SECTION 04 05 72 MASONRY REPAIRS AND PATCHES	72
SECTION 04 05 73 MASONRY REPAIRS AND PATCHES	73
SECTION 04 05 74 MASONRY REPAIRS AND PATCHES	74
SECTION 04 05 75 MASONRY REPAIRS AND PATCHES	75
SECTION 04 05 76 MASONRY REPAIRS AND PATCHES	76
SECTION 04 05 77 MASONRY REPAIRS AND PATCHES	77
SECTION 04 05 78 MASONRY REPAIRS AND PATCHES	78
SECTION 04 05 79 MASONRY REPAIRS AND PATCHES	79
SECTION 04 05 80 MASONRY REPAIRS AND PATCHES	80
SECTION 04 05 81 MASONRY REPAIRS AND PATCHES	81
SECTION 04 05 82 MASONRY REPAIRS AND PATCHES	82
SECTION 04 05 83 MASONRY REPAIRS AND PATCHES	83
SECTION 04 05 84 MASONRY REPAIRS AND PATCHES	84
SECTION 04 05 85 MASONRY REPAIRS AND PATCHES	85
SECTION 04 05 86 MASONRY REPAIRS AND PATCHES	86
SECTION 04 05 87 MASONRY REPAIRS AND PATCHES	87
SECTION 04 05 88 MASONRY REPAIRS AND PATCHES	88
SECTION 04 05 89 MASONRY REPAIRS AND PATCHES	89
SECTION 04 05 90 MASONRY REPAIRS AND PATCHES	90
SECTION 04 05 91 MASONRY REPAIRS AND PATCHES	91
SECTION 04 05 92 MASONRY REPAIRS AND PATCHES	92
SECTION 04 05 93 MASONRY REPAIRS AND PATCHES	93
SECTION 04 05 94 MASONRY REPAIRS AND PATCHES	94
SECTION 04 05 95 MASONRY REPAIRS AND PATCHES	95
SECTION 04 05 96 MASONRY REPAIRS AND PATCHES	96
SECTION 04 05 97 MASONRY REPAIRS AND PATCHES	97
SECTION 04 05 98 MASONRY REPAIRS AND PATCHES	98
SECTION 04 05 99 MASONRY REPAIRS AND PATCHES	99
SECTION 04 05 100 MASONRY REPAIRS AND PATCHES	100

PART 3- EXECUTION

3.1 EXAMINATION

- A. Examine substrates, structure and installation conditions. Do not proceed with architectural concrete masonry work until unsatisfactory conditions have been corrected.
- B. Installation constitutes acceptance of existing conditions and responsibility for satisfactory performance.

3.2 PREPARATION

- A. Do not wet concrete masonry units.
- B. Establish lines, levels and coursing. Verify anchors and flashings are correctly located and installed.
- C. Coordinate masonry work with installation of _____ provided under Section _____ work. Build in _____ occurring within masonry walls as work progresses.

3.3 INSTALLATION

- A. Layout walls in advance for accurate spacing of surface bond patterns, with uniform joint widths and to properly locate openings, movement type joints, returns and offsets. Avoid the use of less than half-size units at corners, jambs and other locations.
- B. Lay up walls plumb and true to comply with specified tolerances. Provide square corners, except as otherwise indicated, with courses level, accurately spaced and coordinated with other work. Use double lines at multiple wythe walls.
- C. Pattern bond: Lay exposed concrete unit masonry in running bond with vertical joint in each course centered on units in courses above and below. Bond and interlock each course of each wythe at corners. Do not use units with less than 4" of horizontal face dimensions at corners or jambs.
 - 1. Install special shape units where indicated.
- D. Lay hollow concrete masonry units with full mortar coverage on horizontal and vertical face shells. Bed webs in mortar in starting course on footings, load bearing walls, all courses of piers, columns and pilasters and where adjacent to cells or cavities to be reinforced or filled with concrete or grout. Maintain 3/8" joint widths, except as necessary at base course bed joints, and except for minor variations required to maintain bond alignment.
- E. Lay solid concrete masonry units with completely filled bed and head joints; butter ends with sufficient

SECTION 04 22 23

ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK

Table of Contents	
SECTION 04 22 23	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 24	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 25	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 26	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 27	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 28	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 29	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 30	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 31	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 32	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 33	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 34	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 35	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 36	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 37	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 38	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 39	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 40	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 41	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 42	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 43	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 44	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 45	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 46	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 47	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 48	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 49	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 50	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 51	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 52	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 53	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 54	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 55	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 56	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 57	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 58	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 59	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 60	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 61	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 62	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 63	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 64	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 65	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 66	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 67	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 68	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 69	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 70	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 71	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 72	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 73	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 74	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 75	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 76	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 77	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 78	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 79	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 80	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 81	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 82	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 83	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 84	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 85	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 86	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 87	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 88	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 89	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 90	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 91	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 92	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 93	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 94	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 95	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 96	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 97	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 98	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 99	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK
SECTION 04 22 100	ARCHITECTURAL CONCRETE MASONRY - SPEC-BRIK

mortar to fill head joints and shove into place. Do not slush head joints.

- F. Compress and cut joints flush for masonry walls that are below grade, concealed or covered by other materials.
- G. Tool joints in all exposed masonry work to a concave joint, unless plans indicate otherwise
- H. Remove masonry units disturbed after laying; clean and reset in fresh mortar. Do not pound corners at jambs to fit stretcher units which have been set in position. If adjustments are required, remove units, clean off mortar and reset in fresh mortar.
- I. Step back unfinished work adjoining new work. Rack back 1/2 unit length in each course; do not tooth. Clean exposed surfaces of set masonry and remove loose masonry units and mortar before laying fresh masonry.
- J. Provide interlocking masonry bond in each course at corners and intersecting walls, unless otherwise indicated on plans such as for stack bond.
- K. Load-bearing walls: If carried up separately, provide rigid steel anchors spaced not more than 2'-0" on center vertically. Embed ends in mortar filled cores. : Build full height of story to underside of structure. Grout juncture with structure solid with grout.
- L. Nonload-bearing walls: Build full height of story to underside of structure, except as otherwise shown. Terminate full height nonload-bearing walls one joint thickness below the structure to allow for deflection of the structural element without loading the wall. Provide an open joint for application of joint sealant [firestopping].
- M. As the work progresses, build in items specified under this and other Sections of the specifications. Fill in solidly with masonry around built-in items.
 - 1. Bed hollow metal frame anchors in mortar. Align anchors with joint coursing. Draw anchors tight and fill space between hollow metal frames and masonry solid with fine mortar grout.
 - 2. Where built-in items are to be embedded in cores of hollow masonry units, place a layer of metal lath or other approved material, in the joint below and rod grout into core.
 - 3. Provide solid masonry bearing for all lintels, beams, joists, plates and load-bearing members.
 - a. Provide solid masonry units or hollow units filled solid.
 - b. Minimum one block course under steel angle lintels and steel joists not bearing on bond beams.
 - c. Minimum two block courses under steel beams and steel beam lintels. Where beams and lintels are parallel with wall, extend solid bearing to walls, extend solid bearing 16" each side of centerline of beam.

SECTION 05100 - MASONRY	1
05101 - Brickwork	1
05102 - Concrete Blockwork	1
05103 - Stone	1
05104 - Mortar	1
05105 - Masonry Joints	1
05106 - Masonry Reinforcement	1
05107 - Masonry Anchors	1
05108 - Masonry Lintels	1
05109 - Masonry Beams	1
05110 - Masonry Joists	1
05111 - Masonry Plates	1
05112 - Masonry Load-Bearing Members	1
05113 - Masonry Firestopping	1
05114 - Masonry Sealant	1
05115 - Masonry Repair	1
05116 - Masonry Protection	1
05117 - Masonry Cleaning	1
05118 - Masonry Painting	1
05119 - Masonry Grouting	1
05120 - Masonry Grout	1
05121 - Masonry Grout	1
05122 - Masonry Grout	1
05123 - Masonry Grout	1
05124 - Masonry Grout	1
05125 - Masonry Grout	1
05126 - Masonry Grout	1
05127 - Masonry Grout	1
05128 - Masonry Grout	1
05129 - Masonry Grout	1
05130 - Masonry Grout	1
05131 - Masonry Grout	1
05132 - Masonry Grout	1
05133 - Masonry Grout	1
05134 - Masonry Grout	1
05135 - Masonry Grout	1
05136 - Masonry Grout	1
05137 - Masonry Grout	1
05138 - Masonry Grout	1
05139 - Masonry Grout	1
05140 - Masonry Grout	1
05141 - Masonry Grout	1
05142 - Masonry Grout	1
05143 - Masonry Grout	1
05144 - Masonry Grout	1
05145 - Masonry Grout	1
05146 - Masonry Grout	1
05147 - Masonry Grout	1
05148 - Masonry Grout	1
05149 - Masonry Grout	1
05150 - Masonry Grout	1
05151 - Masonry Grout	1
05152 - Masonry Grout	1
05153 - Masonry Grout	1
05154 - Masonry Grout	1
05155 - Masonry Grout	1
05156 - Masonry Grout	1
05157 - Masonry Grout	1
05158 - Masonry Grout	1
05159 - Masonry Grout	1
05160 - Masonry Grout	1
05161 - Masonry Grout	1
05162 - Masonry Grout	1
05163 - Masonry Grout	1
05164 - Masonry Grout	1
05165 - Masonry Grout	1
05166 - Masonry Grout	1
05167 - Masonry Grout	1
05168 - Masonry Grout	1
05169 - Masonry Grout	1
05170 - Masonry Grout	1
05171 - Masonry Grout	1
05172 - Masonry Grout	1
05173 - Masonry Grout	1
05174 - Masonry Grout	1
05175 - Masonry Grout	1
05176 - Masonry Grout	1
05177 - Masonry Grout	1
05178 - Masonry Grout	1
05179 - Masonry Grout	1
05180 - Masonry Grout	1
05181 - Masonry Grout	1
05182 - Masonry Grout	1
05183 - Masonry Grout	1
05184 - Masonry Grout	1
05185 - Masonry Grout	1
05186 - Masonry Grout	1
05187 - Masonry Grout	1
05188 - Masonry Grout	1
05189 - Masonry Grout	1
05190 - Masonry Grout	1
05191 - Masonry Grout	1
05192 - Masonry Grout	1
05193 - Masonry Grout	1
05194 - Masonry Grout	1
05195 - Masonry Grout	1
05196 - Masonry Grout	1
05197 - Masonry Grout	1
05198 - Masonry Grout	1
05199 - Masonry Grout	1
05200 - Masonry Grout	1
05201 - Masonry Grout	1
05202 - Masonry Grout	1
05203 - Masonry Grout	1
05204 - Masonry Grout	1
05205 - Masonry Grout	1
05206 - Masonry Grout	1
05207 - Masonry Grout	1
05208 - Masonry Grout	1
05209 - Masonry Grout	1
05210 - Masonry Grout	1
05211 - Masonry Grout	1
05212 - Masonry Grout	1
05213 - Masonry Grout	1
05214 - Masonry Grout	1
05215 - Masonry Grout	1
05216 - Masonry Grout	1
05217 - Masonry Grout	1
05218 - Masonry Grout	1
05219 - Masonry Grout	1
05220 - Masonry Grout	1
05221 - Masonry Grout	1
05222 - Masonry Grout	1
05223 - Masonry Grout	1
05224 - Masonry Grout	1
05225 - Masonry Grout	1
05226 - Masonry Grout	1
05227 - Masonry Grout	1
05228 - Masonry Grout	1
05229 - Masonry Grout	1
05230 - Masonry Grout	1
05231 - Masonry Grout	1
05232 - Masonry Grout	1
05233 - Masonry Grout	1
05234 - Masonry Grout	1
05235 - Masonry Grout	1
05236 - Masonry Grout	1
05237 - Masonry Grout	1
05238 - Masonry Grout	1
05239 - Masonry Grout	1
05240 - Masonry Grout	1
05241 - Masonry Grout	1
05242 - Masonry Grout	1
05243 - Masonry Grout	1
05244 - Masonry Grout	1
05245 - Masonry Grout	1
05246 - Masonry Grout	1
05247 - Masonry Grout	1
05248 - Masonry Grout	1
05249 - Masonry Grout	1
05250 - Masonry Grout	1
05251 - Masonry Grout	1
05252 - Masonry Grout	1
05253 - Masonry Grout	1
05254 - Masonry Grout	1
05255 - Masonry Grout	1
05256 - Masonry Grout	1
05257 - Masonry Grout	1
05258 - Masonry Grout	1
05259 - Masonry Grout	1
05260 - Masonry Grout	1
05261 - Masonry Grout	1
05262 - Masonry Grout	1
05263 - Masonry Grout	1
05264 - Masonry Grout	1
05265 - Masonry Grout	1
05266 - Masonry Grout	1
05267 - Masonry Grout	1
05268 - Masonry Grout	1
05269 - Masonry Grout	1
05270 - Masonry Grout	1
05271 - Masonry Grout	1
05272 - Masonry Grout	1
05273 - Masonry Grout	1
05274 - Masonry Grout	1
05275 - Masonry Grout	1
05276 - Masonry Grout	1
05277 - Masonry Grout	1
05278 - Masonry Grout	1
05279 - Masonry Grout	1
05280 - Masonry Grout	1
05281 - Masonry Grout	1
05282 - Masonry Grout	1
05283 - Masonry Grout	1
05284 - Masonry Grout	1
05285 - Masonry Grout	1
05286 - Masonry Grout	1
05287 - Masonry Grout	1
05288 - Masonry Grout	1
05289 - Masonry Grout	1
05290 - Masonry Grout	1
05291 - Masonry Grout	1
05292 - Masonry Grout	1
05293 - Masonry Grout	1
05294 - Masonry Grout	1
05295 - Masonry Grout	1
05296 - Masonry Grout	1
05297 - Masonry Grout	1
05298 - Masonry Grout	1
05299 - Masonry Grout	1
05300 - Masonry Grout	1
05301 - Masonry Grout	1
05302 - Masonry Grout	1
05303 - Masonry Grout	1
05304 - Masonry Grout	1
05305 - Masonry Grout	1
05306 - Masonry Grout	1
05307 - Masonry Grout	1
05308 - Masonry Grout	1
05309 - Masonry Grout	1
05310 - Masonry Grout	1
05311 - Masonry Grout	1
05312 - Masonry Grout	1
05313 - Masonry Grout	1
05314 - Masonry Grout	1
05315 - Masonry Grout	1
05316 - Masonry Grout	1
05317 - Masonry Grout	1
05318 - Masonry Grout	1
05319 - Masonry Grout	1
05320 - Masonry Grout	1
05321 - Masonry Grout	1
05322 - Masonry Grout	1
05323 - Masonry Grout	1
05324 - Masonry Grout	1
05325 - Masonry Grout	1
05326 - Masonry Grout	1
05327 - Masonry Grout	1
05328 - Masonry Grout	1
05329 - Masonry Grout	1
05330 - Masonry Grout	1
05331 - Masonry Grout	1
05332 - Masonry Grout	1
05333 - Masonry Grout	1
05334 - Masonry Grout	1
05335 - Masonry Grout	1
05336 - Masonry Grout	1
05337 - Masonry Grout	1
05338 - Masonry Grout	1
05339 - Masonry Grout	1
05340 - Masonry Grout	1
05341 - Masonry Grout	1
05342 - Masonry Grout	1
05343 - Masonry Grout	1
05344 - Masonry Grout	1
05345 - Masonry Grout	1
05346 - Masonry Grout	1
05347 - Masonry Grout	1
05348 - Masonry Grout	1
05349 - Masonry Grout	1
05350 - Masonry Grout	1
05351 - Masonry Grout	1
05352 - Masonry Grout	1
05353 - Masonry Grout	1
05354 - Masonry Grout	1
05355 - Masonry Grout	1
05356 - Masonry Grout	1
05357 - Masonry Grout	1
05358 - Masonry Grout	1
05359 - Masonry Grout	1
05360 - Masonry Grout	1
05361 - Masonry Grout	1
05362 - Masonry Grout	1
05363 - Masonry Grout	1
05364 - Masonry Grout	1
05365 - Masonry Grout	1
05366 - Masonry Grout	1
05367 - Masonry Grout	1
05368 - Masonry Grout	1
05369 - Masonry Grout	1
05370 - Masonry Grout	1
05371 - Masonry Grout	1
05372 - Masonry Grout	1
05373 - Masonry Grout	1
05374 - Masonry Grout	1
05375 - Masonry Grout	1
05376 - Masonry Grout	1
05377 - Masonry Grout	1
05378 - Masonry Grout	1
05379 - Masonry Grout	1
05380 - Masonry Grout	1
05381 - Masonry Grout	1
05382 - Masonry Grout	1
05383 - Masonry Grout	1
05384 - Masonry Grout	1
05385 - Masonry Grout	1
05386 - Masonry Grout	1
05387 - Masonry Grout	1
05388 - Masonry Grout	1
05389 - Masonry Grout	1
05390 - Masonry Grout	1
05391 - Masonry Grout	1
05392 - Masonry Grout	1
05393 - Masonry Grout	1
05394 - Masonry Grout	1
05395 - Masonry Grout	1
05396 - Masonry Grout	1
05397 - Masonry Grout	1
05398 - Masonry Grout	1
05399 - Masonry Grout	1
05400 - Masonry Grout	1
05401 - Masonry Grout	1
05402 - Masonry Grout	1
05403 - Masonry Grout	1
05404 - Masonry Grout	1
05405 - Masonry Grout	1
05406 - Masonry Grout	1
05407 - Masonry Grout	1
05408 - Masonry Grout	1
05409 - Masonry Grout	1
05410 - Masonry Grout	1
05411 - Masonry Grout	1
05412 - Masonry Grout	1
05413 - Masonry Grout	1
05414 - Masonry Grout	1
05415 - Masonry Grout	1
05416 - Masonry Grout	1
05417 - Masonry Grout	1
05418 - Masonry Grout	1
05419 - Masonry Grout	1
05420 - Masonry Grout	1
05421 - Masonry Grout	1
05422 - Masonry Grout	1
05423 - Masonry Grout	1
05424 - Masonry Grout	1
05425 - Masonry Grout	1
05426 - Masonry Grout	1
05427 - Masonry Grout	1
05428 - Masonry Grout	1
05429 - Masonry Grout	1
05430 - Masonry Grout	1
05431 - Masonry Grout	1
05432 - Masonry Grout	1
05433 - Masonry Grout	1
05434 - Masonry Grout	1
05435 - Masonry Grout	1
05436 - Masonry Grout	1
05437 - Masonry Grout	1
05438 - Masonry Grout	1
05439 - Masonry Grout	1
05440 - Masonry Grout	1
05441 - Masonry Grout	1
05442 - Masonry Grout	1
05443 - Masonry Grout	1
05444 - Masonry Grout	1
05445 - Masonry Grout	1
05446 - Masonry Grout	1
05447 - Masonry Grout	1
05448 - Masonry Grout	1
05449 - Masonry Grout	1
05450 - Masonry Grout	1
05451 - Masonry Grout	1
05452 - Masonry Grout	1
05453 - Masonry Grout	1
05454 - Masonry Grout	1
05455 - Masonry Grout	1
05456 - Masonry Grout	1
05457 - Masonry Grout	1
05458 - Masonry Grout	1
05459 - Masonry Grout	1
05460 - Masonry Grout	1
05461 - Masonry Grout	1
05462 - Masonry Grout	1
05463 - Masonry Grout	1
05464 - Masonry Grout	1
05465 - Masonry Grout	1
05466 - Masonry Grout	1
05467 - Masonry Grout	1
05468 - Masonry Grout	1
05469 - Masonry Grout	1
05470 - Masonry Grout	1
05471 - Masonry Grout	1
05472 - Masonry Grout	1
05473 - Masonry Grout	1
05474 - Masonry Grout	1
05475 - Masonry Grout	1
05476 - Masonry Grout	1
05477 - Masonry Grout	1
05478 - Masonry Grout	1
05479 - Masonry Grout	1
05480 - Masonry Grout	1
05481 - Masonry Grout	1
05482 - Masonry Grout	1
05483 - Masonry Grout	1
05484 - Masonry Grout	1
05485 - Masonry Grout	1
05486 - Masonry Grout	1
05487 - Masonry Grout	1
05488 - Masonry Grout	1
05489 - Masonry Grout	1
05490 - Masonry Grout	1
05491 - Masonry Grout	1
05492 - Masonry Grout	1
05493 - Masonry Grout	1
05494 - Masonry Grout	1
05495 - Masonry Grout	1
05496 - Masonry Grout	1
05497 - Masonry Grout	1
05498 - Masonry Grout	1
05499 - Masonry Grout	1
05500 - Masonry Grout	1
05501 - Masonry Grout	1
05502 - Masonry Grout	1
05503 - Masonry Grout	1
05504 - Masonry Grout	1
05505 - Masonry Grout	1
05506 - Masonry Grout	1
05507 - Masonry Grout	1
05508 - Masonry Grout	1
05509 - Masonry Grout	1
05510 - Masonry Grout	1
05511 - Masonry Grout	1
05512 - Masonry Grout	1
05513 - Masonry Grout	1
05514 - Masonry Grout	1
05515 - Masonry Grout	1
05516 - Masonry Grout	1
05517 - Masonry Grout	1
05518 - Masonry Grout	1
05519 - Masonry Grout	1
05520 - Masonry Grout	1
05521 - Masonry Grout	1
05522 - Masonry Grout	1
05523 - Masonry Grout	1
05524 - Masonry Grout	1
05525 - Masonry Grout	1
05526 - Masonry Grout	1
05527 - Masonry Grout	1
05528 - Masonry Grout	1
05529 - Masonry Grout	1
05530 - Masonry Grout	1
05531 - Masonry Grout	1
05532 - Masonry Grout	1
05533 - Masonry Grout	1
05534 - Masonry Grout	1
05535 - Masonry Grout	1
05536 - Masonry Grout	1
05537 - Masonry Grout	1
05538 - Masonry Grout	1
05539 - Masonry Grout	1
05540 - Masonry Grout	1
05541 - Masonry Grout	1
05542 - Masonry Grout	1
05543 - Masonry Grout	1
05544 - Masonry Grout	1
05545 - Masonry Grout	1
05546 - Masonry Grout	1
05547 - Masonry Grout	1
05548 - Masonry Grout	1
05549 - Masonry Grout	1
05550 - Masonry Grout	1
05551 - Masonry Grout	1
05552 - Masonry Grout	1
05553 - Masonry Grout	1
05554 - Masonry Grout	1
05555 - Masonry Grout	1
05556 - Masonry Grout	1
05557 - Masonry Grout	1
05558 - Masonry Grout	1
05559 - Masonry Grout	1
05560 - Masonry Grout	1
05561 - Masonry Grout	1
05562 - Masonry Grout	1
05563 - Masonry Grout	1
05564 - Masonry Grout	1
05565 - Masonry Grout	1
05566 - Masonry Grout	1

1. In every second block course, 16" on center vertically, full height of wall and every block course where shown on the drawings.
 2. Unless horizontal reinforcement is to be placed within 16", in the first two bed joints immediately above and below all openings so that it extends a minimum of 24" beyond opening each way.
 3. Unless horizontal reinforcement is to be placed within 16", in the bed joints of the first and second courses below the bearing line in bearing walls when wall receives uniformly distributed floor or roof loads.
 4. In bed joints 16" below bond beams.
 5. In parapet walls 8" on center vertically, beginning at a point not less than 12" below the ceiling line of the heated space below the roof slab.
 6. Lap reinforcement a minimum of 6" and full width at corners and intersections or use special fabricated sections.
 7. Cut or interrupt joint reinforcement at vertical movement (control or expansion joints), unless otherwise indicated.
 8. Prefabricated metal joint reinforcement shall not be used as wall ties in multiple wythe walls, except for composite wall construction and two adjacent tiers of concrete block.
 9. Fully embed side rods in mortar
- S. Anchoring masonry work: Provide anchoring devices of the type shown and specified.
1. Anchor masonry to structural members where masonry abuts or faces such members to comply with the following:
 - a. Provide an open space not less than 1/2" width between masonry and structural member. Keep open space free of mortar or other rigid materials.
 - b. Anchor masonry to structural members with metal ties embedded in masonry joints and attached to the structure. Provide anchors with adjustable tie sections. Space anchors not more than 24" on center vertically and 36" on center horizontally.
 2. Anchor veneers to concrete structural members with dovetail anchors.
- T. Provide control joints for exterior masonry construction In accordance with NCMA-TEK Bulletins 10-1A and 10-2B. Provide sash blocks with premolded shear key. Rake out mortar, if any, and form continuous vertical joints in masonry construction to receive High Performance joint sealant at the locations listed below.
1. Locate control joints at points of natural weakness in masonry and at locations visually acceptable to the Architect.
- U. Install bond beams where indicated. Comply with drawing details for reinforcing steel size and spacing. Fill bond beam masonry units solid with concrete fill or coarse mortar grout.

Table of Contents	
1.0 Introduction	1.0
2.0 General Notes	2.0
3.0 Masonry	3.0
4.0 Concrete	4.0
5.0 Steel	5.0
6.0 Finishes	6.0
7.0 Windows and Doors	7.0
8.0 Mechanical	8.0
9.0 Electrical	9.0
10.0 Other	10.0
CONCRETE PRODUCTS GROUP	

V. Lintels:

1. Install loose steel lintels furnished under Section 05 12 00 Structural Steel Framing where shown. Set lintels in full bed of mortar.
2. Provide minimum bearing at each jamb of 4" for openings for less than 6'-0" and 8" for wider openings.

W. Flashing and weeps:

1. Install concealed through wall masonry flashing at all cavity and veneer wall sills, masonry openings in exterior walls with masonry above head, over all horizontal steel members built into masonry and elsewhere as indicated. Comply with SMACNA "Architectural Sheet Metal Manual" Chapter 4 Flashing recommendations and with NCMA TEK Bulletins 19-4A and 19-5A details to ensure water resistant masonry construction.
2. Install weeps in head joints of final course of exterior masonry wythe above flashing. Space weeps maximum of 24" on center horizontally with exterior ends and located to avoid door openings. Install weeps at head joints with outside face of weep material held 1/8" from the finish face of masonry unit.
3. Install cavity fill on top of base flashing. Install a bed of mortar, conforming to the curve of the flashing, placed under the metal flashing.
4. Install vents in head joints of final top course exterior masonry veneer wythe. Install at head joints with outside face of vent material held 1/8" from the finish face of masonry unit. Space vents 24" on center horizontally.
5. Install compressible joint material at lintels and horizontal steel members. Build in joint fillers and seal with High Performance elastomeric joint sealant.

3.4 REINFORCED CONCRETE MASONRY

A. Fill scheduled wall and column masonry work. Fill all cores solid with concrete fill/coarse masonry grout.

1. Grouting: Comply with ACI 530.1 grout placement requirements. Consolidate grout at time of placement.
 - a. Low-Lift Grouting: Place concrete fill/coarse masonry grout in maximum 5'-0" vertical lifts.
 - b. High-Lift Grouting: Place concrete fill/coarse masonry grout in maximum 12'-0" vertical lifts (Recommend the use of super plasticizer with hi-lift grout).
2. Recess top of grout fill minimum 1-1/2" below top of course to form a key with following lift.
3. Where vertical reinforcing is required, install reinforcing before filling operation. Comply with drawing details for reinforcing steel size and spacing.

B. Install bond beams where indicated. Install reinforcing before filling operation. Fill units solid with concrete fill. Comply with drawing details for reinforcing steel size and spacing.


Table of Contents	
SECTION 05 12 00	STRUCTURAL STEEL FRAMING
SECTION 05 12 01	STEEL FRAMING
SECTION 05 12 02	STEEL BRACING
SECTION 05 12 03	STEEL JOISTS
SECTION 05 12 04	STEEL DECKING
SECTION 05 12 05	STEEL PILING
SECTION 05 12 06	STEEL SHIELDING
SECTION 05 12 07	STEEL WALKWAYS
SECTION 05 12 08	STEEL LADDERS
SECTION 05 12 09	STEEL STAIRS
SECTION 05 12 10	STEEL ROOFING
SECTION 05 12 11	STEEL CLADDING
SECTION 05 12 12	STEEL LINING
SECTION 05 12 13	STEEL CURTAIN WALLS
SECTION 05 12 14	STEEL WINDOW WALLS
SECTION 05 12 15	STEEL DOOR WALLS
SECTION 05 12 16	STEEL SIGNAGE
SECTION 05 12 17	STEEL LIGHT FIXTURES
SECTION 05 12 18	STEEL VENTILATION
SECTION 05 12 19	STEEL EXHAUST
SECTION 05 12 20	STEEL FAN COILS
SECTION 05 12 21	STEEL RADIATORS
SECTION 05 12 22	STEEL HEAT EXCHANGERS
SECTION 05 12 23	STEEL CONDENSERS
SECTION 05 12 24	STEEL EVAPORATORS
SECTION 05 12 25	STEEL REFRIGERATORS
SECTION 05 12 26	STEEL AIR HANDLERS
SECTION 05 12 27	STEEL FAN COILS
SECTION 05 12 28	STEEL RADIATORS
SECTION 05 12 29	STEEL HEAT EXCHANGERS
SECTION 05 12 30	STEEL CONDENSERS
SECTION 05 12 31	STEEL EVAPORATORS
SECTION 05 12 32	STEEL REFRIGERATORS
SECTION 05 12 33	STEEL AIR HANDLERS
SECTION 05 12 34	STEEL FAN COILS
SECTION 05 12 35	STEEL RADIATORS
SECTION 05 12 36	STEEL HEAT EXCHANGERS
SECTION 05 12 37	STEEL CONDENSERS
SECTION 05 12 38	STEEL EVAPORATORS
SECTION 05 12 39	STEEL REFRIGERATORS
SECTION 05 12 40	STEEL AIR HANDLERS
SECTION 05 12 41	STEEL FAN COILS
SECTION 05 12 42	STEEL RADIATORS
SECTION 05 12 43	STEEL HEAT EXCHANGERS
SECTION 05 12 44	STEEL CONDENSERS
SECTION 05 12 45	STEEL EVAPORATORS
SECTION 05 12 46	STEEL REFRIGERATORS
SECTION 05 12 47	STEEL AIR HANDLERS
SECTION 05 12 48	STEEL FAN COILS
SECTION 05 12 49	STEEL RADIATORS
SECTION 05 12 50	STEEL HEAT EXCHANGERS
SECTION 05 12 51	STEEL CONDENSERS
SECTION 05 12 52	STEEL EVAPORATORS
SECTION 05 12 53	STEEL REFRIGERATORS
SECTION 05 12 54	STEEL AIR HANDLERS
SECTION 05 12 55	STEEL FAN COILS
SECTION 05 12 56	STEEL RADIATORS
SECTION 05 12 57	STEEL HEAT EXCHANGERS
SECTION 05 12 58	STEEL CONDENSERS
SECTION 05 12 59	STEEL EVAPORATORS
SECTION 05 12 60	STEEL REFRIGERATORS
SECTION 05 12 61	STEEL AIR HANDLERS
SECTION 05 12 62	STEEL FAN COILS
SECTION 05 12 63	STEEL RADIATORS
SECTION 05 12 64	STEEL HEAT EXCHANGERS
SECTION 05 12 65	STEEL CONDENSERS
SECTION 05 12 66	STEEL EVAPORATORS
SECTION 05 12 67	STEEL REFRIGERATORS
SECTION 05 12 68	STEEL AIR HANDLERS
SECTION 05 12 69	STEEL FAN COILS
SECTION 05 12 70	STEEL RADIATORS
SECTION 05 12 71	STEEL HEAT EXCHANGERS
SECTION 05 12 72	STEEL CONDENSERS
SECTION 05 12 73	STEEL EVAPORATORS
SECTION 05 12 74	STEEL REFRIGERATORS
SECTION 05 12 75	STEEL AIR HANDLERS
SECTION 05 12 76	STEEL FAN COILS
SECTION 05 12 77	STEEL RADIATORS
SECTION 05 12 78	STEEL HEAT EXCHANGERS
SECTION 05 12 79	STEEL CONDENSERS
SECTION 05 12 80	STEEL EVAPORATORS
SECTION 05 12 81	STEEL REFRIGERATORS
SECTION 05 12 82	STEEL AIR HANDLERS
SECTION 05 12 83	STEEL FAN COILS
SECTION 05 12 84	STEEL RADIATORS
SECTION 05 12 85	STEEL HEAT EXCHANGERS
SECTION 05 12 86	STEEL CONDENSERS
SECTION 05 12 87	STEEL EVAPORATORS
SECTION 05 12 88	STEEL REFRIGERATORS
SECTION 05 12 89	STEEL AIR HANDLERS
SECTION 05 12 90	STEEL FAN COILS
SECTION 05 12 91	STEEL RADIATORS
SECTION 05 12 92	STEEL HEAT EXCHANGERS
SECTION 05 12 93	STEEL CONDENSERS
SECTION 05 12 94	STEEL EVAPORATORS
SECTION 05 12 95	STEEL REFRIGERATORS
SECTION 05 12 96	STEEL AIR HANDLERS
SECTION 05 12 97	STEEL FAN COILS
SECTION 05 12 98	STEEL RADIATORS
SECTION 05 12 99	STEEL HEAT EXCHANGERS
SECTION 05 12 100	STEEL CONDENSERS
SECTION 05 12 101	STEEL EVAPORATORS
SECTION 05 12 102	STEEL REFRIGERATORS
SECTION 05 12 103	STEEL AIR HANDLERS
SECTION 05 12 104	STEEL FAN COILS
SECTION 05 12 105	STEEL RADIATORS
SECTION 05 12 106	STEEL HEAT EXCHANGERS
SECTION 05 12 107	STEEL CONDENSERS
SECTION 05 12 108	STEEL EVAPORATORS
SECTION 05 12 109	STEEL REFRIGERATORS
SECTION 05 12 110	STEEL AIR HANDLERS
SECTION 05 12 111	STEEL FAN COILS
SECTION 05 12 112	STEEL RADIATORS
SECTION 05 12 113	STEEL HEAT EXCHANGERS
SECTION 05 12 114	STEEL CONDENSERS
SECTION 05 12 115	STEEL EVAPORATORS
SECTION 05 12 116	STEEL REFRIGERATORS
SECTION 05 12 117	STEEL AIR HANDLERS
SECTION 05 12 118	STEEL FAN COILS
SECTION 05 12 119	STEEL RADIATORS
SECTION 05 12 120	STEEL HEAT EXCHANGERS
SECTION 05 12 121	STEEL CONDENSERS
SECTION 05 12 122	STEEL EVAPORATORS
SECTION 05 12 123	STEEL REFRIGERATORS
SECTION 05 12 124	STEEL AIR HANDLERS
SECTION 05 12 125	STEEL FAN COILS
SECTION 05 12 126	STEEL RADIATORS
SECTION 05 12 127	STEEL HEAT EXCHANGERS
SECTION 05 12 128	STEEL CONDENSERS
SECTION 05 12 129	STEEL EVAPORATORS
SECTION 05 12 130	STEEL REFRIGERATORS
SECTION 05 12 131	STEEL AIR HANDLERS
SECTION 05 12 132	STEEL FAN COILS
SECTION 05 12 133	STEEL RADIATORS
SECTION 05 12 134	STEEL HEAT EXCHANGERS
SECTION 05 12 135	STEEL CONDENSERS
SECTION 05 12 136	STEEL EVAPORATORS
SECTION 05 12 137	STEEL REFRIGERATORS
SECTION 05 12 138	STEEL AIR HANDLERS
SECTION 05 12 139	STEEL FAN COILS
SECTION 05 12 140	STEEL RADIATORS
SECTION 05 12 141	STEEL HEAT EXCHANGERS
SECTION 05 12 142	STEEL CONDENSERS
SECTION 05 12 143	STEEL EVAPORATORS
SECTION 05 12 144	STEEL REFRIGERATORS
SECTION 05 12 145	STEEL AIR HANDLERS
SECTION 05 12 146	STEEL FAN COILS
SECTION 05 12 147	STEEL RADIATORS
SECTION 05 12 148	STEEL HEAT EXCHANGERS
SECTION 05 12 149	STEEL CONDENSERS
SECTION 05 12 150	STEEL EVAPORATORS
SECTION 05 12 151	STEEL REFRIGERATORS
SECTION 05 12 152	STEEL AIR HANDLERS
SECTION 05 12 153	STEEL FAN COILS
SECTION 05 12 154	STEEL RADIATORS
SECTION 05 12 155	STEEL HEAT EXCHANGERS
SECTION 05 12 156	STEEL CONDENSERS
SECTION 05 12 157	STEEL EVAPORATORS
SECTION 05 12 158	STEEL REFRIGERATORS
SECTION 05 12 159	STEEL AIR HANDLERS
SECTION 05 12 160	STEEL FAN COILS
SECTION 05 12 161	STEEL RADIATORS
SECTION 05 12 162	STEEL HEAT EXCHANGERS
SECTION 05 12 163	STEEL CONDENSERS
SECTION 05 12 164	STEEL EVAPORATORS
SECTION 05 12 165	STEEL REFRIGERATORS
SECTION 05 12 166	STEEL AIR HANDLERS
SECTION 05 12 167	STEEL FAN COILS
SECTION 05 12 168	STEEL RADIATORS
SECTION 05 12 169	STEEL HEAT EXCHANGERS
SECTION 05 12 170	STEEL CONDENSERS
SECTION 05 12 171	STEEL EVAPORATORS
SECTION 05 12 172	STEEL REFRIGERATORS
SECTION 05 12 173	STEEL AIR HANDLERS
SECTION 05 12 174	STEEL FAN COILS
SECTION 05 12 175	STEEL RADIATORS
SECTION 05 12 176	STEEL HEAT EXCHANGERS
SECTION 05 12 177	STEEL CONDENSERS
SECTION 05 12 178	STEEL EVAPORATORS
SECTION 05 12 179	STEEL REFRIGERATORS
SECTION 05 12 180	STEEL AIR HANDLERS
SECTION 05 12 181	STEEL FAN COILS
SECTION 05 12 182	STEEL RADIATORS
SECTION 05 12 183	STEEL HEAT EXCHANGERS
SECTION 05 12 184	STEEL CONDENSERS
SECTION 05 12 185	STEEL EVAPORATORS
SECTION 05 12 186	STEEL REFRIGERATORS
SECTION 05 12 187	STEEL AIR HANDLERS
SECTION 05 12 188	STEEL FAN COILS
SECTION 05 12 189	STEEL RADIATORS
SECTION 05 12 190	STEEL HEAT EXCHANGERS
SECTION 05 12 191	STEEL CONDENSERS
SECTION 05 12 192	STEEL EVAPORATORS
SECTION 05 12 193	STEEL REFRIGERATORS
SECTION 05 12 194	STEEL AIR HANDLERS
SECTION 05 12 195	STEEL FAN COILS
SECTION 05 12 196	STEEL RADIATORS
SECTION 05 12 197	STEEL HEAT EXCHANGERS
SECTION 05 12 198	STEEL CONDENSERS
SECTION 05 12 199	STEEL EVAPORATORS
SECTION 05 12 200	STEEL REFRIGERATORS



Color Selections Guide

Table of Contents	
Introduction	1
How to Use This Guide	2
Color Selections	3
Color Selections by Product Line	4
Color Selections by Project Type	5
Color Selections by Material	6
Color Selections by Finish	7
Color Selections by Application	8
Color Selections by Location	9
Color Selections by Climate	10
Color Selections by Budget	11
Color Selections by Maintenance	12
Color Selections by Durability	13
Color Selections by Aesthetics	14
Color Selections by Functionality	15
Color Selections by Safety	16
Color Selections by Compliance	17
Color Selections by Sustainability	18
Color Selections by Innovation	19
Color Selections by Customization	20
Color Selections by Branding	21
Color Selections by Marketing	22
Color Selections by Customer Satisfaction	23
Color Selections by Industry Trends	24
Color Selections by Future Outlook	25

Click on any Color to see detail view



Birmingham Blend



Chesapeake Blend



Delaware Blend



Dixon Blend



Gardner Blend



Houston Blend



Jefferson City Blend



Panama City Blend



Philadelphia Blend



St. Cloud Blend




Stanton Blend



Syracuse Blend

These are digital renderings of CPG colors, and appearance will vary depending on screen and/or printer color calibrations. CPG recommends obtaining physical samples for color selections and building a sample panel for color review prior to construction to assure accurate representation of desired color selections





Birmingham Blend

These are digital renderings of CPG colors, and appearance will vary depending on screen and/or printer color calibrations. CPG recommends obtaining physical samples for color selections and building a sample panel for color review prior to construction to assure accurate representation of desired color selections



Table of Contents	
Introduction	1
Product Lineup	2
Color Selections	3
Texture Options	4
Application Methods	5
Installation Guidelines	6
Maintenance	7
FAQ	8
Contact Us	9




Chesapeake Blend

These are digital renderings of CPG colors, and appearance will vary depending on screen and/or printer color calibrations. CPG recommends obtaining physical samples for color selections and building a sample panel for color review prior to construction to assure accurate representation of desired color selections



Table of Contents	
Introduction	1
Product Overview	2
Color Selection Process	3
Sample Panel Construction	4
Color Review and Approval	5
Installation Guidelines	6
Quality Control	7
Warranty Information	8
Contact Us	9



Delaware Blend

These are digital renderings of CPG colors, and appearance will vary depending on screen and/or printer color calibrations. CPG recommends obtaining physical samples for color selections and building a sample panel for color review prior to construction to assure accurate representation of desired color selections



Table of Contents	
Introduction	1
Product Overview	2
Color Selection Process	3
Sample Panel Construction	4
Color Review and Approval	5
Installation Guidelines	6
Quality Assurance	7
Technical Specifications	8
Ordering Information	9
Contact Us	10



Dixon Blend

These are digital renderings of CPG colors, and appearance will vary depending on screen and/or printer color calibrations. CPG recommends obtaining physical samples for color selections and building a sample panel for color review prior to construction to assure accurate representation of desired color selections





Table of Contents	
Introduction	1
Product Overview	2
Color Selection Process	3
Application Guidelines	4
Technical Specifications	5
Quality Assurance	6
Customer Support	7
Index	8




Panama City Blend

These are digital renderings of CPG colors, and appearance will vary depending on screen and/or printer color calibrations. CPG recommends obtaining physical samples for color selections and building a sample panel for color review prior to construction to assure accurate representation of desired color selections



Table of Contents	
Introduction	Section 1: Introduction
1.1 Project Overview	Section 2: Project Overview
1.2 Objectives	Section 3: Objectives
1.3 Scope of Work	Section 4: Scope of Work
1.4 Key Deliverables	Section 5: Key Deliverables
2.0 Design Requirements	Section 6: Design Requirements
2.1 Aesthetic Requirements	Section 7: Aesthetic Requirements
2.2 Performance Requirements	Section 8: Performance Requirements
2.3 Sustainability Requirements	Section 9: Sustainability Requirements
2.4 Safety Requirements	Section 10: Safety Requirements
3.0 Material Selection	Section 11: Material Selection
3.1 Concrete Color Selection	Section 12: Concrete Color Selection
3.2 Aggregate Selection	Section 13: Aggregate Selection
3.3 Admixture Selection	Section 14: Admixture Selection
3.4 Formwork Selection	Section 15: Formwork Selection
3.5 Curing Compound Selection	Section 16: Curing Compound Selection
3.6 Sealant Selection	Section 17: Sealant Selection
3.7 Maintenance Selection	Section 18: Maintenance Selection
4.0 Construction Methods	Section 19: Construction Methods
4.1 Formwork Installation	Section 20: Formwork Installation
4.2 Concrete Placement	Section 21: Concrete Placement
4.3 Curing and Protection	Section 22: Curing and Protection
4.4 Finishing and Sealing	Section 23: Finishing and Sealing
4.5 Maintenance and Repair	Section 24: Maintenance and Repair
5.0 Quality Assurance	Section 25: Quality Assurance
5.1 Inspection and Testing	Section 26: Inspection and Testing
5.2 Documentation	Section 27: Documentation
5.3 Reporting	Section 28: Reporting
6.0 Conclusion	Section 29: Conclusion
6.1 Summary	Section 30: Summary
6.2 Recommendations	Section 31: Recommendations
6.3 Next Steps	Section 32: Next Steps



Philadelphia Blend

These are digital renderings of CPG colors, and appearance will vary depending on screen and/or printer color calibrations. CPG recommends obtaining physical samples for color selections and building a sample panel for color review prior to construction to assure accurate representation of desired color selections





Table of Contents	
Introduction	1
Product Overview	2
Color Selection Process	3
Sample Panel Construction	4
Color Review and Approval	5
Installation Guidelines	6
Quality Control	7
Warranty Information	8
Contact Us	9




St. Cloud Blend

These are digital renderings of CPG colors, and appearance will vary depending on screen and/or printer color calibrations. CPG recommends obtaining physical samples for color selections and building a sample panel for color review prior to construction to assure accurate representation of desired color selections



Table of Contents	
Introduction	1
Product Overview	2
Color Selection Process	3
Color Matching and Calibration	4
Sample Panel Construction	5
Color Review and Approval	6
Construction Guidelines	7
Quality Control and Assurance	8
Conclusion	9




Stanton Blend

These are digital renderings of CPG colors, and appearance will vary depending on screen and/or printer color calibrations. CPG recommends obtaining physical samples for color selections and building a sample panel for color review prior to construction to assure accurate representation of desired color selections



Table of Contents	
Introduction	1
Product Overview	2
Color Selection Process	3
Sample Panel Construction	4
Color Review and Approval	5
Construction Guidelines	6
Quality Control	7
Warranty Information	8
Contact Us	9



Syracuse Blend

These are digital renderings of CPG colors, and appearance will vary depending on screen and/or printer color calibrations. CPG recommends obtaining physical samples for color selections and building a sample panel for color review prior to construction to assure accurate representation of desired color selections




Table of Contents	
Introduction	1
Product Overview	2
Color Selection Process	3
Sample Panel Construction	4
Color Review and Approval	5
Construction Guidelines	6
Quality Control	7
Warranty and Support	8
Contact Information	9
Appendix A: Color Chart	10
Appendix B: Technical Specifications	11
Appendix C: Project Case Studies	12
Appendix D: Glossary	13
Appendix E: Index	14

Solutions Available Nationwide

The Concrete Products Group LLC (CPG) consists of regional market leaders in the concrete products industry. The CPG is organized to provide consistent, top-quality products to regional and national customers. Our products are produced with consistent specifications and production expertise.



Manufacturing Locations



A-1 BLOCK
1617 South Division
Avenue
Orlando, FL 32805

A. JANDRIS & SONS
202 High St.
Gardner, MA
01440

**ALLIED CONCRETE
PRODUCTS LLC**
3900 Shannon St.
Chesapeake, VA
23323-1054

AMCON BLOCK
P.O. Box 546
2211 Hwy 10 South
St. Cloud, MN
56302-0546

BARNES & CONE
P.O. Box 280
5894 Court St. Rd.
Syracuse, NY
13206-0280

**BASALITE
CONCRETE
PRODUCTS LLC**
605 Industrial Way
Dixon, CA
95620

BLOCK USA
2567 Ruffner Road
Birmingham, Alabama
35210

**FIZZANO BROTHERS
CONCRETE
PRODUCTS, INC.**
1776 Chester Pike
Crum Lynne, PA
19022-1299

**HEADWATERS
CONSTRUCTION
MATERIALS**
7620 Washington Ave.
Houston, TX
77007

**JOHNSON
CONCRETE
COMPANY**
217 Klumac Road
Salisbury, NC 28144

**MIDWEST
PRODUCTS GROUP**
12901 St. Charles Rock
Rd.
Bridgeton, MO
63044-2485

OBERFIELDS, LLC
P.O. Box 362
528 London Rd.
Delaware, OH
43015

ORCO BLOCK CO., INC.
11100 Beach Blvd.
Stanton, CA
90680-0129

www.concreteproductsgroup.com

800-789-0872

Copyright 2016, Concrete Products Group LLC